



Date: 09.09.2021

No. BMM/ENV/2021-22/043

To.
Environmental Officer
KSPCB Regional Office.
Sy No 597P. Ward No 15.
4th Main Near Dr Vishnuvardhana Park,
Kuvempunagara.
Ballari-583104

. Dear Sir.

Sub: Submission of Monthly Environmental monitoring report of M/s. BMM Ispat Ltd.

Danapura Village. Hospet Taluk, Bellary District-reg.

With respect to the above subject, we here by submitting the Stage-I Monthly Environmental monitoring report for the month of August-2021. The monitoring was carried out as per the CFO issued from your kind office

Combined Consent Order No. AW-303323 dated 08 08 2017 (Renewed & Valid up to 30.06 2022)

Thanking You,

Yours faithfully, for M/s BMM Ispat Ltd.

Authorized Signatory

Enclosure: Monitoring report for BMM Stage-I for the month of August-2021.

BMM ispat its Registered Office's Works: (14 Danapu: Village Hissapete - 553 222 Ballan District Karnataka India 1 +91 99723 09413 / 417 f +91 80 3072 3604

BMM ispat Ltd. Corporate Office: 101 1st Floor Pride Elite: 10, Museum Road, Beogalum: 550 001 Karnataka India 1 -91 80 4149 5660 - 1731 -91 80 4149 5664









S 9001 7015

150 14001 2011

15/5/45001 0016

# **BMM ISPATLTD**



# **ENVIRONMENTAL MONITORING REPORT**



Danapur Village, Hospet Taluk, Vijayanagara District, PIN-583222, Karnataka.

Stage - I

**AUGUST -2021** 

Prepared by



# GLOBAL ENVIRONMENT & MINING SERVICES

NABL & MOEF RECOGNIZED LABORATORY

(Consulting Engineers, Mine Designers, Geologists & Surveyors) 3<sup>rd</sup> main road, Basaveswara badavane

HOSAPETE - 583201, Dist., Ballari (Karnataka)

Tel

: 08394 229433 & 295018

e-mail Website : gems\_hpt@yahoo.com : www.globalmining.in

**STAGE-I** 

**PREFACE** 

The industries should monitor environmental parameters as per the frequency and

locations given in the CFE/CFO. And the same should be submitted on every month to the

respective pollution control board.

As part of the conditions and inherent concern on health of the employees and

surroundings M/s. BMM Ispat Ltd., as appointed M/s. Global Environment & Mining Services,

HOSPET, to carry out the environmental pollution monitoring on AAQ Monitoring, Fugitive

monitoring, Noise Monitoring, Water Analysis & Stack monitoring pollution and submit the

same to the Pollution Control Board.

Accordingly, M/s. Global Environment & Mining Services, HOSPET, carried out the pollution

monitoring as per the standard sampling methods prescribed by CPCB, for AAQ Monitoring,

Fugitive monitoring within the plant, Stack monitoring & Personal Dust Sampling as per the

CFO. These monitoring has been carried out in a frequency as mentioned in the CFO and the

same report is being submitted to the Board.

We sincerely thank to officials of M/s. BMM Ispat Ltd., for their valuable co-ordination &

support during the sampling and reporting.

for GLOBAL Environment & Mining Services

Place: Hosapete Date: 03.09.2021

(Managing Partner)

# 1.0 <u>INTRODUCTION</u>

M/s. BMM Ispat Ltd, (BMMIL) is a 2.0 million tons integrated steel plant, manufacturing steel with its state of art in advanced technology and protecting environment. It is committed produce quality product, in environmentally friendly technology. Adopting sufficient air pollution control equipment's, recycling and reusing all the water with 'Zero' discharge facility, generating valuable electric power with waste heat recovery boilers (WHRB) and resource optimizing and minimizing the energy needs through re-utilizing char for CFBC boilers.

M/s. BMM ISPAT Ltd., Presently operating the following units under Stage-I units (Manufacturing units coming under 2.0 MTPA integrated steel plant is monitored and are reported separately);

Sl.No.	Units	Capacity
1	Beneficiation Plant	1.3 MTPA
2	Pellet Plant	1.2 MTPA
3	Sponge Iron Division -1	2 x 100 TPD
4	Induction furnace (billets)	9000 tons/month
5	Rolling Mill (TMT rods)	9000 tons/month
6	Captive Power Plant	25 MW

The report includes environmental monitoring data collected at above site and its surrounding areas, for the month of **AUGUST-2021**. The Parameters monitored are:

- Ambient air quality
- Fugitive dust level
- Stack emission
- Ambient Noise Level
- Water quality



### 2.0 SCOPE AND METHODOLOGY

### 2.1 PREAMBLE

The scope of the study and the present report covers the detailed characterization of the existing environmental status in and around the plant area for major environmental components viz. Ambient & work zone air quality, Fugitive Emission, Noise level and water quality & Stack Emission.

# 2.2 AMBIENT AIR QUALITY

To assess the ambient air quality status, monitoring stations were identified 6 Location plant site. Work zone air monitoring stations were identified in the major work spots. Based on the production activities the parameters chosen for Ambient air quality. were Particulate Matter PM10, Particulate Matter (size less than  $2.5\mu m$ ) PM2.5.

# 2.2.1 PARTICULATE MATTER (PM10) (size less than 10μm).

# **Purpose**

The purpose of this protocol is to provide guidelines for monitoring and analysis of Particulate Matter PM10 in ambient air

**Reference Method:** IS 5182 Part 23 Method of Measurement of Air Pollution: Respirable Suspended Particulate Matter (PM10) cyclonic flow technique.

# Principle of the method

Air is drawn through a size-selective inlet and through a 20.3 X 25.4 cm (8 X 10 in) filter at a flow rate, which is typically 1132 L/min. Particles with aerodynamic diameter less than the cut-point of the inlet are collected, by the filter. The mass of these particles is determined by the difference in filter weights prior to and after sampling. The concentration of PM10 in the designated size range is calculated by dividing the weight gain of the filter by the volume of air sampled.

### Sampling

Field Sampling - Tilt back the inlet and secure it according to manufacturer's instructions. Loosen the faceplate wing nuts and remove the faceplate. Remove the filter from its jacket and center it on the support screen with the rough side of the filter facing upwards. Replace the faceplate and tighten the wing nuts to secure the rubber gasket against the filter edge. Gently lower the inlet. For automatically flow-controlled units, record the designated flow rate on the data sheet. Record the reading



of the elapsed time meter. The specified length of sampling is commonly 8 hours or 24 hours. During this period, several reading (hourly) of flow rate should be taken. After the required time of sampling, record the flow meter reading, take out the filter media from the sampler, and put in a container or envelope.

### **Analysis**

**Filter inspection:** Inspect the filter for pin holes using a light table. Loose particles should be removed with a soft brush. Apply the filter identification number or a code to the filter if it is not a numbered. Condition the filter in conditioning room maintained within 20-30° C and 40-50% relative humidity or in an airtight desiccator for 24 hours. Take initial weight of the filter paper (Wi) before sampling. Condition the filter after sampling in conditioning room maintained within 20-30° C and 40-50% relative humidity or in an airtight desiccator for 24 hours. Take final weight of the filter paper (Wf).

# 2.2.2 Particulate Matter (PM2.5) (size less than 2.5μm).

### **Purpose**

The purpose of this protocol is to provide guidelines for monitoring and analysis of Particulate Matter PM2.5 in ambient air.

**Reference Method:** USEPA 2001 Method of Measurement of Air Pollution: Particulate Matter (PM2.5) cyclonic flow technique.

### **Principle**

An electrically powered air sampler draws ambient air at a constant volumetric flow rate (16.7 lpm) maintained by a mass flow / volumetric flow controller coupled to a microprocessor into specially designed inertial particle-size separator (i.e., cyclones or impactors) where the suspended particulate matter in the PM2.5 size ranges is separated for collection on a 47 mm polytetrafluoroethylene (PTFE) filter over a specified sampling period. Each filter is weighed before and after sample collection to determine the net gain due to the particulate matter. The mass concentration in the ambient air is computed as the total mass of collected particles in the PM2.5 size ranges divided by the actual volume of air sampled, and is expressed in  $\mu g/m^3$ . The microprocessor reads averages and stores five-minute averages of ambient temperature, ambient pressure, filter temperature and volumetric flow rate. In addition, the microprocessor calculates the average temperatures and pressure, total



volumetric flow for the entire sample run time and the coefficient of variation of the flow rate.

# 2.2.3 Sulphur Dioxide (SO2).

**Purpose:** The purpose of this protocol is to provide guidelines for monitoring and analysis of Sulphur dioxide in ambient air.

**Reference Method:** Modified West & Gaeke Method (IS 5182 Part 2 Method of Measurement of Air Pollution: Sulphur dioxide).

Sulphur dioxide from air is absorbed in a solution of potassium tetra chloromercurate (TCM). A dichloro sulphitomercurate complex, which resists oxidation by the oxygen in the air, is formed. Once formed, this complex is stable to strong oxidants such as ozone and oxides of nitrogen and therefore, the absorber solution may be stored for some time prior to analysis. The complex is made to react with para-rosaniline and formaldehyde to form the intensely coloured pararosaniline methyl sulphonic acid. The absorbance of the solution is measured by means of a suitable spectrophotometer.

# Sampling

Place 30 ml of absorbing solution in an impinger and sample for four hours at the flow rate of 1 L/min. After sampling measure the volume of sample and transfer to a sample storage bottle.

# **Analysis**

Replace any water lost by evaporation during sampling by adding distilled water up to the calibration mark on the absorber. Mix thoroughly, pipette out 10 ml of the collected sample into a 25 ml volumetric flask. Add 1 ml 0.6% sulphamic acid and allow reacting for 10 minutes to destroy the nitrite resulting from oxides of nitrogen. Add 2 ml of 0.2% formaldehyde solution and 2 ml pararosaniline solution and make up to 25 ml with distilled water. Prepare a blank in the same manner using 10 ml of unexposed absorbing reagent. After a 30 min colour development interval and before 60 minutes, measure and record the absorbance of samples and reagent blank at 560 nm. Use distilled water; not the reagent blank, as the optical reference.

# 2.2.4 Nitrogen Di Oxide ( $NO_2$ ):

### **Purpose**

The purpose of this protocol is to provide guidelines for monitoring of nitrogen dioxide in ambient.



# Principle of the method

Modified Jacobs & Hochheiser Method (IS 5182 Part 6 Methods for Measurement of Air Pollution: Oxides of nitrogen)

Ambient nitrogen dioxide (NO2) is collected by bubbling air through a solution of sodium hydroxide and sodium arsenite. The concentration of nitrite ion (NO2) produced during sampling is determined calorimetrically by reacting the nitrite ion with phosphoric acid, sulfanilamide, and N-(1-naphthyl)- ethylenediamine dihydrochloride (NEDA) and measuring the absorbance of the highly coloured azo-dye at 540 nm.

# 2.2.5 Ozone (Chemical method)

# **Purpose**

The purpose of this protocol is to provide guidelines for monitoring of ozone in ambient air.

# Principle of the method

Micro-amounts of ozone and the oxidants liberate iodine when absorbed in a 1% solution of potassium iodine buffered at pH 6.8 + 0.2. The iodine is determined spectrophotometrically by measuring the absorption of tri-iodide ion at 352 nm.

### Sampling

Place 10 ml of absorbing solution in a standard impinger and sample for one hour at the flow rate of 1 L/min. Do not expose the absorbing reagent to direct sunlight. After sampling measure the volume of sample and transfer to a sample storage bottle.

### **Analysis**

If, appreciable evaporation of the absorbing solution occurs during sampling, add water to bring the liquid volume to 10 ml. Within 30 to 60 minutes after sample collection, read the absorbance in a cuvette at 352 nm against a reference cuvette containing distilled water. Measure the absorbance of the unexposed reagent and subtract the value from the absorbance of the sample.

# 2.2.6 **Ammonia (NH3)**

### **Purpose**

The purpose of this protocol is to provide guidelines for monitoring of ammonia in ambient air.



# Principle of the method

Indophenol method Ammonia in the atmosphere is collected by bubbling a measured volume of air through a dilute solution of sulphuric acid to form ammonium sulphate. The ammonium sulphate formed in the sample is analyzed calorimetrically by reaction with phenol and alkaline sodium hypochlorite to produce indophenol. The reaction is accelerated by the addition of Sodium Nitroprusside as catalyst.

# Sampling

Place 10 ml of absorbing solution in an impinger and sample for one hour at the flow rate of 1 to 2 L/min. After sampling measure the volume of sample and transfer to a sample storage bottle

# **Analysis**

Transfer contents of the sample bottle to a 25 ml glass stopper graduated cylinder. Maintain all the solutions and sample at 25° C. Add 2 ml buffer. Add 5 ml of working phenol solution, mix, and fill to about 22 ml. Add 2.5 ml of working hypochlorite solution and rapidly mix. Dilute to 25 ml, mix and store in the dark for 30 minutes to develop colour. Measure the absorbance of the solution at 630 nm on a spectrophotometer using 1 cm cells. Prepare a reagent blank and field blank and measure the absorbance as done in the analysis of samples.

# 2.2.7 Benzo(a)Pyrene

### **Purpose**

The purpose of this protocol is to provide guidelines for monitoring of Benzo (a) Pyrene (BaP) in ambient air.

# Principle of the Method

It is based on BIS method IS 5182 (Part 12):2004 and USEPA method (T0-13). This method is designed to collect particulate phase PAHs in ambient air and fugitive emissions and to determine individual PAH compounds using capillary gas chromatograph equipped with flame ionization detector. It is a high volume (1.2m3/min) sampling method capable of detecting sub.ng/m3 concentration of PAH in 24 hours sample (i.e., collected in 3 shifts of 8 hour each with 480 m3 sampling volume of air)



### Sampling

24 hr. sampling using PM10 high volume sampler with 8 hourly samples using EPM 2000 glass fibre or equivalent filter.

# **Sample Processing**

**Extraction:** Filter papers (half of all the filters papers collected in a day) are cut into strips using scissors and transfer to 250 ml beaker. Add  $\sim$ 50 ml. of Toluene (GC/HPLC grade). These samples are extracted with toluene using ultra sonic bath for about 30 minutes. Repeat the procedure twice (50ml x 2 times) for complete extraction. Alternatively, sample can be extracted using Soxhlet extraction apparatus for about 8 hr. with Toluene and repeat it twice.

### **Filtration**

Filter the extracted samples with Whatman filter paper no.41 containing 2 gm of Anhydrous Sodium Sulphate (to remove moisture).

# Sample injection

Take  $2\mu l$  of sample from the amber vial using standard gas tight syringe and inject in the Capillary GC-FID instrument for analysis. Record the resulting concentration of each PAH compound including B(a)P. A  $10ng/\mu l$  concentration B(a)P or other PAH standards are to be injected in GC/FID instrument with every batch of samples. As a control Internal Standard of  $10~ng/\mu l$  conc. is added to each sample prior to the analysis in case of internal calibration is used.

### 2.2.8 Benzene

Samples collected through active sampling (sorbent tubes) are extracted or desorbed by conventional solvent (generally 1-5 ml of carbon disulphide) using ultrasonication for 15 min to remove analyte from the sorbent material. Desorbed samples are analyzed using gas chromatograph (GC) fitted with capillary column and flame ionization detector (FID). A single tube may provide enough samples to permit several analyses.

# Principle of the Method

IS 5182 (Part 11): 2006, The charcoal tubes are available in different sizes and contain varying amount of activated charcoal. The ambient air is sucked through the tube using a low flow sampler used for collection of BTX sample in a way that results in an enrichment of the relevant substances in the activated charcoal. Desorption of the



adsorbed benzene is done using carbon disulphide (CS2). The substances desorbed in the CS2 are analyzed by capillary gas chromatography. A flame ionization detector (FID) is used for analysis while quantification is performed using the internal/external standard.

# **Gas Chromatograph**

Any suitable gas chromatograph with flame ionization detector (FlO) with fused silica capillary columns having a length of 25 m or more, an internal diameter of 320 11m or below and with a stationary phase film thickness less than 1.5 11m as follows or equivalent may be recommended.

### Sampling

Selection of Sorbent Tube '- Samples are collected in glass sampling tube filled with a activated charcoal (coconut shell), Chromo sorb 106 or other suitable adsorbent.

# **Analytical Procedure**

Samples collected through active sampling (sorbent tubes) are extracted or desorbed by conventional solvent (generally 1-5 ml of carbon disulphide) using ultrasonication for 15 min to remove analyte from the sorbent material. Desorbed samples are analyzed using gas chromatograph (GC) fitted with capillary column and flame ionization detector (FID). A single tube may provide enough samples to permit several analyses.

### 2.2.9 Carbon Monoxide (CO)

### Principle:

Samples containing carbon monoxide in the range of 0 to 100 mg/l are analyzed on a non-dispersive infrared absorption gas analyser, namely, an electro-optical spectrophotometer with no spectral dispersion component. It may consist of a single or double source of infrared energy and one or more infrared detectors separated by an optical cell or cells through one or more of which the sample flows, whereby the specific spectral absorption of the component of interest is determined.

# Non dispersive Infrared (NDIR) Gas Analyser

The apparatus shall be constructed so as to be sutiable for operating within the temperature range of 15°C to 40°C and in a relative humidity range of 0 to 90 percent. The apparatus shall embody facilities for the analysis of continuously applied sample or a discrete sample of volume of 2.0 litres. In the later case the purification train shall



be of such a design and dead volume that 2.0 litres is adequate for its proper flushing out. The apparatus shall include facilities for the visual inspection of results and also for their recording. The scale shall be divided into steps of 1.0 percent full scale division (fsd).

Though the basic instrument recommended is for (0 to 100) mg/l range, for samples of higher mg/l range the instrument may be used with proper dilution and conditioning of the samples.

# 2.2.10 Lead (Pb), Nickel (Ni) & Arsenic (As)

### **Purpose**

The purpose of this protocol is to provide guidelines for monitoring of Lead (Pb), Nickel (Ni) & Arsenic (As) in ambient air.

# Principle of the method

The Atomic Absorption Spectroscopy (AAS) technique makes use of absorption spectrometry to assess the concentration of an analyte in the sample. The method is based on active sampling using PM10 Respirable Dust Sampler and then sample analysis is done by atomic absorption spectrophotometer.

### Sampling procedure

Tilt back the inlet and secure it according to manufacturer's instructions. Loosen the face-plate wing-nuts and remove the face plate. Remove the filter from its jacket and centre it on the support screen with the rough side of the filter facing upwards. Replace the face-plate and tighten the wing-nuts to secure the rubber gasket against the filter edge. Gently lower the inlet. For automatically flow-controlled units, record the designated flow rate on the data sheet. Record the reading of the elapsed time meter. The specified length of sampling is commonly 8 hours or 24 hours. During this period, several reading (hourly) of flow rate should be taken. After the required time of sampling, record the flow meter reading and take out the filter media from the sampler and put in a container or envelope.

# 2.3 NOISE LEVELS

# **Measuring Equipment**

The measurements should be made with a sound level meter as specified in IS:9779-1981 The A-weighting network and fast response should be used. The sound level should be measured at the place and time of the annoyance.



### **Conditions of Measurement**

Ambient and work zone Noise level measurement was carried out using a sound level meter (Equinox-107) during day and night times. The measurements were carried out 1 m away from the source and 1 m away from the edge of the roads.

Outdoor measurements should be made at I.2 to I-5 m above the ground and, if practical, at least 3.5 m from walls, buildings or other sound reflecting structures. When circumstances indicate, measurements may be made at greater heights and closer to the wall (for example 0-5 m in front of an open window), provided this is specified and taken into consideration.

Indoor measurements should be made at a distance of at least 1 m from the walls, l-2 to 1.5 m above the floor, and about 1.5 m from the window(s). In order to reduce disturbances from standing waves, the sound levels measured indoors should be averaged over f 0-5 m of each of at least 3 positions. This is especially important when measuring low-frequency noise. The arithmetic average of the readings determines the value to be taken.

The statistical analysis can be based on analogue or digital recordings of the sound level. For estimating purposes, it may in some cases be sufficient to determine the statistical distribution by observing the sound level meter readings at intervals of time by a sampling technique,

The class intervals for the sound level must be chosen according to the character of the noise; in most cases an interval of 5 dB will be appropriate.

# 2.4 WATER SAMPLING

# **Collection and Preservation of Samples**

Collection and preservation of water and wastewater samples; the general principles also apply to the sampling of solids or semisolid matrices.

Ensure that all sampling equipment is clean and quality-assured before use. Use sample containers that are clean and free of contaminants. Bake at 450°C all bottles to be used for organic analysis sampling.

### Record of sample shall be as follows:

### **General** information

- Sample identification number
- Location
- Sample collector



- Date and hour
- Sample type (Grab or composite)

# **Collection of Samples**

### **Ground Water:**

**Grab samples:** Grab samples are single collected at a specific spot at a site over a short period of time (typically seconds or minutes).

### surface water:

**Composite Sampling:** Composite samples vertically over the depth of a water body in one location or horizontally along a specific water depth.

# Sewage treatment plant water.

**Integrated Sampling:** For certain purposes, the information needed is best provided by analyzing mixtures of grab samples collected from different points simultaneously.

# 2.5 <u>Fugitive Emission Monitoring</u>

Fugitive air quality was monitored 36 samples were collected from the analyzed for SPM analyzed by gravimetric method. Work Zone Air quality was monitored at all Plant area, and material handling area.

# 2.6 Stack Monitoring method

Stack Monitoring was Monitored 32 Samples Collected from Vayubodhan Stack sampler VSS 1 stack monitoring kit was used for drawing the flue gas. Sulphur dioxide and oxides of nitrogen in the flue gas were sampled by bubbling flue gas in 3% H2O2 and 0.1N NaOH solution respectively and the analysis of the pollutants were done as per the Indian standard procedures prescribed by CPCB/BIS. Stack emission level was monitored as per the statutory requirement on twice in a month.

### **Stack Emissions Monitoring Methodology**

### **Pre-Sampling Activities**

Weigh the properly conditioned thimble/filter and place it into the clean, air tight Container. Designate appropriate label or ID No. to each thimble/filter container. Particulate matter emission of "Stack Monitoring – Material and Methodology for is kinetic Sampling.



Field activity starts with the collection of detailed information from the industry about the products, raw materials, fuels, and stack dimensions.

# **Traverse Point Calculation**

Calculate the traverse point and accordingly mark the distance from tip of the Nozzle, on Pitot tube and probe. Do not forget to add the collar length of port to the calculated traverses. For detailed calculation of "Stack Monitoring– Material and Methodology for isokinetic sampling.

### **Determination of Dust Concentration**

Determine the mass of dust collected in the thimble by difference i.e., weighing the thimble before and after the run. Dry the thimble in an oven for about 2 hours at 120oC prior to sampling. After sampling, cool, dry and again weigh the thimble along with dust maintaining the same condition as prior to sampling.

# 2.7 DATA ANALYSIS

# 2.7.1 BUFFERZONE AMBIENT AIR QUALITY STATUS

### Danapur Village (A1)

At this location, average of PM10, PM2.5, SO2, NO2 values Average 62.74, 18.12, 9.01 &  $11.13 \mu g/m^3$  respectively. All above the values were found within the Limits. And the results given in **Annexure-1**.

# Mariyammanahalli Village (A2)

At this location, average of PM10, PM2.5, SO2, NO2values Average 59.10, 17.39, 7.58 &  $9.63 \mu g/m^3$  respectively. All above the values were found within the Limits. And the results given in **Annexure-2**.

### Hanumanahalli Village (A3)

At this location, average of PM10, PM2.5, SO2, NO2 values Average 55.16, 15.97, 7.50 &  $9.55~\mu g/m^3 respectively$ . All above the values were found within the Limits. results given in **Annexure-3**.

### Galemmanagudi Village (A4)

At this location, average of PM10, PM2.5, SO2, NO2 values Average 57.63, 16.25, 7.98 &  $9.85~\mu g/m3$  respectively. All above the values were found within the Limits. results given in **Annexure-4**.



### Gunda Village (A5)

At this location, average of PM10, PM2.5, SO2, NO2 values Average 50.56, 14.70, 7.06 &  $8.98 \mu g/m3$  respectively. All above the values were found within the Limits. results given in **Annexure-5.** 

# **Gunda Tanda Village (A6)**

At this location, average of PM10, PM2.5, SO2, NO2 values Average 53.71, 15.47, 6.94 &  $8.85~\mu g/m3$  respectively. All above the values were found within the Limits. results given in **Annexure-6.** 

# 2.8 FUGITIVE DUST CONCENTRATION

Fortnightly fugitive air quality was monitored all plant area SPM value minimum 293.96  $\mu$ g/m3, maximum value 1630.09  $\mu$ g/m3, and average value 753.89  $\mu$ g/m3. The Fugitive air quality 1<sup>st</sup> & 2<sup>nd</sup> Fortnight Results given in **Annexure-7 & Annexure-8**.

### 2.9 STACK MONITORING

Stack emission level was monitored as per the statutory requirement on twice in month. Stack emission level was monitored all chimneys' PM values (mg/Nm3) 1st and 2nd Fort Night Minimum Value 37.70 mg/Nm3, Maximum Value 60.40 mg/Nm3 & Average Value 44.24 mg/Nm3. The Stack Emission Results given in **Annexure-9 & Annexure-19**.

### 3.0 AMBIENT NOISE LEVEL MEASUREMENT

Noise level was recorded at 30 locations each in Ambient and work zone area using Sound Level Meter (Equinox -EQ 107 Instrument / SL-4001) The Day & Night time noise level values were ranging between 49.2 to 72.2 dB (A) and 47.9 to 65.1 dB (A). The noise level status is given in **Annexure-20 & Annexure-21**.

3.1 Water Sample Collected at 18 locations in side plant and surrounding nearest villages and nearest surface water Sample Collected every Month. The Water Analysis Test Report is given in Annexure-22 & Annexure-28.

### 3.2 CONCLUSION

All the monitored Environmental parameters were found to be well within the statutory norms and the same are enclosed as follows.



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

: +918394 229433, 295018

e-mail Website

: gems\_hpt@yahoo.com : www.globalmining.in

BMM STAGE-I

ANNEXURE-01 GEMS-LD/TF/11/01

# ANALYSIS REPORT OF AMBIENT AIR QUALITY DATA

Name of the Industry

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

**Customer Reference** 

WO/ADMIN/FY22/RO38

Sample collected by

Global Environment & Mining Services

Discipline

Chemical

Group

: Atmospheric Pollution

Sample Type

: Ambient Air Quality Monitoring

Particulars of Sample Collected

Respirable Dust Sampler, FPS Sampler

August-2021

03.09.2021

Location

A1-Danapur Village

**Duration of Monitoring** 

: 24 Hour

Report Issued Date Report Number

ULR-TC532321000000644F

### RESULTS

					OULIU	-			NAME OF TAXABLE PARTY.	
I	Parameters		PM: [μg/1		PM [μg/		SO [μg/	Services .	1000	0 <sub>2</sub> ′m³]
	Reference Method		IS:5182: 2006 USEPA 2001 (Part-23) Gravimetric (RF-2017) Method		IS:5182: 2001 (Part-2) (RF-2017)		IS :5182: (Part-6) 2006 (RF-2017)			
Date of Sampling	Date of Received Sample	Sample Code	Result	STD	Result	STD	Result	STD	Result	STD
02.08.2021	03.08.2021	2083	57.12		17.01		8.46		10.37	
03.08.2021	04.08.2021	2098	63.9		18.45		9.12		11.54	
09.08.2021	10.08.2021	2178	60.34		16.99		8.91		10.83	
10.08.2021	11.08.2021	2204	67.56		19.37		10.24		12.31	
16.08.2021	17.08.2021	2330	55.71	100	15.83	60	7.18	80	9.67	80
17.08.2021	18.08.2021	2353	61.28		17.65		7.92		10.13	
23.08.2021	24.08.2021	2486	70.13		21.14		10.75		12.72	
24.08.2021	25.08.2021	2498	65.85		18.49	]	9.47		11.49	
	Average		62.74		18.12		9.01		11.13	

**INFERENCE** 

As per NAAQMS Standards (2009),

Report Status: - Measured Values for the above parameters are within the limit.

**Analysed By** J. M. Thippeswamy Chemist

S Shameem Banu Senior chemist

The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.
This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing.

Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

The tests results marked with \* Recognised by MOEF & CC



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

: +918394 229433, 295018 : gems\_hpt@yahoo.com

e-mail Website

: www.globalmining.in

BMM STAGE-I

**ANNEXURE-02** GEMS-LD/TF/11/01

# ANALYSIS REPORT OF AMBIENT AIR QUALITY DATA

Name of the Industry

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

**Customer Reference** 

WO/ADMIN/FY22/RO38

Sample collected by

Global Environment & Mining Services

Discipline

Chemical

Group

Atmospheric Pollution

Sample Type

Ambient Air Quality Monitoring

Particulars of Sample Collected

Respirable Dust Sampler, FPS Sampler

Month

August-2021

Location

A2 -Mariyammana halli Village

**Duration of Monitoring** Report Issued Date

24 Hour 03.09.2021

Report Number

ULR-TC532321000000645F

### RESULTS

]	Parameters		PM <sub>1</sub> [μg/n	The same of the sa	PM [μg/	I <sub>2.5</sub> ′m³]	SO <sub>2</sub> [μg/n		NO <sub>2</sub> [μg/m³]	
	Reference Method		IS:5182: 2006 USEPA 2001 (Part-23) Gravimetric (RF-2017) Method		IS:5182: 2001 (Part-2) (RF-2017)		IS:5182: (Part-6) 2006 (RF-2017)			
Date of Sampling	Date of Received Sample	Sample Code	Result	STD	Result	STD	Result	STD	Result	STD
02.08.2021	03.08.2021	2084	62.18		18.34		8.27		10.43	
03.08.2021	04.08.2021	2099	58.63		16.91		7.12		9.34	
09.08.2021	10.08.2021	2179	49.79		14.65		6.69		8.72	
10.08.2021	11.08.2021	2205	56.14		15.87		7.34		9.49	
16.08.2021	17.08.2021	2331	64.82	100	19.23	60	8.56	80	10.21	80
17.08.2021	18.08.2021	2354	57.46		17.15		7.49		9.67	
23.08.2021	24.08.2021	2487	59.91		16.93		7.12		9.08	
24.08.2021	25.08.2021	2499	63.84		20.06		8.04		10.13	
	Average		59.10		17.39		7.58		9.63	

**INFERENCE** 

As per NAAQMS Standards (2009),

Report Status: - Measured Values for the above parameters are within the limit.

**Analysed By** J. M. Thippeswamy Chemist

S Shameem Banu Senior chemist

The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute artsing out of this report is subject to Hosapete jurisdiction only.

The tests results marked with \* Recognised by MOEF & CC

Recognised by Ministry of Environment, Forest and Climate Change for Laboratory

Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

: +918394 229433, 295018 : gems\_hpt@yahoo.com

e-mail Website

: www.globalmining.in

**BMM STAGE-I** 

**ANNEXURE-03** GEMS-LD/TF/11/01

# ANALYSIS REPORT OF AMBIENT AIR QUALITY DATA

Name of the Industry

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

**Customer Reference** 

WO/ADMIN/FY22/RO38

Sample collected by

**Global Environment & Mining Services** 

Discipline

Chemical

Group

Atmospheric Pollution

Sample Type

**Ambient Air Quality Monitoring** 

Particulars of Sample Collected

Respirable Dust Sampler, FPS Sampler

Month

August-2021

Location

A3 -Hanumanahalli Village

**Duration of Monitoring Report Issued Date** 

24 Hour 03.09.2021 :

Report Number

ULR-TC532321000000646F

### RESULTS

I	Parameters		PM <sub>10</sub> [μg/m³] IS:5182: 2006		[μg/1	PM <sub>2.5</sub> [μg/m <sup>3</sup> ]		2 m³]	NO <sub>2</sub> [μg/m³]	
Reference Method			IS:5182 (Part- (RF-20	23)	USEPA Gravim Meth	etric	IS:5182 (Part (RF-20	-2)	IS :5: (Part-6 (RF-2	2006
Date of Sampling	Date of Received Sample	Sample Code	Result	STD	Result	STD	Result	STD	Result	STD
02.08.2021	03.08.2021	2085	59.15		17.14		8.04		10.83	
03.08.2021	04.08.2021	2100	53.74		15.66		7.49		9.67	
09.08.2021	10.08.2021	2180	58.61		16.27		7.92		10.04	
10.08.2021	11.08.2021	2206	62.56		18.34		8.91		11.21	
16.08.2021	17.08.2021	2332	54.82	100	15.53	60	6.87	80	8.46	80
17.08.2021	18.08.2021	2355	46.79		13.75		6.54		8.12	
23.08.2021	24.08.2021	2488	55.46		16.38		7.18		9.35	
24.08.2021	25.08.2021	2500	50.17		14.71	]	7.02		8.72	
	Average		55.16		15.97		7.50		9.55	

**INFERENCE** 

As per NAAQMS Standards (2009),

Report Status: - Measured Values for the above parameters are within the limit.

**Analysed By** J. M. Thippeswamy Chemist

S Shameem Banu Senior chemist



The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.


This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute artsing out of this report is subject to Hosapete jurisdiction only.

The tests results marked with \* Recognised by MOEF & CC

Recognised by Ministry of Environment, Forest and Climate Change for Laboratory

Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey

1. 2. 3. 4. 5.



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

Ph

: +918394 229433, 295018

e-mail

: gems\_hpt@yahoo.com

Website

: www.globalmining.in

**BMM STAGE-I** 

**ANNEXURE-04** GEMS-LD/TF/11/01

### **ANALYSIS REPORT OF AMBIENT AIR QUALITY DATA**

Name of the Industry

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

**Customer Reference** 

WO/ADMIN/FY22/RO38

Sample collected by

**Global Environment & Mining Services** 

Discipline

Chemical

Group

Atmospheric Pollution

Sample Type

Ambient Air Quality Monitoring

Particulars of Sample Collected

Respirable Dust Sampler, FPS Sampler

Month

August-2021

Location

A4-Galemmanagudi Village

**Duration of Monitoring** 

24 Hour

Report Issue Date Report Number

03.09.2021

ULR-TC532321000000657F RESULTS

	Parameters  Reference  Method		PM <sub>10</sub> [μg/m <sup>3</sup> ] IS:5182: 2006 (Part-23) (RF-2017)		PM <sub>2.5</sub> [μg/m³] USEPA 2001 Gravimetric Method		SO <sub>2</sub> [μg/m <sup>3</sup> ] IS:5182: 2001 (Part-2)		NO <sub>2</sub> [μg/m <sup>3</sup> ] IS :5182: (Part-6) 2006	
Date of Sampling	Date of Received Sample	Sample Code	(RF-2 Result	STD	Metl Result	STD	(RF-2	017) STD	(RF-2	STD
05.08.2021 06.08.2021 12.08.2021 13.08.2021 19.08.2021 20.08.2021 26.08.2021 27.08.2021	06.08.2021 07.08.2021 13.08.2021 14.08.2021 20.08.2021 27.08.2021 28.08.2021 Average	2130 2159 2253 2268 2410 2459 2517 2534	64.08 57.36 52.71 55.92 61.25 56.67 52.34 60.68 57.63	100	17.56 16.27 14.93 15.75 17.62 15.89 14.73 17.21 16.25	60	9.13 8.56 7.92 7.69 8.27 7.34 6.91 8.04 7.98	80	11.25 10.43 9.49 9.08 10.24 9.67 8.43 10.21 9.85	80

INFERENCE | As per NAAQMS Standards (2009),

Report Status: - Measured Values for the above parameters are within the limit.

**Analysed By** J. M. Thippeswamy Chemist

S Shameem Banu Senior chemist

The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute artsing out of this report is subject to Hosapete jurisdiction only.

The tests results marked with \* Recognised by MOEF & CC

Recognised by Ministry of Enginement, Forest and Climate Change for Laboratory.



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

Ph

: +918394 229433, 295018 : gems\_hpt@yahoo.com

e-mail Website

: www.globalmining.in

**BMM STAGE-I** 

**ANNEXURE-05** GEMS-LD/TF/11/01

# **ANALYSIS REPORT OF AMBIENT AIR QUALITY DATA**

Name of the Industry

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

**Customer Reference** 

WO/ADMIN/FY22/RO38

Sample collected by

Global Environment & Mining Services

Discipline

: Chemical

Group

Atmospheric Pollution

Sample Type

**Ambient Air Quality Monitoring** 

Particulars of Sample Collected

Respirable Dust Sampler, FPS Sampler

Month

August-2021

Location

**A5-Gunda Village** 

**Duration of Monitoring** Report Issue Date

24 Hour 03.09.2021

Report Number

ULR-TC532321000000658F

### RESULTS

I	Parameters		PM1 [μg/n	Accesses to the second	PM: [μg/		SO2 [μg/m3]		NO2 [μg/m3]	
	Reference Method		IS:5182: 2006 USEPA 2001 (Part-23) Gravimetric (RF-2017) Method		IS:5182: 2001 (Part-2) (RF-2017)		IS :5182: (Part-6) 2006 (RF-2017)			
Date of Sampling	Date of Received Sample	Sample Code	Result	STD	Result	STD	Result	STD	Result	STD
05.08.2021	06.08.2021	2131	49.76		14.27		6.94		8.46	
06.08.2021	07.08.2021	2160	45.31	]	13.12		6.37		8.12	
12.08.2021	13.08.2021	2254	56.64		16.34		7.69		9.35	
13.08.2021	14.08.2021	2269	52.22		14.95		6.81		8.72	
19.08.2021	20.08.2021	2411	43.49	100	12.63	60	6.12	80	7.93	80
20.08.2021	21.08.2021	2460	47.85	1	14.01		7.05		9.14	
26.08.2021	27.08.2021	2518	51.63		15.22		7.26		9.67	
27.08.2021	28.08.2021	2535	57.61		17.05	1	8.27		10.43	
	Average		50.56		14.70		7.06		8.98	

INFERENCE

As per NAAQMS Standards (2009),

Report Status: - Measured Values for the above parameters are within the limit.

**Analysed By** J. M. Thippeswamy

Chemist

S Shameem Banu Senior chemist

The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.
This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing.

Total liability of our laboratory is limited to the Involce amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

The tests results marked with \* Recognised by MOEF & CC



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

Ph

: +918394 229433, 295018 : gems\_hpt@yahoo.com

e-mail Website

: www.globalmining.in

**BMM STAGE-I** 

**ANNEXURE-06** GEMS-LD/TF/11/01

# **ANALYSIS REPORT OF AMBIENT AIR QUALITY DATA**

Name of the Industry

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

**Customer Reference** 

WO/ADMIN/FY22/RO38

Sample collected by

**Global Environment & Mining Services** 

Discipline

Chemical

Group

Atmospheric Pollution

Sample Type

**Ambient Air Quality Monitoring** 

Particulars of Sample Collected

Respirable Dust Sampler, FPS Sampler

Month Location August-2021

**Duration of Monitoring** 

A6-Gunda Tanda Village 24 Hour

Report Issue Date

03.09.2021

Report Number

ULR-TC532321000000659F

RESULTS

	Parameters		PM [μg/۱		PM [μg/1		SO <sub>2</sub> [μg/m³]		NO <sub>2</sub> [μg/m³]	
	Reference Method				Gravin	USEPA 2001 Gravimetric Method		IS:5182: 2001 (Part-2) (RF-2017)		182: ) 2006 017)
Date of Sampling	Date of Received Sample	Sample Code	Result	STD	Result	STD	Result	STD	Result	STD
05.08.2021	06.08.2021	2132	54.63		15.42		6.37		8.12	
06.08.2021	07.08.2021	2161	49.17		14.21		6.12		7.93	
12.08.2021	13.08.2021	2255	57.34		16.86		7.26		9.26	
13.08.2021	14.08.2021	2270	51.72		15.03		6.81		8.72	
19.08.2021	20.08.2021	2412	55.69	100	16.17	60	7.05	80	9.17	80
20.08.2021	21.08.2021	2461	47.31		13.45		6.54		8.21	
26.08.2021	27.08.2021	2519	53.46		15.26		7.26		9.34	
27.08.2021	28.08.2021	2536	60.34		17.34		8.12		10.06	
	Average		53.71		15.47		6.94		8.85	

**INFERENCE** 

As per NAAQMS Standards (2009),

Report Status: - Measured Values for the above parameters are within the limit.

**Analysed By** J. M. Thippeswamy

Chemist

S Shameem Banu Senior chemist



The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute artsing out of this report is subject to Hosapete jurisdiction only.

The tests results marked with \* Recognised by MOEF & CC



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

: +918394 229433, 295018 : gems\_hpt@yahoo.com

e-mail Website

: www.globalmining.in

**BMM STAGE-I** 

**ANNEXURE-07** GEMS-LD/TF/11/01

# FORTNIGHTLY FUGITIVE AIR QUALITY MONITORING DATA

1 Name of the Industry BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference**  WO/ADMIN/FY22/RO38

3 Sample collected by GLOBAL Environment & Mining Services, Hosapete

4 Particulars of sample collected : RDS Sampler (GEMS-01, GEMS-02, GEMS-03, GEMS-04, GEMS-05)

5 Month August-2021 (1stFort Night)

6 Discipline Chemical

7 Group Atmospheric Pollution

8 Method adopted IS 5182 (Part 4): 1999 RA 2014

9 Report Issued Date 03.09.2021

10 Report Number ULR-TC532321000000656F

SI. NO.	Location / Plant	Sample Code	Date Of Monitoring	Date Of Sample Receipt	SPM (μg/m³)	Standard
I. Bene	eficiation Plant-1					
1.	Main Canteen	2128	05.08.2021	06.08.2021	1323.60	2000
2.	Main Crusher	2129	05.08.2021	06.08.2021	622.37	2000
3.	Iron Ore Screen	2173	09.08.2021	10.08.2021	337.82	2000
II. Pelle	et Plant-I					
4.	Near Pellet Plant	2174	09.08.2021	10.08.2021	783.61	2000
5.	TG Zero Meter	2175	09.08.2021	10.08.2021	554.85	2000
6.	Pellet Stock Yard	2176	09.08.2021	10.08.2021	870.26	2000
III. Spo	onge Iron Division-1					
7.	Control Room SID-I	2177	09.08.2021	10.08.2021	786.33	2000
8.	Near Product bin	2199	10.08.2021	11.08.2021	941.94	2000
9.	Coal Feeding Area	2200	10.08.2021	11.08.2021	389.54	2000
IV. Indi	uction Furnace & Rolling Mill		771			
10.	IF Office	2201	10.08.2021	11.08.2021	509.50	2000
11.	TMT Stock Yard	2202	10.08.2021	11.08.2021	304.20	2000
12.	RML Office	2203	10.08.2021	11.08.2021	293.96	2000
V. Pow	er Plant 25 MW					
13.	25 MW ESP	2236	11.08.2021	12.08.2021	517.78	2000
14.	25 MW ACC	2237	11.08.2021	12.08.2021	1393.97	2000
VI. Site	Services					
15.	Main Stores	2238	11.08.2021	12.08.2021	606.07	2000
16.	Old Admin Building	2239	11.08.2021	12.08.2021	350.45	2000
17.	Labour Gate	2240	11.08.2021	12.08.2021	461.94	2000
18.	Safety Office	2252	12.08.2021	13.08.2021	523.75	2000

Note: SPM- Suspended Particulate matter. (µg/m³), INFERENCE: The Measured Values are within the limits

**Analysed By** J. M. Thippeswamy

J. M. B

Chemist

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.
- Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

  This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

  The tests results marked with \* Recognised by MOEF & CC

- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

Ph

: +918394 229433, 295018 : gems\_hpt@yahoo.com

e-mail Website

: www.globalmining.in

**BMM STAGE-I** 

**ANNEXURE-08** GEMS-LD/TF/11/01

# FORTNIGHTLY FUGITIVE AIR QUALITY MONITORING DATA

1 Name of the Industry BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference**  WO/ADMIN/FY22/RO38

3 Sample collected by

GLOBAL Environment & Mining Services, Hosapete

4 Particulars of sample collected:

RDS Sampler (GEMS-01, GEMS-02, GEMS-03, GEMS-04, GEMS-05)

5 Month August-2021 (2nd Fort Night)

6 Discipline Chemical

7 Group Atmospheric Pollution

Method adopted 8

IS 5182 (Part 4): 1999 RA 2014

Report Issued Date 9

03.09.2021

10 Report Number ULR-TC532321000000754F

SI. NO.	Location / Plant	Sample Code	Date Of Monitoring	Date Of Sample Receipt	SPM (μg/m³)	Standard
I. Benef	ficiation Plant-1					
1.	Main Canteen	2408	19.08.2021	20.08.2021	461.69	2000
2.	Main Crusher	2409	19.08.2021	20.08.2021	795.16	2000
3.	Iron Ore Screen	2454	20.08.2021	21.08.2021	475.10	2000
II. Pelle	et Plant-I					
4.	Near Pellet Plant	2455	20.08.2021	21.08.2021	901.62	2000
5.	TG Zero Meter	2456	20.08.2021	21.08.2021	713.00	2000
6.	Pellet Stock Yard	2457	20.08.2021	21.08.2021	673.07	2000
III. Spo	nge Iron Division-1					
7.	Control Room SID-I	2458	20.08.2021	21.08.2021	699.00	2000
8.	Near Product bin	2469	21.08.2021	22.08.2021	403.84	2000
9.	Coal Feeding Area	2470	21.08.2021	22.08.2021	1326.45	2000
IV. Indi	iction Furnace & Rolling Mill					
10.	IF Office	2471	21.08.2021	22.08.2021	1508.68	2000
11.	TMT Stock Yard	2472	21.08.2021	22.08.2021	584.85	2000
12.	RML Office	2473	21.08.2021	22.08.2021	1216.89	2000
V. Powe	er Plant 25 MW					
13.	25 MW ESP	2481	23.08.2021	24.08.2021	1127.00	2000
14.	25 MW ACC	2482	23.08.2021	24.08.2021	399.92	2000
VI. Site	Services					
15.	Main Stores	2483	23.08.2021	24.08.2021	851.33	2000
16.	Old Admin Building	2484	23.08.2021	24.08.2021	595.31	2000
17.	Labour Gate	2485	23.08.2021	24.08.2021	1630.09	2000
18.	Safety Office (OHC)	2497	24.08.2021	25.08.2021	1205.42	2000

Note: SPM - Suspended Particulate matter (µg/m³), INFERENCE: The Measured Values are within the limits.

**Analysed By** J. M. Thippeswamy Chemist

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.
- Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

  This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

  The tests results marked with \* Recognised by MOEF & CC

- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane, HOSPET - 583201, Dist., Bellary (Karnataka)

: +918394 229433, 295018

e-mail

: gems\_hpt@yahoo.com

Website

: www.globalmining.in

**BMM STAGE-I** 

ANNEXURE-09 GEMS-LD/TF/10/01

# **Analysis Report of Stack Emission**

1 Name of the Industry

**Customer Reference** 

2 3 Sample collected by

Particulars of sample collected 4

5 Discipline

6 Group

7 Sample Type

8 Sampling Location

9 Month of Sampling

Date of Sample Received 10

Date of Sample Analysis 11

12 **Date Sample Analysis Completion** 

13 Report Issued Date

Report Number 14

3

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

WO/ADMIN/FY22/RO38

GLOBAL Environment & Mining Services, Hosapete

Vayubodhan Stack sampler VSS1Sl.No.304 DTB 07 Chemical

Atmospheric Pollution

Stack Monitoring

**Pellet Plant-1 ESP** 

August-2021

10.08.2021& 20.08.2021

11.08.2021& 21.08.2021

12.08.2021& 22.08.2021

03.09.2021

: ULR-TC532321000000689F

### **Stack Details**

1 Flue Used

2 Stack Height (mtr)

Stack Diameter (mtr)

Coal & furnace oil

100.0 7.0

### **Emission Details**

				Re	sult	
SI.	Parameters	Method	Unit	1 <sup>st</sup> Fort Night	2 <sup>nd</sup> Fort Night	Permissible Limit
No.	Date of Monitoring			10.08.2021	20.08.2021	Limit
	Sample Code			2207	2462	
1	Ambient Temperature	IS: 11255 (Part 1) - 1985 (RA 2014)	oC.	29	28	-
2	Stack Temperature	IS: 11255 (Part 1) - 1985 (RA 2014)	oC.	118	112	-
3	Velocity of Flue Gas	IS: 11255 (Part 1) - 1985 (RA 2014)	m/sec	6.23	6.06	-
4	Gas flow rate at Stack Condition	IS-11255(Part 03) (RA 2014)	m³/hr	863243	839687	-
5	Gas flow rate at NTP	IS-11255(Part 03) (RA 2014)	Nm³/hr	666750	656483	-
6	Particulate Matter	IS: 11255 (Part 1) - 1985 (RA 2014)	mg/Nm³	58.30	48.70	100
7	Sulphur Dioxide	IS: 11255 (Part 2): (RA 2014)	mg/Nm³	42.90	28.60	NS
8	Nitrogen Dioxide	IS:11255 (Part7): 2005 (RA 2017)	mg/Nm³	8.20	2.05	NS
9	Carbon Monoxide	GEMS/SOP/69	%	0.003	0.001	-

Note: NS- Not Specified, RA: Reaffirmed, INFERENCE: The Measured Values are within the limits.,

**Analysed By** J. M. Thippeswamy

Chemist

S Shameem Bar Senior chemis

The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising needia without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

The tests results marked with \* Recognised by MOEF & CC Recognised by Ministry of Environment, Forest and Climate Change for Laboratory

Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

: +918394 229433, 295018 : gems\_hpt@yahoo.com

e-mail Website

: www.globalmining.in

**BMM STAGE-I** 

**ANNEXURE-10 GEMS-LD/TF/10/01** 

# **Analysis Report of Stack Emission**

Name of the Industry 1

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference**  WO/ADMIN/FY22/RO38

3 Sample collected by GLOBAL Environment & Mining Services, Hosapete

4 Particulars of sample collected Vayubodhan Stack sampler VSS 1 Sl.No.304 DTB 07

5 Discipline Chemical

6 Group Atmospheric Pollution

7 Sample Type **Stack Monitoring** 

8 Sampling Location 2X100TPD Sponge iron plant ESP

9 Month of Sampling August-2021

10 Date of Sample Received

12.08.2021 & 24.08.2021

11 Date of Sample Analysis

13.08.2021 & 25.08.2021

12 **Date Sample Analysis Completion** 

14.08.2021 & 26.08.2021

13 Report Issued Date

03.09.2021

Report Number

ULR-TC532321000000703F

# **Stack Details**

1 Flue Used Coal

2 Stack Height (mtr) 60.0

3 Stack Diameter (mtr) 2.00

### **Emission Details**

				Res	sult		
Sl. No.	Parameters	Method	Unit	1 <sup>st</sup> Fort Night	2 <sup>nd</sup> Fort Night	Permissible Limit	
NO.	Date of Monitoring			12.08.2021	24.08.2021	Linit	
	Sample Code			2256	2501		
1	Ambient Temperature	IS: 11255 (Part 1) - 1985 (RA 2014)	oC.	28	29	-	
2	Stack Temperature	IS: 11255 (Part 1) - 1985 (RA 2014)	oC.	126	134	-	
3	Velocity of Flue Gas	IS: 11255 (Part 1) - 1985 (RA 2014)	m/sec	6.77	7.01	-	
4	Gas flow rate at Stack Condition	IS-11255(Part 03) (RA 2014)	m³/hr	76577	79292	-	
5	Gas flow rate at NTP	IS-11255(Part 03) (RA 2014)	Nm³/hr	57768	58835	-	
6	Particulate Matter	IS: 11255 (Part 1) - 1985 (RA 2014)	mg/Nm³	55.10	60.40	100	
7	Sulphur Dioxide	IS: 11255 (Part 2): (RA 2014)	mg/Nm³	17.16	40.04	NS	
8	Nitrogen Dioxide	IS:11255 (Part7): 2005 (RA 2017)	mg/Nm³	6.15	14.35	NS	
9	Carbon Monoxide	GEMS/SOP/69	%	0.002	0.007	-	

Note: NS- Not Specified. RA: Reaffirmed, INFERENCE: The Measured Values are within the limits.,

**Analysed By** 

J. M. Thippeswamy Chemist

S Shameem Banu Senior chemist

The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied. 1.

Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.
This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing.

Total liability of our laboratory is limited to the invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only. The tests results marked with \* Recognised by MOEF & CC



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

: +918394 229433, 295018 : gems\_hpt@yahoo.com

e-mail Website

: www.globalmining.in

BMM STAGE-I

**ANNEXURE-11** GEMS-LD/TF/10/01

# **Analysis Report of Stack Emission**

1 Name of the Industry BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District

2 **Customer Reference**  WO/ADMIN/FY22/RO38

3 Sample collected by **GLOBAL Environment & Mining Services, Hosapete** Vayubodhan Stack sampler VSS 1 Sl.No.304 DTB 07

4 Particulars of sample collected 5

Chemical

Discipline 6 Group

Atmospheric Pollution

7 Sample Type

Stack Monitoring

8 Sampling Location

Induction Furnace1&2

9 Month of Sampling August-2021

10 Date of Sample Received

11 Date of Sample Analysis

12 Date Sample Analysis Completion 13 Report Issued Date

03.09.2021

14 Report Number

# **Stack Details**

1 Flue Used **Electric Power** 

2 Stack Height (mtr) 3 Stack Diameter (mtr)

30.0 1.0

# **Emission Details**

				Re	sult		
Sl. No.	Parameters	Method	Unit	1 <sup>st</sup> Fort Night	2 <sup>nd</sup> Fort Night	Permissible Limit	
NO.	Date of Monitoring			-	-	Lillit	
	Sample Code				-		
1	Ambient Temperature	IS: 11255 (Part 1) - 1985 (RA 2014)	°C			-	
2	Stack Temperature	IS: 11255 (Part 1) - 1985 (RA 2014)	oC.				
3	Velocity of Flue Gas	IS: 11255 (Part 1) - 1985 (RA 2014)	m/sec			-	
4	Gas flow rate at Stack Condition	IS-11255(Part 03) (RA 2014)	m³/hr			-	
5	Gas flow rate at NTP	IS-11255(Part 03) (RA 2014)	Nm³/hr	Under Ma	intenance	-	
6	Particulate Matter	IS: 11255 (Part 1) - 1985 (RA 2014)	mg/Nm <sup>3</sup>			100	
7	Sulphur Dioxide	IS: 11255 (Part 2): (RA 2014)	mg/Nm³			NS	
8	Nitrogen Dioxide	IS:11255 (Part7): 2005 (RA 2017)	mg/Nm <sup>3</sup>			NS	
9	Carbon Monoxide	GEMS/SOP/69	%			-	

Note: NS- Not Specified, RA: Reaffirmed, INFERENCE: The Measured Values are within the limits..



- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.
- Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

  This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

  The tests results marked with \* Recognised by MOEF & CC

- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

: +918394 229433, 295018 : gems\_hpt@yahoo.com

e-mail Website

: www.globalmining.in

**BMM STAGE-I** 

**ANNEXURE-12** GEMS-LD/TF/10/01

# **Analysis Report of Stack Emission**

1 Name of the Industry BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District

2 **Customer Reference**  WO/ADMIN/FY22/RO38

3 Sample collected by GLOBAL Environment & Mining Services, Hosapete

4 Particulars of sample collected Vayubodhan Stack sampler VSS 1 Sl.No.304 DTB 07

5 Discipline Chemical

6 Group Atmospheric Pollution

7 Sample Type **Stack Monitoring** 

8 Sampling Location Rolling mill reheating furnace

9 Month of Sampling August-2021

10 Date of Sample Received

11.08.2021 & 23.08.2021

11 Date of Sample Analysis 12.08.2021 & 24.08.2021

12 Date Sample Analysis Completion

13.08.2021 & 25.08.2021

13 Report Issued Date 03.09.2021

Report Number 14

3

ULR-TC532321000000698F

# **Stack Details**

1 Flue Used Coal

2 Stack Height (mtr)

Stack Diameter (mtr)

30.0 8.0

# **Emission Details**

				Res	sult	Permissible Limit	
Sl. No.	Parameters	Method	Unit	1 <sup>st</sup> Fort Night	2 <sup>nd</sup> Fort Night		
NO.	Date of Monitoring			11.08.2021	23.08.2021	Limit	
	Sample Code			2241	2489		
1	Ambient Temperature	IS: 11255 (Part 1) - 1985 (RA 2014)	oC	30	28	-	
2	Stack Temperature	IS: 11255 (Part 1) - 1985 (RA 2014)	oC.	95	91	-	
3	Velocity of Flue Gas	IS: 11255 (Part 1) - 1985 (RA 2014)	m/sec	5.24	5.87	-	
4	Gas flow rate at Stack Condition	IS-11255(Part 03) (RA 2014)	m³/hr	9483	10623	-	
5	Gas flow rate at NTP	IS-11255(Part 03) (RA 2014)	Nm³/hr	7808	8785	-	
6	Particulate Matter	IS: 11255 (Part 1) - 1985 (RA 2014)	mg/Nm <sup>3</sup>	47.50	54.90	100	
7	Sulphur Dioxide	IS: 11255 (Part 2): (RA 2014)	mg/Nm <sup>3</sup>	17.16	28.60	NS	
8	Nitrogen Dioxide	IS:11255 (Part7): 2005 (RA 2017)	mg/Nm <sup>3</sup>	0.00	20.50	NS	
9	Carbon Monoxide	GEMS/SOP/69	%	0.008	0.014	-	

Note: NS- Not Specified. RA: Reaffirmed, INFERENCE: The Measured Values are within the limits.,

**Analysed By** J. M. Thippeswamy Chemist

S Shameem Banu Senior chemist

The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

The tests results marked with \* Recognised by MOEF & CC



(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

: +918394 229433, 295018

e-mail Website : gems\_hpt@yahoo.com : www.globalmining.in

**BMM STAGE-I** 

**ANNEXURE-13** GEMS-LD/TF/10/01

# **Analysis Report of Stack Emission**

1 Name of the Industry BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District

2 **Customer Reference**  WO/ADMIN/FY22/RO38

3 Sample collected by GLOBAL Environment & Mining Services, Hosapete

4 Particulars of sample collected Vayubodhan Stack sampler VSS 1 Sl.No. 304 DTB 07

5 Discipline

Chemical

6 Group Atmospheric Pollution

7 Sample Type Stack Monitoring

8 Sampling Location

AFBC Boiler ESP (25 MW Power Plant)

9 Month of Sampling August-2021

10 Date of Sample Received

11 Date of Sample Analysis

**Date Sample Analysis Completion** 12

03.09.2021

13 Report Issued Date 14 Report Number

3

# **Stack Details**

1 Flue Used

Coal

2 Stack Height (mtr)

65.0

Stack Diameter (mtr)

2.5

# **Emission Details**

				Re	sult		
SI. No.	Parameters	Method	Unit	1 <sup>st</sup> Fort Night	2 <sup>nd</sup> Fort Night	Permissible	
110.	Date of Monitoring				-	Limit	
	Sample Code			-	-		
1	Ambient Temperature	IS: 11255 (Part 1) - 1985 (RA 2014)	oC.			-	
2	Stack Temperature	IS: 11255 (Part 1) - 1985 (RA 2014)	oC.			-	
3	Velocity of Flue Gas	IS: 11255 (Part 1) - 1985 (RA 2014)	m/sec			-	
4	Gas flow rate at Stack Condition	IS-11255(Part 03) (RA 2014)	m³/hr			-	
5	Gas flow rate at NTP	IS-11255(Part 03) (RA 2014)	Nm³/hr	Shute	down		
6	Particulate Matter	IS: 11255 (Part 1) - 1985 (RA 2014)	mg/Nm³			50	
7	Sulphur Dioxide	IS: 11255 (Part 2): (RA 2014)	mg/Nm³			600	
8	Nitrogen Dioxide	IS:11255 (Part7): 2005 (RA 2017)	mg/Nm³			300	
9	Carbon Monoxide	GEMS/SOP/69	%			-	

Note: NS- Not Specified. RA: Reaffirmed,



The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

The tests results marked with \* Recognised by MOEF & CC



5

# **GLOBAL**ENVIRONMENT & MINING SERVICES

(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

Ph e-mail : +918394 229433, 295018 : gems\_hpt@yahoo.com

Website

: www.globalmining.in

**BMM STAGE-I** 

**ANNEXURE-14 GEMS-LD/TF/10/01** 

# **Analysis Report of Stack Emission**

1 Name of the Industry BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference** WO/ADMIN/FY22/RO38

3 Sample collected by GLOBAL Environment & Mining Services, Hosapete 4 Particulars of sample collected Vayubodhan Stack sampler VSS 1 Sl.No.304 DTB 07

Discipline Chemical

6 Group Atmospheric Pollution 7 Sample Type Stack Monitoring

8 **Date of Analysis Completion** August-2021 (1st Fort Night)

9 Date of Sample Received 10.08.2021 Date of Sample Analysis 10 11.08.2021 **Date Sample Analysis Completion** 11 : 12.08.2021 12 Report Issued Date 03.09.2021

13 Report Number ULR-TC532321000000690F

SI. No	Stack Attached to	Date of Monitoring	Sample Code	Fuel Used	Ta °C	TS °C	V m/Sec	Height (m)	Diameter (m)	PM mg/Nm³	KSPCB Std mg/Nm³
Chir	nneys attached to Bag Filter	(De dusting Uni	ts)								
Ben	eficiation Plant			Y'CHAN							
1	Ore Crushing & Screening	10.08.2021	2208		32	45	5.37	30	1.20	42.0	50
2	Ore Fines Hopper Bottom	10.08.2021	2209		32	48	5.45	30	1.20	38.5	50
3	Main Crusher (RMHS)	10.08.2021	2210		28	48	5.13	30	1.20	44.8	50

SI. No	Beneficiation Plant	Gas flow rate at Stack Condition m³/hr	Gas flow rate at NTP Nm³/hr	KSPCB Std
1	Ore Crushing & Screening	21867	20973	•
2	Ore Fines Hopper Bottom	22193	21086	-
3	Main Crusher (RMHS)	20890	19588	-

Parameter	Protocol
Particulate Matter (mg/Nm3)	IS: 11255 (Part 1) - 1985 (reaffirmed 2014)
Gas flow rate at Stack Condition	IS-11255(Part 03) (RA 2014)
Gas flow rate at NTP	IS-11255(Part 03) (RA 2014)

**Analysed By** J. M. Thippeswamy Chemist

J.M.B

S Shameem Banu Senior chemist

The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing.

Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

The tests results marked with \* Recognised by MOEF & CC

Recognised by Ministry of Environment, Forest and Climate Change for Laboratory

Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane, HOSPET - 583201, Dist., Bellary (Karnataka)

: +918394 229433, 295018

e-mail Website

: gems\_hpt@yahoo.com : www.globalmining.in

**BMM STAGE-I** 

**ANNEXURE-15 GEMS-LD/TF/10/01** 

# **Analysis Report of Stack Emission**

1 Name of the Industry

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference**  WO/ADMIN/FY22/RO38

3 Sample collected by

4 Particulars of sample collected GLOBAL Environment & Mining Services, Hosapete Vayubodhan Stack sampler VSS 1 Sl.No.304 DTB 07

5 Discipline Chemical

6 Group

Atmospheric Pollution

7 Sample Type

8

Stack Monitoring

Date of Analysis Completion 9 Date of Sample Received

August-2021 (1st Fort Night)

10

: 10.08.2021 & 11.08.2021

Date of Sample Analysis 11 **Date Sample Analysis Completion** 

11.08.2021 & 12.08.2021 : 12.08.2021 & 13.08.2021

12 Report Issued Date 03.09.2021

Report Number

ULR-TC532321000000699F

SI. No	Stack Attached to	Date of Monitoring	Sample Code	Fuel Used	Ta °C	TS °C	V m/Sec	Height (m)	Diameter (m)	PM mg/Nm³	KSPCB Std mg/Nm³
Chir	nneys attached to Bag Filte	r (De dusting Uni	ts)								
Pell	et Plant			-							
4	Mixed Area	10.08.2021	2211		28	45	5.63	30	1.20	43.2	50
5	Mixed Area Pellet Discharge Point	10.08.2021 11.08.2021	2211 2242		28 28	45 39	5.63 5.54	30	1.20	43.2 39.6	50

SI. No	Pellet Plant	Gas flow rate at Stack Condition m <sup>3</sup> /hr	Gas flow rate at NTP Nm³/hr	KSPCB Std
4	Mixed Area	22926	21700	
5	Pellet Discharge Point	22559	21764	-
6	Product Transfer Point	23903	23360	-

Parameter	Protocol
Particulate Matter (mg/Nm3)	IS: 11255 (Part 1) - 1985 (reaffirmed 2014)
Gas flow rate at Stack Condition	IS-11255(Part 03) (RA 2014)
Gas flow rate at NTP	IS-11255(Part 03) (RA 2014)

**Analysed By** J. M. Thippeswamy

Chemist



- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

  Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

  This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

  The tests results marked with \* Recognised by MOEF & CC

  Recognised by Ministry of Environment, Forest and Climate Change for Laboratory Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka) : +918394 229433, 295018

e-mail Website

: gems\_hpt@yahoo.com : www.globalmining.in

**BMM STAGE-I** 

**ANNEXURE-16 GEMS-LD/TF/10/01** 

# **Analysis Report of Stack Emission**

1 Name of the Industry

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference**  WO/ADMIN/FY22/RO38

3 Sample collected by GLOBAL Environment & Mining Services, Hosapete

4 Particulars of sample collected Vayubodhan Stack sampler VSS 1 Sl.No.304 DTB 07

5 Discipline Chemical

6 Group

Atmospheric Pollution

7 Sample Type Stack Monitoring

8 Date of Analysis Completion August-2021 (1st Fort Night)

9 Date of Sample Received

11.08.2021 & 12.08.2021

10 Date of Sample Analysis

12.08.2021 & 13.08.2021

11 **Date Sample Analysis Completion** 

: 13.08.2021 & 14.08.2021

12 Report Issued Date 03.09.2021

13 Report Number ULR-TC532321000000704F

SI. No	Stack Attached to	Date of Monitoring	Sample Code	Fuel Used	Ta °C	TS °C	V m/Sec	Height (m)	Diameter (m)	PM mg/Nm³	KSPCB Std mg/Nm <sup>3</sup>
Chir	mneys attached to Bag Filter	r (De dusting Uni	ts)								
2 X	100 TPD Sponge Iron Kiln 1	. & 2									-
7	Cooler Discharge -1	11.08.2021	2244		28	38	5.58	30	1.20	42.4	50
8	Cooler Discharge -2	12.08.2021	2257		30	45	5.41	30	1.20	39.2	50
9	Coal Crusher	12.08.2021	2258		30	40	5.32	30	1.20	44.7	50
10	Transfer House	12.08.2021	2259		31	39	5.01	30	1.20	41.5	50
11	Intermediate Bin	12.08.2021	2260		28	40	4.86	30	1.20	43.8	50

SI. No	2 X 100 TPD Sponge Iron Kiln 1 & 2	Gas flow rate at Stack Condition m³/hr	Gas flow rate at NTP Nm³/hr	KSPCB Std
7	Cooler Discharge -1	22722	21991	-
8	Cooler Discharge -2	22030	20991	-
9	Coal Crusher	21663	20971	-
10	Transfer House	20401	19878	-
11	Intermediate Bin	19790	19031	-

Parameter	Protocol
Particulate Matter (mg/Nm3)	IS: 11255 (Part 1) - 1985 (reaffirmed 2014)
Gas flow rate at Stack Condition	IS-11255(Part 03) (RA 2014)
Gas flow rate at NTP	IS-11255(Part 03) (RA 2014)

**Analysed By** J. M. Thippeswamy Chemist

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.
- Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

  This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

  The tests results marked with \* Recognised by MOEF & CC
- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

e-mail

: +918394 229433, 295018 : gems\_hpt@yahoo.com

Website

: www.globalmining.in

BMM STAGE-I

**ANNEXURE-17** GEMS-LD/TF/10/01

# **Analysis Report of Stack Emission**

1 Name of the Industry

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference**  WO/ADMIN/FY22/RO38

3 Sample collected by GLOBAL Environment & Mining Services, Hosapete

4 Particulars of sample collected Vayubodhan Stack sampler VSS 1 Sl.No.304 DTB 07

5 Discipline

Chemical

6 Group Atmospheric Pollution

7 Sample Type Stack Monitoring

8 Date of Analysis Completion August-2021 (2NDFort Night)

9 Date of Sample Received 23.08.2021

Date of Sample Analysis 10

: 24.08.2021

11 **Date Sample Analysis Completion** 12 Report Issued Date

: 25.08.2021 03.09.2021

13 Report Number

ULR-TC532321000000778F

SI. No	Stack Attached to	Date of Monitoring	Sample Code	Fuel Used	Ta °C	TS °C	V m/Sec	Height (m)	Diameter (m)	PM mg/Nm³	KSPCB Std mg/Nm <sup>3</sup>
Chi	nneys attached to Bag Filter	(De dusting Uni	ts)								
Ben	eficiation Plant										
1	Ore Crushing & Screening	23.08.2021	2490		26	36	5.22	30	1.20	44.5	50
2	Ore Fines Hopper Bottom	23.08.2021	2491		26	40	4.86	30	1.20	38.9	50
3	Main Crusher (RMHS)	23.08.2021	2492		30	39	5.04	30	1.20	40.4	50

SI. No	Beneficiation Plant	Gas flow rate at Stack Condition m³/hr	Gas flow rate at NTP Nm³/hr	KSPCB Std
1	Ore Crushing & Screening	21256	20568	-
2	Ore Fines Hopper Bottom	19790	18905	-
3	Main Crusher (RMHS)	20523	19931	=

Parameter	Protocol
Particulate Matter (mg/Nm³)	IS: 11255 (Part 1) - 1985 (reaffirmed 2014)
Gas flow rate at Stack Condition	IS-11255(Part 03) (RA 2014)
Gas flow rate at NTP	IS-11255(Part 03) (RA 2014)

**Analysed By** J. M. Thippeswamy

J.K1.19

Chemist

Verified By S Shameem Banu Senior chemist

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

  Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

  This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

  The tests results marked with \* Recognised by MOEF & CC
- 2. 3. 4. 5. 6.
- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

e-mail

: +918394 229433, 295018 : gems\_hpt@yahoo.com

Website

: www.globalmining.in

BMM STAGE-I

**ANNEXURE-18** GEMS-LD/TF/10/01

# **Analysis Report of Stack Emission**

1 Name of the Industry

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference** 

WO/ADMIN/FY22/RO38

3 Sample collected by GLOBAL Environment & Mining Services, Hosapete

Particulars of sample collected 4

Vayubodhan Stack sampler VSS 1 Sl.No.304 DTB 07

5 Discipline

Chemical

6 Group

Atmospheric Pollution

7 Sample Type

Stack Monitoring

8 **Date of Analysis Completion** 

August-2021 (2NDFort Night)

9 Date of Sample Received

20.08.2021

10 Date of Sample Analysis 21.08.2021

**Date Sample Analysis Completion** 11

22.08.2021

12 Report Issued Date

03.09.2021

13 Report Number

ULR-TC532321000000776F

SI. No	Stack Attached to	Date of Monitoring	Sample Code	Fuel Used	Ta ºC	TS °C	V m/Sec	Height (m)	Diameter (m)	PM mg/Nm³	KSPCB Std mg/Nm <sup>3</sup>
Chin	nneys attached to Bag Filte	r (De dusting Uni	ts)								
Dalla	et Plant										
rent	TI FIAIIL										
4	Mixed Area	20.08.2021	2463		29	41	5.07	30	1.20	38.7	50
		20.08.2021	2463 2464		29 28	41	5.07 4.88	30	1.20	38.7 43.4	50 50

SI. No	Pellet Plant	Gas flow rate at Stack Condition m³/hr	Gas flow rate at NTP Nm³/hr	KSPCB Std
4	Mixed Area	20645	19856	
5	Pellet Discharge Point	19872	18869	
6	Product Transfer Point	19790	19092	-

Parameter	Protocol
Particulate Matter (mg/Nm3)	IS: 11255 (Part 1) - 1985 (reaffirmed 2014)
Gas flow rate at Stack Condition	IS-11255(Part 03) (RA 2014)
Gas flow rate at NTP	IS-11255(Part 03) (RA 2014)

**Analysed By** 

J. M. Thippeswamy Chemist

Verified By

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.
- Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

  This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

  The tests results marked with \* Recognised by MOEF & CC
- 1. 2. 3. 4. 5.
- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane, HOSPET - 583201, Dist., Bellary (Karnataka)

Ph

: +918394 229433, 295018

e-mail Website

: gems\_hpt@yahoo.com : www.globalmining.in

> **ANNEXURE-19** GEMS-LD/TF/10/01

**BMM STAGE-I** 

# **Analysis Report of Stack Emission**

1 Name of the Industry BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference**  WO/ADMIN/FY22/RO38

3 Sample collected by GLOBAL Environment & Mining Services, Hosapete

4 Particulars of sample collected Vayubodhan Stack sampler VSS 1 Sl.No.304 DTB 07

5 Discipline Chemical

6 Group Atmospheric Pollution

7 Sample Type

Stack Monitoring

8 Date of Analysis Completion

August-2021 (2NDFort Night)

9 Date of Sample Received 24.08.2021

10 Date of Sample Analysis

25.08.2021

**Date Sample Analysis Completion** 11

26.08.2021 : 03.09.2021

12 Report Issued Date 13 Report Number

ULR-TC532321000000779F

SI. No	Stack Attached to	Date of Monitoring	Sample Code	Fuel Used	Ta °C	TS °C	V m/Sec	Height (m)	Diameter (m)	PM mg/Nm³	KSPCB Std mg/Nm <sup>3</sup>
Chir	mneys attached to Bag Filter	(De dusting Uni	ts)								
2 X	100 TPD Sponge Iron Kiln 1 &	& 2									
7	Cooler Discharge -1	24.08.2021	2502		30	43	4.90	30	1.20	39.9	50
8	Cooler Discharge -2	24.08.2021	2503		29	45	5.28	30	1.20	42.3	50
9	Coal Crusher	24.08.2021	2504		27	40	5.03	30	1.20	37.7	50
10	Transfer House	24.08.2021	2505		27	38	5.27	30	1.20	43.5	50
11	Intermediate Bin	24.08.2021	2506		28	37	5.12	30	1.20	41.2	50

SI. No	2 X 100 TPD Sponge Iron Kiln 1 & 2	Gas flow rate at Stack Condition m³/hr	Gas flow rate at NTP Nm³/hr	KSPCB Std
7	Cooler Discharge -1	19953	19132	-
8	Cooler Discharge -2	21500	20419	-
9	Coal Crusher	20482	19632	-
10	Transfer House	21460	20701	
11	Intermediate Bin	20849	20244	

Parameter	Protocol
Particulate Matter (mg/Nm3)	IS: 11255 (Part 1) - 1985 (reaffirmed 2014)
Gas flow rate at Stack Condition	IS-11255(Part 03) (RA 2014)
Gas flow rate at NTP	IS-11255(Part 03) (RA 2014)

**Analysed By** J. M. Thippeswamy


Chemist



- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.
- Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

  This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

  The tests results marked with \* Recognised by MOEF & CC
- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

Ph e-mail : +918394 229433, 295018 : gems\_hpt@yahoo.com

Website

: www.globalmining.in

BMM STAGE-I

**ANNEXURE-20** GEMS-LD/TF/08/01

# AMBIENT NOISE LEVEL MONITORING REPORT

Name of the Industry

: BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

**Customer Reference** 

WO/ADMIN/FY22/RO38

Sample collected by

**Global Environment & Mining Services** 

Discipline

Chemical

Group Sample Type **Atmospheric Pollution** Noise Level Monitoring

Particulars of Sample Collected

Equinox-107

Month

August-2021

Report Issue Date

03.09.2021

Method Adopted

IS 9989-1981 Reaffirmed 2014 ULR-TC532321000000715F

Report No

Noise Level dB (A) SI. Date of **Day Time Night Time** Location No Monitoring Standard Standard Min Max Min Max 1 52.7 66.9 48.7 65.1 Main Gate 02.08.2021 75 70 2 49.2 67.5 47.9 64.9 **Near ATM** 03.08.2021 75 70 3 53.1 63.1 50.2 58.2 **Transit House** 04.08.2021 75 70 4 50.9 64.7 **CAAQMS Station** 48.8 61.8 11.08.2021 75 70 5 49.5 60.2 56.7 Gunda Road 48.3 12.08.2021 75 70 6 53.3 63.8 50.1 62.1 **Gunda Railway Station** 13.08.2021 75 70 7 51.7 67.1 51.6 60.5 **Bagging Shed** 16.08.2021 75 70 8 54.2 66.5 53.2 61.9 Railway Siding 17.08.2021 75 70 9 53.6 69.3 51.3 63.4 4th Gate 18.08.2021 75 70 10 50.3 65.9 49.7 59.3 **Bricks Plant** 19.08.2021 75 70 11 54.7 72.2 52.6 61.8 Kempuhalla (Wagon Tippler) 20.08.2021 75 70 12 54.1 65.1 51.4 58.6 Danapura Bridge 23.08.2021 75 70 13 71.7 59.2 53.2 63.7 2nd Gate 24.08.2021 75 70 14 52.6 64.5 49.9 55.9 **Project Store** 25.08.2021 75 70 15 55.9 65.9 53.1 59.4 Dispatch (Truck Parking Area) 26.08.2021 75 70

**INFERENCE** 

As per CPCB Standards,

Report Status: - Measured Values for the above parameters are within the limit.

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied. 1. 2. 3. 4. 5.
- Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

  This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing.
- Total liability of our laboratory is limited to the invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only. The tests results marked with \* Recognised by MOEF & CC
- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory
- Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey



(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane.

HOSPET - 583201, Dist., Bellary (Karnataka)

Ph

: +918394 229433, 295018

e-mail Website

: gems\_hpt@yahoo.com : www.globalmining.in

BMM STAGE-I

**ANNEXURE-21 GEMS-LD/TF/08/01** 

# **AMBIENT NOISE LEVEL MONITORING REPORT**

Name of the Industry

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

**Customer Reference** 

WO/ADMIN/FY22/RO38

Sample collected by

**Global Environment & Mining Services** 

Discipline

Chemical

Group Sample Type

Atmospheric Pollution Noise Level Monitoring

Particulars of Sample Collected

Equinox-107

Month Report Issue Date August-2021

03.09.2021

Method Adopted

IS 9989-1981 Reaffirmed 2014

Report No ULR-TC532321000000777F

			Noise Level dB (A)								
SI.	Location	Date of	Day	Time		Night Time					
No		Monitoring	Min	Max	Standard	Min	Max	Standard			
1	Main Gate	05.08.2021	51.8	67.5	75	49.1	64.7	70			
2	Near ATM	06.08.2021	53.1	66.2	75	48.4	65.1	70			
3	Transit House	09.08.2021	52.3	64.3	. 75	50.7	58.6	70			
4	CAAQMS Station	10.08.2021	49.9	65.1	75	49.1	62.4	70			
5	Gunda Road	18.08.2021	51.4	62.4	75	47.6	55.8	70			
6	Gunda Railway Station	19.08.2021	52.6	64.2	75	50.9	61.6	70			
7	Bagging Shed	20.08.2021	53.1	65.9	75	49.8	59.7	70			
8	Railway Siding	21.08.2021	52.9	67.2	75	52.3	62.1	70			
9	4th Gate	23.08.2021	54.2	70.7	75	50.5	64.5	70			
10	Bricks Plant	24.08.2021	51.6	66.2	75	48.7	61.8	70			
11	Kempuhalla (Wagon Tippler)	25.08.2021	53.1	71.5	75	51.4	60.4	70			
12	Danapura Bridge	11.08.2021	55.7	67.1	75	50.9	59.3	70			
13	2nd Gate	12.08.2021	60.3	69.3	75	53.7	62.9	70			
14	Project Store	16.08.2021	51.9	66.2	75	47.9	59.7	70			
15	Dispatch (Truck Parking Area)	17.08.2021	54.6	67.4	75	51.2	61.3	70			

**INFERENCE** 

As per CPCB Standards,

Report Status: - Measured Values for the above parameters are within the limit.

Verified By S Shameem Banu Senior chemist

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.
- 1. 2. 3. 4. 5. 6.
- Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

  This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing.
- Total liability of our laboratory is limited to the invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only. The tests results marked with \* Recognised by MOEF & CC
- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3<sup>rd</sup> Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

Ph e-mail : +918394 229433, 295018 : gems\_hpt@yahoo.com

Website

: www.globalmining.in

BMM STAGE-I

**ANNEXURE-22** GEMS-LD/TF/23/01

# **Analysis Report of Water Quality Data**

1 Name of the Industry

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference** 

WO/ADMIN/FY22/RO38

3 Sample collected by : GLOBAL Environment & Mining Services

4 Particulars of sample collected

: Grab Sampling

5 Sampling Procedure

GEMS-LD/SOP/32

6 Discipline Chemical

7 Group Pollution & Environment

8 Sample Type **Ground Water** 

9 Date of Sampling

13.08.2021

10 Sample Received

: 13.08.2021

11 Date of Analysis

13.08.2021

12 Date of Analysis Completion : 21.08.2021

13 Report Issue Date 03.09.2021

14 Report Number

: ULR-TC532321000000708F

					Results	Standards as per IS:		
Sl.	D			S	ample Co	de		
No	Parameters	Protocol	Unit	2271	2272	2273	10500	0:2012
				GW1 (Danapur Village)	GW2 (Hanumana halli)	GW3 (Gelemmana Gudi)	Desirable Limits	Permissible Limits
1.	Colour	IS: 3025 (PART 4)- 1984, RA-2002 Platinum cobalt Method	Hazen	<5	<5	<5	5	15
2.	Conductivity	APHA 23 <sup>rd</sup> Edition 2017 2510 B (Pg. No.2-54)	μS/cm	2300	2900	1840		
3.	Total Dissolved Solids	APHA 23 <sup>rd</sup> Edition 2017 2540 C (Pg. No.2-65)	mg/L	1428	1840	1182	500	2000
4.	рН	APHA 23 <sup>rd</sup> Edition 2017 4500 B (Pg. No.4-92 to 4-96)	-	7.42	7.29	7.35	6.5 to 8.5	NR
5.	Turbidity (NTU)	APHA 23 <sup>rd</sup> Edition 2017 2130 B (Pg. No.2-14)	NTU	0.5	0.3	0.7	1	5
6.	Total Suspended Solids	APHA 23rd Edition 2017 2540 D (Pg. No.2-66 to 2-67)	mg/L	Nil	Nil	Nil	-	-
7.	Sulphate as SO <sub>4</sub>	APHA 23 <sup>rd</sup> Edition 2012 4500 SO <sub>4</sub> <sup>2-</sup> E (Page No. 4-190)	mg/L	173.54	187.61	109.14	200	400
8.	phosphorusas P	APHA 23 <sup>RD</sup> EDITION -4500-P D (Pg. No. 4-163 to4-164)	mg/L	Nil	Nil	Nil	-	-
9.	Sodium as Na	APHA 23 <sup>rd</sup> Edition 2017 Na 3500 B (Pg. No.3-97to 3-98)	mg/L	348.50	494.03	304.27	-	
10.	Potassium as K	APHA 23rd Edition 2017 K 3500 B (Pg., No.3-87 to 3-88)	mg/L	0.0	0.0	0.0	2	-
11.	Calcium as Ca	APHA 23 <sup>rd</sup> Edition 2017 3500 Ca B (Pg. No.3-84)	mg/L	136	112	120	75	200
12.	Magnesium as Mg	APHA 23 <sup>rd</sup> Edition 2017 3500-B Mg By calculation	mg/L	51.03	69.50	38.88	30	100
13.	Total Hardness as CaCO <sub>3</sub>	APHA 23 <sup>rd</sup> Edition 2017 2340 C (Page No. 2-46)	mg/L	550	566	460	200	600
14.	Chloride as Cl	APHA 23 <sup>rd</sup> Edition 2017 4500 Cl- (Page No. 4-72)	mg/L	317.63	470.49	322.60	250	1000
15.	Fluoride as F	APHA 23 <sup>rd</sup> Edition 2012 4500 F- D (Page No. 4-87 to 4-88)	mg/L	0.95	1.18	0.99	1	1.5
16.	Nitrate Nitrogen as NO <sub>3</sub>	APHA 23 <sup>rd</sup> Edition 2012 4500 NO3 E (Pg. No.4-125 to 4-127)	mg/L	32.43	36.20	29.40	45 (811)	nt s

The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied

Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

The tests results marked with \* Recognised by MOEF & CC



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3<sup>rd</sup> Main Road, Basaveswara Badavane, HOSPET - 583201, Dist., Bellary (Karnataka)

Ph

: +918394 229433, 295018

e-mail Website

: gems\_hpt@yahoo.com : www.globalmining.in

BMM STAGE-I

							ANN	EXURE-
17.	Total Alkalinity as CaCO <sub>3</sub>	APHA 23 <sup>rd</sup> Edition 2320 B (Pg. No.2-35)	mg/L	450	544	370	200	600
18.	Acidity as CaCO <sub>3</sub>	IS:3025 (part 22)-1986, RA-2014 Indicator method	mg/L	Nil	Nil	Nil	-	-
19.	Total Iron as Fe	APHA 23rd Edition 3111 B. Direct Air Acetylene Flame Method	mg/L	0.10	0.08	0.19	0.30	NR
20.	Nickel as Ni	APHA 23rd Edition 3111 B. Direct Air Acetylene Flame Method	mg/L	<0.01	<0.01	<0.01	0.02	NR
21.	Manganese as Mn	APHA 23 <sup>rd</sup> Edition 3111 B. Direct Air Acetylene Flame Method	mg/L	0.061	0.107	0.140	0.10	0.30
22.	Copper as Cu	APHA 23 <sup>rd</sup> Edition 3111 B. Direct Air Acetylene Flame Method	mg/L	0.312	0.375	0.267	0.05	1.50
23.	Zinc as Zn	APHA 23 <sup>rd</sup> Edition 3111 B. Direct Air Acetylene Flame Method	mg/L	<0.1	<0.1	<0.1	5	15
24.	Lead as Pb	APHA 23 <sup>rd</sup> Edition 3111 B. Direct Air Acetylene Flame Method	mg/L	<0.01	<0.01	<0.01	0.01	NR
25.	Total Coli form count	APHA 23 <sup>rd</sup> Edition 9222-B (p.no.9-66) Membrane filter technique	MPN/ 100 ml	Ab	Ab	Ab	Shall not be detectable in any 100 ml sample	-
26.	Escherichia coli count	APHA 23 <sup>rd</sup> Edition 9222 (p.no.9-76) Membrane filter technique	MPN/ 100 ml	Ab	Ab	Ab	Shall not be detectable in any 100ml sample	-

Note: NR-No relaxation, Ab-Absent.

**INFERENCE** 

As per Standards IS: 10500:2012

Report Status: - Measured Values for the above parameters are within the limit.

J. FL. US

**Analysed By** J. M. Thippeswamy Chemist

S Shameem Banu Senior chemist



1. 2. 3. 4. 5. 6.

The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

The tests results marked with \* Recognised by MOEF & CC.

Recognised by Ministry of Englanding and Climate Change for Laboratory.



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane, HOSPET - 583201, Dist., Bellary (Karnataka)

Ph

: +918394 229433, 295018

e-mail Website

: gems\_hpt@yahoo.com : www.globalmining.in

BMM STAGE-I

**ANNEXURE-23** GEMS-LD/TF/23/01

# **Analysis Report of Water Quality Data**

1 Name of the Industry BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference** 

WO/ADMIN/FY22/RO38

3 Sample collected by

: GLOBAL Environment & Mining Services

4 Particulars of sample collected

**Grab Sampling** 

5 Sampling Procedure

: GEMS-LD/SOP/32

6 Discipline Chemical

7 Group

: Pollution & Environment

8 Sample Type

: Ground Water

9 Date of Sampling

10 Sample Received : 13.08.2021

: 13.08.2021

11 Date of Analysis

13.08.2021

Date of Analysis Completion 12

: 21.08.2021

13 Report Issue Date 14 Report Number

03.09.2021

: ULR-TC532321000000709F

Sl.				Sa	Results imple Cod	lo.	Standards as per	
No	Parameters	Dwatacal	*****	2274	2275	2276	IS: 105	00:2012
110	- 4.4	Protocol	Unit	GW4 (Mariyammana Halli)	GW5 (Transit House BW)	GW6 (RO Drinking Water)	Desirable Limits	Permissible Limits
1.	Colour	IS: 3025 (PART 4)- 1984, RA-2002 Platinum cobalt Method	Hazen	<5	<5	<5	5	15
2.	Conductivity	APHA 23 <sup>rd</sup> Edition 2017 2510 B (Pg., No.2-54)	μS/cm	2900	360	98	-	-
3.	Total Dissolved Solids	APHA 23rd Edition 2017 2540 C (Pg. No.2-65)	mg/L	1824	348	64	500	2000
4.	pH	APHA 23rd Edition 2017 4500 B (Pg. No.4-92 to 4-96)	-	7.46	8.25	7.67	6.5 to 8.5	NR
5.	Turbidity (NTU)	APHA 23 <sup>rd</sup> Edition 2017 2130 B (Pg. No.2-14)	NTU	0.4	0.2	0	1	5
6.	Total Suspended Solids	APHA 23rd Edition 2017 2540 D (Pg., No.2-66 to 2-67)	mg/L	Nil	Nil	Nil		-
7.	Sulphate as SO <sub>4</sub>	APHA 23 <sup>rd</sup> Edition 2012 4500 SO <sub>4</sub> <sup>2</sup> - E (Page No. 4-190)	mg/L	221.54	55.11	9.53	200	400
8.	Phosphorusas P	APHA 23 <sup>RD</sup> EDITION -4500-P D (Pg. No. 4-163 to4-164)	mg/L	Nil	Nil	Nil	-	-
9.	Sodium as Na	APHA 23 <sup>rd</sup> Edition 2017 Na 3500 B (Pg. No.3-97to 3-98)	mg/L	534.50	84.47	4.85	-	-
10.	Potassium as K	APHA 23rd Edition 2017 K 3500 B (Pg. No.3-87 to 3-88)	mg/L	3.10	0.0	0.0	-	-
11.	Calcium as Ca	APHA 23 <sup>rd</sup> Edition 2017 3500 Ca B (Pg. No.3-84)	mg/L	168	44	14.4	75	200
12.	Magnesium as Mg	APHA 23 <sup>rd</sup> Edition 2017 3500-B Mg By calculation	mg/L	29.64	9.23	1.94	30	100
13.	Total Hardness as CaCO3	APHA 23 <sup>rd</sup> Edition 2017 2340 C (Page No. 2-46)	mg/L	542	148	44	200	600
14.	Chloride as Cl	APHA 23 <sup>rd</sup> Edition 2017 4500 Cl- (Page No. 4-72)	mg/L	458.15	49.60	2.99	250	1000
15.	Fluoride as F	APHA 23rd Edition 2012 4500 F- D (Page No. 4-87 to 4-88)	mg/L	0.61	0.74	0.21	1	1.5
16.	Nitrate Nitrogen as NO3	APHA 23 <sup>rd</sup> Edition 2012 4500 NO3 E (Pg. No.4-125 to 4-127)	mg/L	40.37	22.32	3.94	48 dnme	118 AMR

The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

2. 3. 4. 5.

Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

The tests results marked with \* Recognised by MOEF & CC



(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

Ph

: +918394 229433, 295018

e-mail Website

: gems\_hpt@yahoo.com : www.globalmining.in

BMM STAGE-I

	T		, , , , , , , , , , , , , , , , , , , ,				ANN	EXURE-2
17.	Total Alkalinity as CaCO <sub>3</sub>	APHA 23 <sup>rd</sup> Edition 2320 B (Pg. No.2-35)	mg/L	490	120	40	200	600
18.	Acidity as CaCO <sub>3</sub>	IS:3025 (part 22)-1986, RA-2014 Indicator method	mg/L	Nil	Nil	Nil		
19.	Total Iron as Fe	APHA 23 <sup>rd</sup> Edition 3111 B. Direct Air Acetylene Flame Method	mg/L	0.13	0.16	0.11	0.30	NR
20.	Nickel as Ni	APHA 23 <sup>rd</sup> Edition 3111 B. Direct Air Acetylene Flame Method	mg/L	<0.01	<0.01	<0.01	0.02	NR
21.	Manganese as Mn	APHA 23 <sup>rd</sup> Edition 3111 B. Direct Air Acetylene Flame Method	mg/L	0.110	0.92	0.074	0.10	0.30
22.	Copper as Cu	APHA 23 <sup>rd</sup> Edition 3111 B. Direct Air Acetylene Flame Method	mg/L	0.304	0.253	0.297	0.05	1.50
23.	Zinc as Zn	APHA 23 <sup>rd</sup> Edition 3111 B. Direct Air Acetylene Flame Method	mg/L	<0.1	<0.1	<0.1	5	15
24.	Lead as Pb	APHA 23 <sup>rd</sup> Edition 3111 B. Direct Air Acetylene Flame Method	mg/L	<0.01	<0.01	<0.01	0.01	NR
25.	Total Coli form count	APHA 23 <sup>rd</sup> Edition 9222-B (p.no.9-66) Membrane filter technique	MPN/ 100 ml	Ab	Ab	Ab	Shall not be detectable in any 100 ml sample	
26.	Escherichia coli count	APHA 23 <sup>rd</sup> Edition 9222 (p.no.9-76) Membrane filter technique	MPN/ 100 ml	Ab	Ab	Ab	Shall not be detectable in any 100ml sample	-

Note: NR-No relaxation, Ab-Absent, BDL-Below detectable Limit.

INFERENCE

As per Standards IS: 10500:2012

Report Status: - Measured Values for the above parameters are within the limit.

J.M. Q **Analysed By** J. M. Thippeswamy Chemist

Verified By S Shameem Banu Senior chemist



The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

2. 3. 4. 5. 6.

The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither interred nor implied.

Water Samples will be destroyed after 15Days, Minerals 3 Months, Filler papers & Thimbles After analysis Discard.

This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

The tests results marked with \* Recognised by MOEF & CC

Recognised by Ministry of Environment, Forest and Climate Change for Laboratory Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey



(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

Ph

: +918394 229433, 295018 : gems\_hpt@yahoo.com

e-mail Website

: www.globalmining.in

**BMM STAGE-I** 

**ANNEXURE-24** GEMS-LD/TF/23/01

# **Analysis Report of Water Quality Data**

1 Name of the Industry

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference**  WO/ADMIN/FY22/RO38

3 Sample collected by

: GLOBAL Environment & Mining Services

4 Particulars of sample collected

: Composite Sampling

5 Sampling Procedure

: GEMS-LD/SOP/32

6 Discipline

Chemical

7 Group

8 Sample Type Pollution & Environment

9 Date of Sampling : Sewage Treatment Plant (Outlet)

10 Sample Received

13.08.2021

11 Date of Analysis

: 13.08.2021

: 13.08.2021

12 Date of Analysis Completion 13 Report Issue Date

21.08.2021 : 03.09.2021

Report Number

ULR-TC532321000000710F

Sl. No.	Parameters	Protocol	Unit	Results			
				STP 45 KLD	STP-1 90 KLD	STP-2 90 KLD	As per KSPCB
		Sample code	-	2277	2278	2279	Std
1.	рН	APHA 23rd Edition 2017 4500 B (Pg. No.4-92 to 4-96)	-	7.64	7.45	7.79	6.5 to 9.0
2.	Total Suspended Solids	APHA 23rd Edition 2017 2540 D (Pg. No.2-66 to 2-67)	mg/L	12.08	9.72	7.13	<100
3.	Biochemical Oxygen Demand as BOD (3 days at 27°C)	IS:3025 (part 44)-1993, Reaffirmed -2019	mg/L	12	10	14	30
4.	Chemical Oxygen Demand as COD	APHA 23 <sup>rd</sup> Edition 2017 5220 C (Pg. No.5-19 to 5-20)	mg/L	42.65	37.48	40.02	50
5.	Oil & Grease	APHA 23rd Edition 2017 5520 B (Pg. No.5-40 to 5-41)	mg/L	3.94	Nil	Nil	10

Note: BDL-Below detectable Limit., INFERENCE: The Measured values are within the Limit.

STP 45 KLD - Near Fortivia

STP-1 90 KLD - Near ISP Area

STP-2 90 KLD - Near Gunda Guest House

Analysed By J. M. Thippeswamy Chemist

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

  Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

  This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

  The tests results marked with \* Recognised by MOEF & CC.

  Recognised by Mistance Recognised by MOEF & CC.
- 1. 2. 3. 4. 5. 6.
- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

Ph e-mail : +918394 229433, 295018 : gems\_hpt@yahoo.com

Website

: www.globalmining.in

**BMM STAGE-I** 

**ANNEXURE-25** GEMS-LD/TF/23/01

# **Analysis Report of Water Quality Data**

Name of the Industry 1 BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference** WO/ADMIN/FY22/RO38

3 Sample collected by **GLOBAL Environment & Mining Services** 

4 Particulars of sample collected Composite Sampling 5 Sampling Procedure GEMS-LD/SOP/32

6 Discipline Chemical

7 Group Pollution & Environment

8 Sample Type Waste Water 9 Date of Sampling 13.08.2021 10 Sample Received : 13.08.2021 11 Date of Analysis : 13.08.2021 Date of Analysis Completion : 21.08.2021

13 Report Issue Date : 03.09.2021

Report Number 14 ULR-TC532321000000711F

Sl. No.				Res		
	Parameters	Protocol	Unit	Neutralization Pit 70 MW Power Plant	Neutralization Pit 2x70 MW Power Plant	As per KSPCB Std
		Sam	ple Code	2280	2281	
1.	рН	APHA 23 <sup>rd</sup> Edition 2017 4500 B (Pg. No.4-92 to 4-96)	-	8.20	7.37	6.5 to 9.0
2.	Total Suspended Solids	APHA 23 <sup>rd</sup> Edition 2017 2540 D (Pg. No.2-66 to 2-67)	mg/L	13.41	21.86	100
3.	Chemical Oxygen Demand as COD	APHA 23 <sup>rd</sup> Edition 2017 5220 C (Pg. No.5-19 to 5-20)	mg/L	84.52	102.94	250
4.	Oil & Grease	APHA 23rd Edition 2017 5520 B (Pg. No.5-40 to 5-41)	mg/L	4.5	7.0	10

Note: BDL-Below detectable Limit

INFERENCE: The Measured values are within the Limit.

**Analysed By** J. M. Thippeswamy Chemist

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.
- 2. 3. 4. 5. 6.
- Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

  This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.
- The tests results marked with \* Recognised by MOEF & CC
- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane, HOSPET - 583201, Dist., Bellary (Karnataka)

Ph

: +918394 229433, 295018 : gems\_hpt@yahoo.com

e-mail Website

: www.globalmining.in

BMM STAGE-I

**ANNEXURE-26** GEMS-LD/TF/23/01

# **Analysis Report of Surface Water Quality Data**

Name of the Industry 1

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference**  WO/ADMIN/FY22/RO38

3 Sample collected by **GLOBAL Environment & Mining Services** 

4 Particulars of sample collected : Composite Sampling GEMS-LD/SOP/32

5 Sampling Procedure Discipline

6

: Chemical

7 Group Pollution & Environment

Sample Type 8

Surface Water

9 Date of Sampling : 13.08.2021

10 Sample Received

13.08.2021

11 Date of Analysis

: 13.08.2021

12 **Date of Analysis Completion** 

21.08.2021

13 Report Issue Date 03.09.2021

Report Number

ULR-TC532321000000712F

SI.	Parameters	Protocol		Res		
No.			Unit	Danayakanakere Upstream	Danayakanakere Downstream	IS 2296 - 1982
			Sample code	2282	2283	CLASS -B
1.	рН	APHA 23 <sup>RD</sup> Edition 4500 H+B (Pg. No.4-95 to 4-99)	-	7.50	7.65	6.5-8.5
2.	Dissolved Oxygen	APHA 23 <sup>RD</sup> Edition 4500 C (Pg. No.4-146)	mg/L	5.8	6.2	>5.0
3.	Biochemical Oxygen Demand as BOD (5 days at 20°C)	APHA 23 <sup>RD</sup> Edition 5210 B (Pg. No.5-6 to 5-10)	mg/L	2.5	2.0	3.0
4.	Fluorides (as F)	APHA 23 <sup>RD</sup> Edition 4500F-D (Pg. No.4-90 to 4-91)	mg/L	0.42	0.49	1.5
5.	Color	APHA 23 <sup>RD</sup> Edition 2120 B (Pg. No.2-6 to 2-7)	Hazen	8	10	300
6.	Cyanides (as CN)	APHA 23 <sup>RD</sup> Edition 4500 CN- (Pg. No.4-45 to 4-46)	mg/L	BDL	BDL	0.05
7.	Arsenic (as As)	APHA-23 RD Edition-3114 -B (Pg. No.3 -36 to 3-40)	mg/L	<0.01	01 <0.01	
8.	Phenolic Compounds (as C <sub>6</sub> H <sub>5</sub> OH)	IS:3025 (part 43)-1992, RA-2014, Chloroform extraction method	mg/L	BDL	BDL	0.005
9.	Chromium (as Cr <sup>6+)</sup>	APHA-23 <sup>RD</sup> Edition-3500 Cr B (Pg. No.3-71 to 3-72)	mg/L	<0.001	<0.001	1.0
10.	Anionic detergents (as MBAS)	APHA 23 <sup>RD</sup> Edition 5540 C (Pg. No.5-55 to 5-57)	mg/L	BDL	BDL	1.0
11.	Total Coliform Organisms					
	Total Coli forms	APHA 23 RD Edition 9221-C (Pg. No.9-72 to 9-74)	MPN/100 ml	Absent	Absent	500
	Escherichia coli or E. coli	APHA 23 RD Edition 9221-F (Pg. No.9-78 to 9-79)	MPN/100 ml	Absent	Absent	-

Note: BDL-Below detectable Limit

INFERENCE: The Measured values are within the Limit.

**Analysed By** J. M. Thippeswamy Chemist



- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

  Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

  This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only. 2. 3. 4. 5. 6.
- The tests results marked with \* Recognised by MOEF & CC Recognised by Ministry of Environment, Forest and Climate Change for Laboratory Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSPET - 583201, Dist., Bellary (Karnataka)

: +918394 229433, 295018

e-mail Website

: gems\_hpt@yahoo.com : www.globalmining.in

BMM STAGE-I

**ANNEXURE-27** GEMS-LD/TF/23/01

# **Analysis Report of Surface Water Quality Data**

1 Name of the Industry BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference** WO/ADMIN/FY22/RO38

3 Sample collected by **GLOBAL Environment & Mining Services** 

4 Particulars of sample collected **Composite Sampling** 5 Sampling Procedure GEMS-LD/SOP/32

6 Discipline Chemical

7 Group Pollution & Environment

8 Sample Type Surface Water 9 Date of Sampling 13.08.2021 Sample Received : 13.08.2021 11 Date of Analysis 13.08.2021 12 Date of Analysis Completion 21.08.2021

13 Report Issue Date 03.09.2021

Report Number ULR-TC532321000000713F

SI.	Parameters	Protocol		Res	IS 2296 - 1982	
No.			Unit	Tungabhadra dam Upstream Tungabhadra dam Downstream		
		San	iple Code	2284	2285	CLASS -B
1.	рН	APHA 23 <sup>RD</sup> Edition 4500 H+ B (Pg. No.4-95 to 4-99)	-	7.49	7.68	6.5-8.5
2.	Dissolved Oxygen	APHA 23 <sup>RD</sup> Edition 4500 C (Pg. No.4-146)	mg/L	5.6	5.8	>5.0
3.	Biochemical Oxygen Demand as BOD (5 days at 20°C)	APHA 23 <sup>RD</sup> Edition 5210 B (Pg. No.5-6 to 5-10)	mg/L	Nil	Nil	3.0
4.	Fluorides (as F)	APHA 23 <sup>RD</sup> Edition 4500F-D (Pg. No.4-90 to 4-91)	mg/L	0.28	0.59	1.5
5.	Color	APHA 23 <sup>RD</sup> Edition 2120 B (Pg. No.2-6 to 2-7)	Hazen	BDL	BDL	300
6.	Cyanides (as CN)	APHA 23 <sup>RD</sup> Edition 4500 CN- (Pg. No.4-45 to 4-46)	mg/L	BDL	BDL	0.05
7.	Arsenic (as As)	APHA-23 RD Edition-3114 -B (Pg. No.3 -36 to 3-40)	mg/L	<0.01	<0.01	0.2
8.	Phenolic Compounds (as C <sub>6</sub> H <sub>5</sub> OH)	IS:3025 (part 43)-1992, RA-2014, Chloroform extraction method	mg/L	BDL	BDL	0.005
9.	Chromium (as Cr <sup>6+)</sup>	APHA-23 <sup>RD</sup> Edition-3500 Cr B (Pg. No.3-71 to 3-72)	mg/L	<0.001 <0.001		1.0
10.	Anionic detergents (as MBAS)	APHA 23 <sup>RD</sup> Edition 5540 C (Pg. No.5-55 to 5-57)	mg/L	BDL	BDL	1.0
11.	Total Coliform Organisms,					
	Total Coli forms	APHA 23RD Edition 9221-C (Pg. No.9-72 to 9-74)	MPN/ 100 ml	Absent	Absent	500
	Escherichia coli or E. coli	APHA 23RD Edition 9221-F (Pg. No.9-78 to 9-79)	MPN/ 100 ml	Absent	Absent	-

Note: BDL-Below detectable Limit

INFERENCE: the measured values are within the Limit

**Analysed By** J. M. Thippeswamy Chemist

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied. 1. 2. 3. 4. 5. 6. 7
- Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

  This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing.
- Total liability of our laboratory is limited to the invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only. The tests results marked with \* Recognised by MOEF & CC
- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey



(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane.

HOSPET - 583201, Dist., Bellary (Karnataka)

Ph e-mail : +918394 229433, 295018 : gems\_hpt@yahoo.com

Website

: www.globalmining.in

BMM STAGE-I

**ANNEXURE-28** GEMS-LD/TF/23/01

# **Analysis Report of Surface Water Quality Data**

1 Name of the Industry BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference** 

WO/ADMIN/FY22/RO38

3 Sample collected by **GLOBAL Environment & Mining Services** 

4 Particulars of sample collected

**Composite Sampling** 

5 Sampling Procedure : GEMS-LD/SOP/32

6 Discipline Chemical

7 Group Pollution & Environment

8 Sample Type

9 Date of Sampling : Surface Water

10

13.08.2021

Sample Received

: 13.08.2021

11 Date of Analysis

13.08.2021

Date of Analysis Completion 12

: 21.08.2021

13 Report Issue Date : 03.09.2021

14 Report Number

: ULR-TC532321000000714F

SI.	Parameters	Protocol		Results		IS 2296 - 1982
No.			Unit	KempuHalla KempuHalla Upstream Downstream		
			Sample code	2286	2287	CLASS -B
1.	рН	APHA 23 <sup>RD</sup> Edition 4500 H+ B (Pg. No.4-95 to 4-99)	-	8.12	8.08	6.5-8.5
2.	Dissolved Oxygen	APHA 23 <sup>RD</sup> Edition 4500 C (Pg. No.4-146)	mg/L	5.8	5.4	>5.0
3.	Biochemical Oxygen Demand as BOD (5 days at 20°C)	APHA 23 <sup>RD</sup> Edition 5210 B (Pg. No.5-6 to 5-10)	mg/L	2.0	2.5	3.0
4.	Fluorides (as F)	APHA 23 <sup>RD</sup> Edition 4500F-D (Pg. No.4-90 to 4-91)	mg/L	1.12	1.06	1.5
5.	Color	APHA 23 <sup>RD</sup> Edition 2120 B (Pg. No.2-6 to 2-7)	Hazen	BDL	BDL	300
6.	Cyanides (as CN)	APHA 23 <sup>RD</sup> Edition 4500 CN <sup>-</sup> (Pg. No.4-45 to 4-46)	mg/L	<0.01	<0.01	0.05
7.	Arsenic (as As)	APHA-23 RD Edition-3114 – B (Pg. No.3 -36 to 3-40)	mg/L	BDL	BDL	0.2
8.	Phenolic Compounds (as C <sub>6</sub> H <sub>5</sub> OH)	IS:3025 (part 43)-1992, RA-2014, Chloroform extraction method	mg/L	<0.001	<0.001	0.005
9.	Chromium (as Cr <sup>6+)</sup>	APHA-23 <sup>RD</sup> Edition-3500 Cr B (Pg., No.3-71 to 3-72)	mg/L	BDL	BDL	1.0
10.	Anionic detergents (as MBAS)	APHA 23 <sup>RD</sup> Edition 5540 C (Pg. No.5-55 to 5-57)	mg/L	BDL	BDL	1.0
11.	Total Coliform Organisms,					
	Total Coli forms	APHA 23RD Edition 9221-C (Pg. No.9-72 to 9-74)	MPN/100 ml	Absent	Absent	500
	Escherichia coli or E. coli	APHA 23RD Edition 9221-F (Pg. No.9-78 to 9-79)	MPN/100 ml	Absent	Absent	-

Note: BDL-Below detectable Limit

INFERENCE: The Measured values are within the Limit

**Analysed By** J. M. Thippeswamy Chemist

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied. 1. 2. 3. 4.
- Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

  This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

  The tests results marked with \* Recognised by MOEF & CC
- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey