

ENVIRONMENTAL MONITORING REPORT



Danapur Village, Hosapete Taluk, Vijayanagara District, PIN-583222, Karnataka.

STAGE-II

SEPTEMBER - 2022

Prepared by



GLOBAL ENVIRONMENT & MINING SERVICES

NABL & MOEFCC Recognized Laboratory

(Consulting Engineers, Mine Designers, Geologists & Surveyors) 3rd main road, Basaveswara badavane

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

Tel : 08394 229433 & 295018

e-mail : gems_hpt@yahoo.com

Website : www.globalmining.in

STAGE-2

PREFACE

The industries should monitor environmental parameters as per the frequency and locations given in the CFE/CFO. And the same should be submitted on every month to the

respective pollution control board.

As part of the conditions and inherent concern on health of the employees and

surroundings M/s. BMM Ispat Ltd., as appointed M/s. Global Environment & Mining Services,

Hosapete, to carry out the environmental pollution monitoring on AAQ Monitoring, Fugitive

monitoring within the plant, Stack monitoring submit the same to the Pollution Control

Board.

Accordingly, M/s. Global Environment & Mining Services, Hosapete, carried out the pollution

monitoring as per the standard sampling methods prescribed by CPCB, for AAQ Monitoring,

Fugitive monitoring within the plant, Stack monitoring & Personal Dust Sampling as per the

CFO. These monitoring has been carried out in a frequency as mentioned in the CFO and the

same report is being submitted to the Board.

We sincerely thank to officials of M/s. BMM Ispat Ltd., for their valuable co-ordination &

support during the sampling and reporting.

for GLOBAL Environment & Mining Services

Place: Hosapete Date:04.10.2022

K. Ramakrishna Reddy

(Technical Manager)



1.0 EXECUTIVE SUMMARY

1.1 INTRODUCTION

The journey of the BMM Group is a reflection of the path tread by every entrepreneur who believes in the human potential and one's own ability to bring about a life affirming change that transcends time. BMM Group was born out of this committed belief of Late Shri UdaichandSinghi.

Entrenched in the Indian ethos, with an astute understanding of market needs, values and sensibilities *Mr. Dinesh Kumar Singhi* inherited the legacy from his father and has built the BMM Group on sound fundamentals since 1998. He steered the company towards growth by being the first mining company to establish a power generation plant for captive use, and creating a steel plant from the captive ore mine. Over the last 12 years, BMM has been able to add value to every relationship under his able and dynamic leadership.

Today, BMM is a 4900 Crores Company due to its focus on market orientation and optimal usage of technology to achieve process efficiency and value addition. BMM has always believed in the principle of sharing and hence continues to transfer this benefit derived from sustained growth to its employees, partners and associates. The unique value proposition that defines the very fabric of the BMM culture is the firm's belief in unleashing this 'potential in tones' in terms of its human capital, continuous growth and consistent benefits to its stakeholders.

The human potential at BMM is reflected in the depth of domain expertise across diverse sectors and dynamism of youth at various levels in the Organization. Business operations lead by professionals with decades of market understanding and a dynamic team enables BMM to deliver superior product quality. This human potential keeps BMM attuned to scaling new heights and meeting customer expectations. While consistently adding value to its partners, BMM is sensitive to its responsibility towards the environment by implementing best practices in its Business Operations and contribution to society through various social Endeavors.

BMM has a commitment of being a good Corporate Citizen and is committed to achieving business goals through ethical means. BMM hence has been able to have deeper relevance to society by creating value that is inclusive and truly benefits all.





1.2 PROMOTERS OF THE PROJECT

BMM Group, one of the leading Steel, Power & Mining companies in India that has achieved the present level under the leadership and guidance of **Sri. Dinesh Kumar Singhi**, the Founder & Chairman of the group, is promoting the project. His vision is to globalize the company business and do value addition by operating responsibly and in a sustainable manner in exploring, exploiting, excavating and processing minerals followed by setting up steel plant facilities.

BMM is a step towards forward integration has set up new merchant Bar Mill. The works is located at:

BMM ISPAT LIMITED

(Registered Office & Works) #114, Danapur Hosapete - 583 222 Vijayanagara Dist., Karnataka Phone +91 08394-264000, +91 9686550808/09 Fax - 08394 264010

1.3 Site Location

BMM ISPAT LIMITED is located at Danapur about 15 Kms away from Hosapete in Karnataka. The plant site can be connected by national highway, viz. NH-13. The plant is 1 km away from the NH-13 near Danapur village. The nearest railway station is Hospet; Bangalore is at a distance of 300 kms. Seaport is Belikere and Karwar, the nearest Airport is in the private sector belonging to JSW, a Jindal Group company at Thoranagallu (Vidyanagara).



M/s. BMM ISPAT Ltd., Has accorded Environmental Clearance for 2.0 MTPA Integrated Steel Plant, with the following facilities.

S.N.	Items	Capacity
1	Iron ore beneficiation plant	3.40 MTPA
2	Palletizing Plant	1.20 MTPA
3	DRI Plant	0.70 MTPA
4	Coke Oven	0.80 MTPA
5	Sinter Plant	2.50 MTPA
6	Blast furnace	1.70 MTPA
7	EAF & BOF Steel making shop	2.30 MTPA
8	Continuous casting machines Slab Caster Billet Caster	1.10 MTPA 1.10 MTPA
9	Rolling mills: Hot strip mill Structural/wire rods	1.00 MTPA 1.00 MTPA
10	Oxygen Plant	2x500 TPD
11	Calcining	1,080 TPD
12	Cement Plant	1.40 MTPA
13	Power Plant	230 MW

Out of the above units, presently 4 x 500 TPD Sponge Iron Plants and 1X70 MW Thermal Power Plants have been commissioned on August 2011. Beneficiation plant-2, Pellet Plant-2 are commissioned on March 2012. 2X70 MW Thermal based power plants have commissioned on Jan 2013, EAF, Steel Making Shop, CCM, Rolling Mill, Oxygen plants are commissioned on August 2015. Remaining units are under various stages of implementation.

Hence environmental pollution monitoring is being carried out for 4 x 500 TPD sponge iron plants, 1X70 MW Thermal Power Plant, 1.3MTPA Beneficiation, 1.2MTPA Pellet Plant, 2X70MW Power plant, SMS, and RML.

- 1.4 The report includes environmental monitoring data collected at above site for the month of September-2022. The Parameters monitored are:
 - Ambient Air Quality
 - · Fugitive Dust Level
 - Stack Emission



2.0 SCOPE AND METHODOLOGY

2.1 PREAMBLE

The scope of the study and the present report covers the detailed characterization of the existing environmental status in and around the plant area for major environmental components viz. Ambient & work zone air quality, Fugitive Emission, Noise level and water quality & Stack Emission.

2.2 AMBIENT AIR QUALITY

To assess the ambient air quality status, monitoring stations were identified 6 Location plant site. Work zone air monitoring stations were identified in the major work spots. Based on the production activities the parameters chosen for ambient air quality. Were Particulate Matter PM10, Particulate Matter (size less than $2.5\mu m$) PM2.5.

2.2.1 PARTICULATE MATTER (PM10)(size less than 10μm).

Purpose

The purpose of this protocol is to provide guidelines for monitoring and analysis of Particulate Matter PM10 in ambient air

Reference Method: IS 5182 Part 23 Method of Measurement of Air Pollution: Respirable Suspended Particulate Matter (PM10) cyclonic flow technique.

Principle of the method

Air is drawn through a size-selective inlet and through a 20.3 X 25.4 cm (8 X 10 in) filter at a flow rate, which is typically 1132 L/min. Particles with aerodynamic diameter less than the cut-point of the inlet are collected, by the filter. The mass of these particles is determined by the difference in filter weights prior to and after sampling. The concentration of PM10 in the designated size range is calculated by dividing the weight gain of the filter by the volume of air sampled.

Sampling

Field Sampling - Tilt back the inlet and secure it according to manufacturer's instructions. Loosen the faceplate wing nuts and remove the faceplate. Remove the filter from its jacket and centre it on the support screen with the rough side of the filter facing upwards. Replace the faceplate and tighten the wing nuts to secure the rubber gasket against the filter edge. Gently lower the inlet. For automatically flow-



controlled units, record the designated flow rate on the data sheet. Record the reading of the elapsed time meter. The specified length of sampling is commonly 8 hours or 24 hours. During this period, several reading (hourly) of flow rate should be taken. After the required time of sampling, record the flow meter reading, take out the filter media from the sampler, and put in a container or envelope.

Analysis

Filter inspection: Inspect the filter for pin holes using a light table. Loose particles should be removed with a soft brush. Apply the filter identification number or a code to the filter if it is not a numbered. Condition the filter in conditioning room maintained within 20-30° C and 40-50% relative humidity or in an airtight desiccator for 24 hours. Take initial weight of the filter paper (Wi) before sampling. Condition the filter after sampling in conditioning room maintained within 20-30° C and 40-50% relative humidity or in an airtight desiccator for 24 hours. Take final weight of the filter paper (Wf).

2.2.2 Particulate Matter (PM2.5)(size less than 2.5μm)

Purpose

The purpose of this protocol is to provide guidelines for monitoring and analysis of Particulate Matter PM2.5 in ambient air.

<u>Reference Method:</u> USEPA 2001 Method of Measurement of Air Pollution: Particulate Matter (PM2.5) cyclonic flow technique.

Principle

An electrically powered air sampler draws ambient air at a constant volumetric flow rate (16.7 lpm) maintained by a mass flow / volumetric flow controller coupled to a microprocessor into specially designed inertial particle-size separator (i.e. cyclones or impactors) where the suspended particulate matter in the PM2.5 size ranges is separated for collection on a 47 mm polytetrafluoroethylene (PTFE) filter over a specified sampling period. Each filter is weighed before and after sample collection to determine the net gain due to the particulate matter. The mass concentration in the ambient air is computed as the total mass of collected particles in the PM2.5 size ranges divided by the actual volume of air sampled, and is expressed in µg/m3. The microprocessor reads averages and stores five-minute averages of ambient temperature, ambient pressure, filter temperature and volumetric flow rate. In



addition, the microprocessor calculates the average temperatures and pressure, total volumetric flow for the entire sample run time and the coefficient of variation of the flow rate.

2.2.3 Sulphur Dioxide (SO2)

<u>Purpose:</u> The purpose of this protocol is to provide guidelines for monitoring and analysis of sulphur dioxide in ambient air.

Reference Method: Modified West &Gaeke Method (IS 5182 Part 2 Method of Measurement of Air Pollution: Sulphur dioxide).

Sulphur dioxide from air is absorbed in a solution of potassium tetra chloromercurate (TCM). A dichlorosulphitomercurate complex, which resists oxidation by the oxygen in the air, is formed. Once formed, this complex is stable to strong oxidants such as ozone and oxides of nitrogen and therefore, the absorber solution may be stored for some time prior to analysis. The complex is made to react with para-rosaniline and formaldehyde to form the intensely coloured pararosaniline methyl sulphonic acid. The absorbance of the solution is measured by means of a suitable spectrophotometer.

Sampling

Place 30 ml of absorbing solution in an impinger and sample for four hours at the flow rate of 1 L/min. After sampling measure the volume of sample and transfer to a sample storage bottle.

Analysis

Replace any water lost by evaporation during sampling by adding distilled water up to the calibration mark on the absorber. Mix thoroughly, pipette out 10 ml of the collected sample into a 25 ml volumetric flask. Add 1 ml 0.6% sulphamic acid and allow reacting for 10 minutes to destroy the nitrite resulting from oxides of nitrogen. Add 2 ml of 0.2% formaldehyde solution and 2 ml pararosaniline solution and make up to 25 ml with distilled water. Prepare a blank in the same manner using 10 ml of unexposed absorbing reagent. After a 30 min colour development interval and before 60 minutes, measure and record the absorbance of samples and reagent blank at 560 nm. Use distilled water; not the reagent blank, as the optical reference.



2.2.4 Nitrogen Di Oxide (NO₂):

Purpose

The purpose of this protocol is to provide guidelines for monitoring of nitrogen dioxide in ambient.

Principle of the method

Modified Jacobs & Hochheiser Method (IS 5182 Part 6 Methods for Measurement of Air Pollution: Oxides of nitrogen)

Ambient nitrogen dioxide (NO2) is collected by bubbling air through a solution of sodium hydroxide and sodium arsenite. The concentration of nitrite ion (NO2) produced during sampling is determined calorimetrically by reacting the nitrite ion with phosphoric acid, sulfanilamide, and N-(1-naphthyl)- ethylenediamine dihydrochloride (NEDA) and measuring the absorbance of the highly coloured azo-dye at 540 nm.

2.2.5 Ozone (Chemical method)

Purpose

The purpose of this protocol is to provide guidelines for monitoring of ozone in ambient air.

Principle of the method

Micro-amounts of ozone and the oxidants liberate iodine when absorbed in a 1% solution of potassium iodine buffered at pH 6.8 + 0.2. The iodine is determined spectrophotometrically by measuring the absorption of tri-iodide ion at 352 nm.

Sampling

Place 10 ml of absorbing solution in a standard impinger and sample for one hour at the flow rate of 1 L/min. Do not expose the absorbing reagent to direct sunlight. After sampling measure the volume of sample and transfer to a sample storage bottle.

Analysis

If, appreciable evaporation of the absorbing solution occurs during sampling, add water to bring the liquid volume to 10 ml. Within 30 to 60 minutes after sample collection, read the absorbance in a cuvette at 352 nm against a reference cuvette containing distilled water. Measure the absorbance of the unexposed reagent and subtract the value from the absorbance of the sample.



2.2.6 Ammonia (NH_3)

Purpose

The purpose of this protocol is to provide guidelines for monitoring of ammonia in ambient air.

Principle of the method

Indophenol method Ammonia in the atmosphere is collected by bubbling a measured volume of air through a dilute solution of sulphuric acid to form ammonium sulphate. The ammonium sulphate formed in the sample is analysed calorimetrically by reaction with phenol and alkaline sodium hypochlorite to produce indophenol. The reaction is accelerated by the addition of Sodium Nitroprusside as catalyst.

Sampling

Place 10 ml of absorbing solution in an impinger and sample for one hour at the flow rate of 1 to 2 L/min. After sampling measure the volume of sample and transfer to a sample storage bottle

Analysis

Transfer contents of the sample bottle to a 25 ml glass stopper graduated cylinder. Maintain all the solutions and sample at 25° C. Add 2 ml buffer. Add 5 ml of working phenol solution, mix, and fill to about 22 ml. Add 2.5 ml of working hypochlorite solution and rapidly mix. Dilute to 25 ml, mix and store in the dark for 30 minutes to develop colour. Measure the absorbance of the solution at 630 nm on a spectrophotometer using 1 cm cells. Prepare a reagent blank and field blank and measure the absorbance as done in the analysis of samples.

2.2.7 Benzo(a)Pyrene

Purpose

The purpose of this protocol is to provide guidelines for monitoring of Benzo (a) Pyrene (BaP) in ambient air.

Principle of the Method

It is based on BIS method IS 5182 (Part 12):2004 and USEPA method (TO-13). This method is designed to collect particulate phase PAHs in ambient air and fugitive emissions and to determine individual PAH compounds using capillary gas chromatograph equipped with flame ionization detector. It is a high volume



(1.2m3/min) sampling method capable of detecting sub.ng/m3 concentration of PAH in 24 hours sample (i.e., collected in 3 shifts of 8 hour each with 480 m3 sampling volume of air).

Sampling

24 hr. sampling using PM10 high volume sampler with 8 hourly samples using EPM 2000 glass fibre or equivalent filter.

Sample Processing

Extraction: Filter papers (half of all the filters papers collected in a day) are cut into strips using scissors and transfer to 250 ml beaker. Add \sim 50 ml. of Toluene (GC/HPLC grade). These samples are extracted with toluene using ultra sonic bath for about 30 minutes. Repeat the procedure twice (50ml x 2 times) for complete extraction. Alternatively, sample can be extracted using soxhlet extraction apparatus for about 8 hr. with Toluene and repeat it twice.

Filtration

Filter the extracted samples with Whatman filter paper no.41 containing 2 gm of Anhydrous Sodium Sulphate (to remove moisture).

Sample injection

Take $2\mu l$ of sample from the amber vial using standard gas tight syringe and inject in the Capillary GC-FID instrument for analysis. Record the resulting concentration of each PAH compound including B(a)P. A $10ng/\mu l$ concentration B(a)P or other PAH standards are to be injected in GC/FID instrument with every batch of samples. As a control Internal Standard of 10 $ng/\mu l$ conc. is added to each sample prior to the analysis in case of internal calibration is used.

2.2.8 Benzene

Samples collected through active sampling (sorbent tubes) are extracted or desorbed by conventional solvent (generally 1-5 ml of carbon disulphide) using ultrasonication for 15 min to remove analyte from the sorbent material. Desorbed samples are analyzed using gas chromatograph (GC) fitted with capillary column and flame ionization detector (FID). A single tube may provide enough samples to permit several analyses.



Principle of the Method

IS 5182 (Part 11): 2006, the charcoal tubes are available in different sizes and contain varying amount of activated charcoal. The ambient air is sucked through the tube using a low flow sampler used for collection of BTX sample in a way that results in an enrichment of the relevant substances in the activated charcoal. Desorption of the adsorbed benzene is done using carbon disulphide (CS2). The substances desorbed in the CS2 are analyzed by capillary gas chromatography. A flame ionization detector (FID) is used for analysis while quantification is performed using the internal/external standard.

Gas Chromatograph

Any suitable gas chromatograph with flame ionization detector (FlO) with fused silica capillary columns having a length of 25 m or more, an internal diameter of 320 11m or below and with a stationary phase film thickness less than 1.5 11m as follows or equivalent may be recommended.

Sampling

Selection of Sorbent Tube '- Samples are collected in glass sampling tube filled with an activated charcoal (coconut shell), Chromo sorb 106 or other suitable adsorbent.

Analytical Procedure

Samples collected through active sampling (sorbent tubes) are extracted or desorbed by conventional solvent (generally 1-5 ml of carbon disulphide) using ultrasonication for 15 min to remove analyte from the sorbent material. Desorbed samples are analysed using gas chromatograph (GC) fitted with capillary column and flame ionization detector (FID). A single tube may provide enough samples to permit several analyses.

2.2.9 <u>Carbon Monoxide (CO)</u>

Principle:

Samples containing carbon monoxide in the range of 0 to 100 mg/l are analysed on a non-dispersive infrared absorption gas analyser, namely, an electro-optical spectrophotometer with no spectral dispersion component. It may consist of a single or double source of infrared energy and one or more infrared detectors separated by an optical cell or cells through one or more of which the sample flows, whereby the specific spectral absorption of the component of interest is determined.



Non dispersive Infrared (NDIR) Gas Analyser

The apparatus shall be constructed so as to be suitable for operating within the temperature range of 15°C to 40°C and in a relative humidity range of 0 to 90 percent. The apparatus shall embody facilities for the analysis of continuously applied sample or a discrete sample of volume of 2.0 litres. In the later case the purification train shall be of such a design and dead volume that 2.0 litres Pis adequate for its proper flushing out. The apparatus shall include facilities for the visual inspection of results and also for their recording. The scale shall be divided into steps of 1.0 percent full scale division (fsd).

Though the basic instrument recommended is for (0 to 100) mg/l range, for samples of higher mg/l range the instrument may be used with proper dilution and conditioning of the samples.

2.2.10 Lead (Pb), Nickel (Ni) & Arsenic (As)

Purpose

The purpose of this protocol is to provide guidelines for monitoring of Lead (Pb), Nickel (Ni) & Arsenic (As) in ambient air.

Principle of the method

The Atomic Absorption Spectroscopy (AAS) technique makes use of absorption spectrometry to assess the concentration of an analyte in the sample. The method is based on active sampling using PM10 Respirable Dust Sampler and then sample analysis is done by atomic absorption spectrophotometer.

Sampling procedure

Tilt back the inlet and secure it according to manufacturer's instructions. Loosen the face-plate wing-nuts and remove the face plate. Remove the filter from its jacket and centre it on the support screen with the rough side of the filter facing upwards. Replace the face-plate and tighten the wing-nuts to secure the rubber gasket against the filter edge. Gently lower the inlet. For automatically flow-controlled units, record the designated flow rate on the data sheet. Record the reading of the elapsed time meter. The specified length of sampling is commonly 8 hours or 24 hours. During this period, several reading (hourly) of flow rate should be taken. After the required time of sampling, record the flow meter reading and take out the filter media from the sampler and put in a container or envelope.

3.0 Fugitive Emission Monitoring

Fugitive air quality was monitored 40 samples were collected from the analyzed for SPM analyzed by gravimetric method. Work Zone Air quality was monitored at all Plant area and material handling area.

4.0 Stack Monitoring

Stack Monitoring was Collected 60 Sample from Vayubodhan Stack sampler VSS1 stack monitoring was used for drawing the flue gas. Sulphur dioxide and oxides of Nitrogen in the flue gas was sampled by bubbling flue gas solution respectively and the analyses of the pollutants were done as per the Indian Standard procedures prescribed by CPCB/BIS. Stack Emission level was monitored as per the statutory requirement on twice in a month.

4.1 Stack Emissions Monitoring Methodology

Sampling Procedure

Pre-Sampling Activities

Weigh the properly conditioned thimble/filter and place it into the clean, air tight Container. Designate appropriate label or ID No. to each thimble/filter container. Particulate matter emission of "Stack Monitoring – Material and Methodology for is kinetic Sampling.

Field activity starts with the collection of detailed information from the industry about the products, raw materials, fuels, and stack dimensions.

4.2 Traverse Point Calculation

Calculate the traverse point and accordingly mark the distance from tip of the Nozzle, on Pitot tube and probe. Do not forget to add the collar length of port to the calculated traverses. For detailed calculation of "Stack Monitoring- Material and Methodology for isokinetic sampling.

4.3 Determination of Dust Concentration

Determine the mass of dust collected in the thimble by difference i.e., weighing the thimble before and after the run. Dry the thimble in an oven for about 2 hours at 120°C prior to sampling. After sampling, cool, dry and again weigh the thimble along with dust maintaining the same condition as prior to sampling.



DATA ANALYSIS

4.4 <u>BUFFERZONE AMBIENT AIR QUALITY STATUS</u> Danapur Village (A1)

At this location, average of PM10, PM2.5, SO2, NO2 values Average 60.78, 17.06, $10.79 \& 13.32 \ \mu g/m^3$ respectively. All above the values were found within the Limits. And the results given in **Annexure-1**.

Mariyammanahalli Village (A2)

At this location, average of PM10, PM2.5, SO2, NO2values Average 58.16, 16.28, 9.47 & 12.46 μg/m³respectively. All above the values were found within the Limits. And the results given in **Annexure-2**.

Hanumanahalli Village (A3)

At this location, average of PM10, PM2.5, SO2, NO2 values Average 56.98, 15.12, $9.02\&11.65~\mu g/m^3$ respectively. All above the values were found within the Limits. Results given in **Annexure-3**.

Galemmanagudi Village (A4)

At this location, average of PM10, PM2.5, SO2, NO2 values Average 52.35, 14.72, $7.53\&10.08~\mu g/m^3$ respectively. All above the values were found within the Limits. Results given in **Annexure-4**.

Gunda Village (A5)

At this location, average of PM10, PM2.5, SO2, NO2 values Average 50.18, 14.15, $7.68\&10.39~\mu g/m^3$ respectively. All above the values were found within the Limits. Results given in **Annexure-5**.

Gunda Tanda Village (A6)

At this location, average of PM10, PM2.5, SO2, NO2 values Average 54.47, 15.26, $8.24\&10.90~\mu g/m^3$ respectively. All above the values were found within the Limits. Results given in **Annexure-6**.



5.1 FUGITIVE DUST CONCENTRATION

Fortnightly fugitive air quality was monitored all plant area SPM value minimum $264.44 \mu g/m^3$, maximum value $1720.71 \mu g/m^3$ and average value $829.27 \mu g/m^3$. The Fugitive air quality 1^{st} & 2^{nd} Fortnight Results given in **Annexure-7** & **Annexure-8**.

5.2 STACK MONITORING

Stack emission level was monitored all chimneys' PM values (mg/Nm³) 1st and 2ndFortnight Minimum Value 12.40mg/Nm³, Maximum Value 55.80mg/Nm³& Average Value 29.41mg/Nm³. 1st& 2nd Fortnight Results are given in Annexure-9& Annexure-21.

5.3 CONCLUSION

All the monitored Environmental parameters were found to be well within the statutory norms and the same are enclosed as follows.





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

Ph : +918394 355369, 295018 e-mail : gems_hpt@yahoo.com

Website : www.globalmining.in



ANNEXURE-01 GEMS-LD/TF/11/01

ANALYSIS REPORT OF AMBIENT AIR QUALITY DATA

Name of the Industry BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

Customer Reference WO/ADMIN/FY23/R073 Sample collected by

Global Environment & Mining Services

Discipline Chemical

Group Atmospheric Pollution

Sample Type **Ambient Air Quality Monitoring**

Particulars of Sample Collected Respirable Dust Sampler, FPS Sampler

Month SEPTEMBER-2022 Location A1-Danapur Village

Duration of Monitoring 24 Hour Report Issued Date 04.10.2022

Report Number ULR-TC532322000000688F

RESULTS

	Parameters		PM [μg/		PM [μg/	Telephone .	SO [µg/		No [µg/	El Triese
	Reference Method		IS:5182: 2006		IS:5182: (Part-6) 2006 (RF-2017)					
Date of Sampling	Date of Sample Received	Sample Code	Result	STD	Result	STD	Result	STD	Result	STD
05.09.2022	06.09.2022	2415	59.81		16.70		10.07		13.58	
06.09.2022	07.09.2022	2441	65.57	1	18.70		8.30		9.89	
12.09.2022	13.09.2022	2531	56.90	56.90	15.97		11.74		15.03	
13.09.2022	14.09.2022	2555	69.59		19.64		10.85		11.34	
19.09.2022	20.09.2022	2715	52.69	100	14.25	60	9.52	80	15.96	80
20.09.2022	21.09.2022	2743	49.87		13.67		9.96		10.81	
26.09.2022	27.09.2022	2856	69.60	1	19.98		12.07		17.28	
27.09.2022	28.09.2022	2875	62.20		17.53	13.84		12.66		
	Average		60.78		17.06		10.79		13.32	

SLNO	INSTRUMENT DETAILS							
1	Instrument Name	Respirable Dust Sampler (RDS)	Fine Particulate Sampler (FPS)					
2	Make & Model	Enviro instruments / AAS-217 BL	Enviro instruments / El-133					
3	Serial No	R.D.S. / 14-A-142	PM2.5/PM10 Sampler / 158-K-20					
4	Calibration Date	01.04.2022	07.03.2022					
5	Calibration Due Date	31.03.2023	06.03.2023					

As per NAAQMS Standards (2009), INFERENCE Report Status: • Measured Values for the above parameters are within the limit.

> Analysed By Rukmini G Chemist



- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

 Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

 This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

Ph: +918394355369,295018 e-mail: gems_hpt@yahoo.com Website: www.globalmining.in

> ANNEXURE-01 GEMS-LD/TF/11/01

ANALYSIS REPORT OF AMBIENT AIR QUALITY DATA

Name of the Industry

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

Customer Reference

WO/ADMIN/FY23/R073

Sample collected by

Global Environment & Mining Services

Discipline

Chemical

Group

Atmospheric Pollution

Sample Type

Ambient Air Quality Monitoring

Particulars of Sample Collected

CO Analyser

Month

SEPTEMBER-2022 A1-Danapur Village

Location

: 1 Hour

Duration of Monitoring Report Issued Date

: 04.10.2022

RESULTS

Sì. No.	Date of Sampling	Sample Code	CO (1 Hour) [mg/m³]	Standard
1	05.09.2022	2415	0.12	
2	06.09.2022	2441	0.16	1
3	12.09.2022	2531	0.11	1
4	13.09.2022	2555	0.13	1
5	19.09.2022	2715	0.15	4.0
6	20.09.2022	2743	0.12	1
7	26.09.2022	2856	0.09	1
8	27.09.2022	2875	0.08	

Note: CO - GEMS/SOP/86/as per CO Analyzer Manual (1 Hour)

ND - Not Detected

SL NO	INS	INSTRUMENT DETAILS				
1	Instrument Name	CO Gas Detector				
2	Make & Model	Vasthi Instruments Pvt Ltd & VS-70-70-CC				
3	Serial No	180883821				
4	Calibration Date	09.07.2022				
5	Calibration Due Date	08.07.2023				

INFERENCE As per NAAQMS Standards (2009),
Report Status: - Measured Values for the above parameters are within the limit

Ruy ln. Analysed By Rukmini G Chemist Verified By Chemist

- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory
- Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

Ph : +918394 355369, 295018 e-mail : gems_hpt@yahoo.com

Website : www.globalmining.in



TC-5323

ANNEXURE-02 GEMS-LD/TF/11/01

ANALYSIS REPORT OF AMBIENT AIR QUALITY DATA

Name of the Industry

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

Customer Reference

WO/ADMIN/FY23/R073

Sample collected by

Global Environment & Mining Services

Discipline

Chemical

Group

Atmospheric Pollution

Sample Type

Ambient Air Quality Monitoring

Particulars of Sample Collected

Respirable Dust Sampler, FPS Sampler

Month

SEPTEMBER-2022

Location **Duration of Monitoring** A2-Mariyammanahalli Village

Report Issued Date

24 Hour 04.10.2022

Report Number

ULR-TC532322000000689F

RESULTS

Parameters		РМ [µg/I	2000	PM [µg/	53335	SC [µg/	100 mars	NC [μg/	2000	
	Reference Method		IS:5182: 2006 (Part-23) (RF-2017)		USEPA 2001 Gravimetric Method		IS:5182: 2001 (Part-2) (RF-2017)		IS:5182: (Part-6) 2006 (RF-2017)	
Date of Sampling	Date of Sample Received	Sample Code	Result	STD	Result	STD	Result	STD	Result	STD
05.09.2022	06.09.2022	2416	58.87		16.71		10.19		12.27	
06.09.2022	07.09.2022	2442	66.66	1	18.96		6.64		9.36	
12.09.2022	13.09.2022	2532	48.79	1	13.76	11.07		12.13		
13.09.2022	14.09.2022	2556	65.89	1	18.03		8.41		13.85	
19.09.2022	20.09.2022	2716	55.17	100	15.72	60	10.96	80	11.34	80
20.09.2022	21.09.2022	2744	69.28		19.29		7.53		13.72	
26.09.2022	27.09.2022	2857	51.33	1	14.41	İ	11.74		15.03	
27.09.2022	28.09.2022	2876	49.31	1	13.38	Ī	9.19		10.42	
	Average		58.16		16.28		9.47		12.46	

SL NO	INSTRUMENT DETAILS							
1	Instrument Name	Respirable Dust Sampler (RDS)	Fine Particulate Sampler (FPS)					
2	Make & Model	Enviro instruments / APM -460BL	Enviro instruments / EI-133					
3	Serial No	R.D.S./330-DTF-2005	PM2.5 /PM10 Sampler / 159-K-20					
4	Calibration Date	01.04.2022	07.03.2022					
5	Calibration Due Date	31.03.2023	06.03.2023					

INFERENCE

As per NAAQMS Standards (2009),

Report Status: - Measured Values for the above parameters are within the limit.

Analysed By Rukmini G Chemist

B P Lingaraja Chemist

Note:

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

 Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

 This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing.
- Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only. Recognised by Ministry of Environment, Forest and Climate Change for Laboratory
- Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

Ph

: +918394 355369, 295018

: gems_hpt@yahoo.com Website : www.globalmining.in

> ANNEXURE-02 GEMS-LD/TF/11/01

ANALYSIS REPORT OF AMBIENT AIR QUALITY DATA

Name of the Industry

Customer Reference

Sample collected by

Discipline

Group

Sample Type

Particulars of Sample Collected

Month

Location

Duration of Monitoring

Report Issued Date

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

WO/ADMIN/FY23/R073

Global Environment & Mining Services

Chemical

Atmospheric Pollution

Ambient Air Quality Monitoring

CO Analyser

SEPTEMBER-2022

A2-Mariyammanahalli Village

1 Hour

04.10.2022

RESULTS

SI. No.	Date of Sampling	Sample Code	CO (1 Hour) [mg/m³]	Standard
1	05.09.2022	2416	0.13	
2	06.09.2022	2442	0.10	
3	12.09.2022	2532	0.21	
4	13.09.2022	2556	0.19	
5	19.09.2022	2716	0.12	4.0
6	20.09.2022	2744	0.15	
7	26.09.2022	2857	0.11	
8	27.09.2022	2876	0.09	1

Note: CO - GEMS/SOP/86/as per CO Analyzer Manual (1 Hour)

ND - Not Detected

SL NO	INSTRUMENT DETAILS				
1	Instrument Name	CO Gas Detector			
2	Make & Model	Vasthi Instruments Pvt Ltd & VS-70-70-C0			
3	Serial No	190883821			
4	Calibration Date	09.07.2022			
5	Calibration Due Date	08.07.2023			

As per NAAQMS Standards (2009), INFERENCE Report Status: - Measured Values for the above parameters are within the limit

Rukmini G Chemist

Chemist

- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory
- Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane.

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

Ph : +918394 355369, 295018

e-mail : gems_hpt@yahoo.com Website : www.globalmining.in



TC-5323

ANNEXURE-03 GEMS-LD/TF/11/01

ANALYSIS REPORT OF AMBIENT AIR QUALITY DATA

Name of the Industry

Customer Reference

Sample collected by

Discipline Group

Sample Type

Particulars of Sample Collected

Month Location

Duration of Monitoring Report Issued Date

Report Number

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

WO/ADMIN/FY23/R073

Global Environment & Mining Services

Chemical

Atmospheric Pollution

Ambient Air Quality Monitoring

Respirable Dust Sampler, FPS Sampler

SEPTEMBER-2022

A3-Hanumanahalli Village

24 Hour

04.10.2022

ULR-TC532322000000690F

RESULTS

			T	AAAAAA	T T					
Reference IS:5:		PM [µg/	The state of the s	PM [μg/i		SO [μg/ι	5/m	NO [μg/		
		(Part-23) Gravimetric (Part-2) (Part-2)		(Part-23)		: 2006 USEPA 2001 IS:5182: 2001 -23) Gravimetric (Part-2)		(Part-23) Gravimetric (Part-2)		IS:5: (Part-6 (RF-2
Date of Sampling	Date of Sample Received	Sample Code	Result	STD	Result	STD	Result	STD	Result	STD
05.09.2022	06.09.2022	2417	67.40		18.88		9.19		13.06	
06.09.2022	07.09.2022	2443	56.99	1	15.84		7.53		9.63	
12.09.2022	13.09.2022	2533	61.27	1	17.19		11.85 9.52	1	13.98	
13.09.2022	14.09.2022	2557	53.04		14.98				12.66	
19.09.2022	20.09.2022	2717	48.82	100	13.35	60	6.75	80	9.76	80
20.09.2022	21.09.2022	2745	59.91	1	16.86		8.97		10.95	
26.09.2022	27.09.2022	2858	45.97		12.82		8.30		11.01	
27.09.2022	28.09.2022	2877	62.42		17.40		10.07		12.13	
	Average		56.98		15.92		9.02		11.65	

SLNO	INSTRUMENT DETAILS							
1	Instrument Name	Respirable Dust Sampler (RDS)	Fine Particulate Sampler (FPS)					
2	Make & Model	Greentech instruments / GTI -151	Enviro instruments / EI-133					
3	Serial No	R.D.S./242-DTC-2020	PM2.5 /PM10 Sampler / 160-K-20					
4	Calibration Date	01.04.2022	07.03.2022					
5	Calibration Due Date	31.03.2023	06.03.2023					

INFERENCE

As per NAAQMS Standards (2009),

Report Status: - Measured Values for the above parameters are within the limit.

Rukmini G Chemist



- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied. Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.
- Water Samples will be destroyed after 1917ays, Minerals 3 Months, Finer papers & Immotes After analysis Discard.

 This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total Hability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

 Recognised by Ministry of Environment, Forest and Climate Change for Laboratory

 Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

Ph: +918394 355369, 295018 e-mail: gems_hpt@yahoo.com Website: www.globalmining.in

> ANNEXURE-03 GEMS-LD/TF/11/01

ANALYSIS REPORT OF AMBIENT AIR QUALITY DATA

Name of the Industry

: BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

Customer Reference

: WO/ADMIN/FY23/R073

Sample collected by

: Global Environment & Mining Services

Discipline

: Chemical

Group

Atmospheric Pollution

Sample Type

Ambient Air Quality Monitoring

Particulars of Sample Collected

CO Analyser

Month

SEPTEMBER-2022

Location
Duration of Monitoring

A3-Hanumanahalli Village

Report Issued Date

: 1 Hour : 04.10.2022

RESULTS

SI. No.	Date of Sampling	Sample Code	CO (1 Hour) [mg/m³]	Standard
1	05.09.2022	2417	0.18	
2	06.09.2022	2443	0.23	1
3	12.09.2022	2533	0.21	
4	13.09.2022	2557	0.14	1 40
5	19.09.2022	2717	0.11	4.0
6	20.09.2022	2745	0.15	
7	26.09.2022	2858	0.12	
8	27.09.2022	2877	0.10	

Note: CO - GEMS/SOP/86/as per CO Analyzer Manual (1 Hour)

ND - Not Detected

SL NO	INSTRUMENT DETAILS				
1	Instrument Name	CO Gas Detector			
2	Make & Model	Vasthi Instruments Pvt Ltd & VS-70-70-CC			
3	Serial No	180883821			
4	Calibration Date	09.07.2022			
5	Calibration Due Date	08.07.2023			

INFERENCE As per NAAQMS Standards (2009),
Report Status: - Measured Values for the above parameters are within the limit

Ruy b. Analysed By Rukmini G Chemist



- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory
- Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

Ph : +918394 355369, 295018 e-mail : gems_hpt@yahoo.com Website : www.globalmining.in



TC-5323

ANNEXURE-04 GEMS-LD/TF/11/01

ANALYSIS REPORT OF AMBIENT AIR QUALITY DATA

Name of the Industry BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

Customer Reference WO/ADMIN/FY23/R073

Sample collected by **Global Environment & Mining Services**

Discipline Chemical

Group Atmospheric Pollution

Sample Type **Ambient Air Quality Monitoring**

Particulars of Sample Collected Respirable Dust Sampler, FPS Sampler

SEPTEMBER-2022 Location

A4-Galemmanagudi Village

Duration of Monitoring 24 Hour Report Issue Date 04.10.2022

Report Number ULR-TC532322000000708F

RESULTS

Parameters		PM [μg/		PM _{2.5} [μg/m³]		SO ₂ [μg/m³]		NO ₂ [μg/m³]		
	Reference Method		IS:5182 (Part (RF-2	-23)	Active Control of the Party of	USEPA 2001		IS:5182: (Part-6) 2006 (RF-2017)		
Date of Sampling	Date of Sample Received	Sample Code	Result	STD	Result	STD	Result	STD	Result	STD
07.09.2022	08.09.2022	2464	61.07		17.62		10.41		12.00	
08.09.2022	09.09.2022	2483	48.44		13.73		6.64		9.63	
14.09.2022	15.09.2022	2569	58.69		16.52		7.86		10.81	
15.09.2022	16.09.2022	2600	65.05		18.17		5.65		8.44	
21.09.2022	22.09.2022	2777	45.93	100	12.49	60	6.86	80	9.76	80
22.09.2022	23.09.2022	2807	37.45	ACCRECATE TO	10.50		6.20	00	9.36	00
28.09.2022	29.09.2022	2898	54.10		15.14		5.65		8.84	
29.09.2022	30.09.2022	2911	48.05		13.60	ľ	10.96		11.80	
	Average		52.35		14.72		7.53		10.08	

SLNO	INSTRUMENT DETAILS					
1	Instrument Name	Respirable Dust Sampler (RDS)	Fine Particulate Sampler (FPS)			
2	Make & Model	Enviro instruments / AAS-217 BL	Enviro instruments / EI-133			
3	Serial No	R.D.S. / 14-A-142	PM2.5 /PM10 Sampler / 158-K-20			
4	Calibration Date	01.04.2022	07.03.2022			
5	Calibration Due Date	31.03.2023	06.03.2023			

As per NAAQMS Standards (2009), INFERENCE Report Status: - Measured Values for the above parameters are within the limit.

> Rul G Analysed By Rukmini G Chemist



- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

 Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

 This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

 Recognised by Ministry of Environment, Forest and Climate Change for Laboratory

 Recognised by Government of Karnataka, Maharashira, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

Ph

: +918394 355369, 295018

e-mail

: gems_hpt@yahoo.com Website : www.globalmining.in

ANNEXURE-04 GEMS-LD/TF/11/01

ANALYSIS REPORT OF AMBIENT AIR QUALITY DATA

Name of the Industry

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

Customer Reference

WO/ADMIN/FY23/R073

Sample collected by

Global Environment & Mining Services

Discipline Group

Chemical

Sample Type

Atmospheric Pollution

Particulars of Sample Collected

Ambient Air Quality Monitoring

Month

CO Analyser

Location

SEPTEMBER-2022

Duration of Monitoring

A4-Galemmanagudi Village 1 Hour

Report Issued Date

04.10.2022

RESULTS

SI. No.	Date of Sampling	Sample Code	CO (1 Hour) [mg/m³]	Standard
1	07.09.2022	2464	0.16	
2	08.09.2022	2483	0.12	1
3	14.09.2022	2569	0.24	
4	15.09.2022	2600	0.22	4.0
5	21.09.2022	2777	0.18	4.0
6	22.09.2022	2807	0.12	1
7	28.09.2022	2898	0.08	
8	29.09.2022	2911	0.11	

Note: CO - GEMS/SOP/86/as per CO Analyzer Manual (1 Hour) ND - Not Detected

SL NO	TRUMENT DETAILS	
1	Instrument Name	CO Gas Detector
2	Make & Model	Vasthi Instruments Pvt Ltd & VS-70-70-CC
3	Serial No	180883821
4	Calibration Date	09.07.2022
5	Calibration Due Date	08.07.2023

As per NAAQMS Standards (2009), INFERENCE Report Status: • Measured Values for the above parameters are within the limit

Analysed By Rukmini G Chemist





- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory
- Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

Ph : +918394 355369, 295018 e-mail : gems_hpt@yahoo.com

Website : www.globalmining.in



TC-5323

ANNEXURE-05 GEMS-LD/TF/11/01

ANALYSIS REPORT OF AMBIENT AIR QUALITY DATA

Name of the Industry

Customer Reference

Sample collected by

Discipline

Group

Sample Type

Particulars of Sample Collected

Month

Location

Duration of Monitoring

Report Issue Date Report Number

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

WO/ADMIN/FY23/R073

Global Environment & Mining Services

Chemical

Atmospheric Pollution

Ambient Air Quality Monitoring

Respirable Dust Sampler, FPS Sampler

SEPTEMBER-2022

A5-Gunda Village

24 Hour

04.10.2022

ULR-TC532322000000709F

RESULTS

Parameters		PM1 [µg/n		PM: [μg/		SO2 [μg/m3]		NO2 [μg/m3]		
	Reference Method		IS:5182: (Part- (RF-20	23)	USEPA Gravimetri		IS:5182: 2001 (Part-2) (RF-2017)		IS:5182: (Part-6) 2006 (RF-2017)	
Date of Sampling	Date of Received Sample	Sample Code	Result	STD	Result	STD	Result	STD	Result	STD
07.09.2022	08.09.2022	2465	58.85	8.85	16.54		8.52		11.47	
08.09.2022	09.09.2022	2484	48.08		13.29		7.64 9.19		9.89	
14.09.2022	15.09.2022	2570	37.84	1	10.84				12.27	
15.09.2022	16.09.2022	2601	54.12		15.15		5.20	1	8.97	
21.09.2022	22.09.2022	2778	45.38	100	12.81	60	8.64	80	10.68	80
22.09.2022	23.09.2022	2808	58.21	1	16.43		5.54	1	9.76	
28.09.2022	29.09.2022	2899	39.38	1	11.41		7.64	1	8.70	
29.09.2022	30.09.2022	2912	59.61		16.71		9.08		11.34	
	Average		50.18		14.15		7.68		10.39	

SL NO	INSTRUMENT DETAILS						
1 Instrument Name		Respirable Dust Sampler (RDS)	Fine Particulate Sampler (FPS)				
2	Make & Model	Enviro instruments / APM -460 BL	Enviro instruments / El-133				
3	Serial No	R.D.S./330-DTF-2005	PM2.5 /PM10 Sampler / 159-K-20				
4	Calibration Date	01.04.2022	07.03.2022				
5	Calibration Due Date	31.03.2023	06.03.2023				

INFERENCE

As per NAAQMS Standards (2009),

Report Status: - Measured Values for the above parameters are within the limit.

Rukmini G Chemist

B P Lingara Chemist

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

 Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

 This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of Law & should not use any advertising media without special permission in writing. Total Hability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

 Recognised by Ministry of Environment, Forest and Climate Change for Laboratory

 Recognised by Government of Karnataka, Maharushtra, Goa for DGPS survey
- 3. 4. 5.





(Consulting Engineers, Mine designers, Geologist & Surveyors)
3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

Ph : +918394 355369, 295018

e-mail : gems_hpt@yahoo.com Website : www.globalmining.in

> ANNEXURE-05 GEMS-LD/TF/11/01

ANALYSIS REPORT OF AMBIENT AIR QUALITY DATA

Name of the Industry

Customer Reference

Sample collected by

Discipline

Group

Sample Type

Particulars of Sample Collected

Month

Location

Duration of Monitoring Report Issued Date : BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

WO/ADMIN/FY23/R073

Global Environment & Mining Services

Chemical

Cnemicai

Atmospheric Pollution

Ambient Air Quality Monitoring

CO Analyser

SEPTEMBER-2022

A5-Gunda Village 1 Hour

1 Hour

: 04.10.2022

RESULTS

SI. No.	Date of Sampling	Sample Code	CO (1 Hour) [mg/m³]	Standard
1	07.09.2022	2465	< 0.01	
2	08.09.2022	2484	< 0.01	1
3	14.09.2022	2570	0.12	1
4	15.09.2022	2601	< 0.01	1
5	21.09.2022	2778	< 0.01	4.0
6	22.09.2022	2808	0.11	1
7	28.09.2022	2899	< 0.01	1
8	29.09.2022	2912	< 0.01	1

Note: CO - GEMS/SOP/86/as per CO Analyzer Manual (1 Hour)

ND - Not Detected

SL NO INSTRUMENT DETAILS				
1	Instrument Name	CO Gas Detector		
2	Make & Model	Vasthi Instruments Pvt Ltd & VS-70-70-C0		
3	Serial No	180883821		
4	Calibration Date	09.07.2022		
5	Calibration Due Date	08.07.2023		

INFERENCE As per NAAQMS Standards (2009),
Report Status: • Measured Values for the above parameters are within the limit

Ruy by Analysed By Rukmini G Chemist



- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory
- Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

Ph

: +918394 355369, 295018

e-mail Website

: gems_hpt@yahoo.com : www.globalmining.in

TC-5323

ANNEXURE-06 GEMS-LD/TF/11/01

ANALYSIS REPORT OF AMBIENT AIR QUALITY DATA

Name of the Industry

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

Customer Reference

WO/ADMIN/FY23/R073

Sample collected by

Global Environment & Mining Services

Discipline

Chemical

Group

Atmospheric Pollution :

Sample Type

Ambient Air Quality Monitoring

Particulars of Sample Collected

Respirable Dust Sampler, FPS Sampler

Month

SEPTEMBER-2022

Location

A6-Gunda Tanda Village

Duration of Monitoring

24 Hour

Report Issue Date

04.10.2022

Report Number

ULR-TC532322000000710F

RESULTS

Parameters			PM [μg/1		PM [μg/ι		SO [µg/i		NC [μg/	(E)
	Reference Method		IS:5182: 2006 (Part-23) (RF-2017)		USEPA 2001 Gravimetric Method		IS:5182: 2001 (Part-2) (RF-2017)		IS:5182: (Part-6) 2006 (RF-2017)	
Date of Sampling	Date of Received Sample	Sample Code	Result	STD	Result	STD	Result	STD	Result	STD
07.09.2022	08.09.2022	2466	58.45		16.43		9.15		11.34	-
08.09.2022	09.09.2022	2485	47.37		13.47		8.20	1	10.29	
14.09.2022	15.09.2022	2571	67.66		18.98		9.86		12.79	
15.09.2022	16.09.2022	2602	56.84		15.87		5.58		8.57	
21.09.2022	22.09.2022	2779	39.48	100	11.35	60	9.26	80	12.00	80
22.09.2022	23.09.2022	2809	62.47		17.08		5.94		8.84	
28.09.2022	29.09.2022	2900	53.82		15.26		8.20		10.81	
29.09.2022	30.09.2022	2913	49.63		13.64		9.74		12.58	
	Average		54.47		15.26		8.24		10.90	

SLNO	INSTRUMENT DETAILS						
1	Instrument Name	Respirable Dust Sampler (RDS)	Fine Particulate Sampler (FPS)				
2	Make & Model	Greentech instruments / GTI -151	Enviro instruments / EJ-133				
3	Serial No	R.D.S./242-DTC-2020	PM2.5 /PM10 Sampler / 160-K-20				
4	Calibration Date	01.04.2022	07.03.2022				
5	Calibration Due Date	31.03.2023	06.03.2023				

INFERENCE

As per NAAQMS Standards (2009),

Report Status: - Measured Values for the above parameters are within the limit







- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

 Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

 This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing.
- Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only. Recognised by Ministry of Environment, Forest and Climate Change for Laboratory
- Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors)

3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

Ph

: +918394 355369, 295018 : gems_hpt@yahoo.com

e-mail

Website : www.globalmining.in

ANNEXURE-06 GEMS-LD/TF/11/01

ANALYSIS REPORT OF AMBIENT AIR QUALITY DATA

Name of the Industry

: BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

Customer Reference

: WO/ADMIN/FY23/R073

Sample collected by

Global Environment & Mining Services

Discipline

Chemical

Group

Atmospheric Pollution

Sample Type

Ambient Air Quality Monitoring

Particulars of Sample Collected

: CO Analyser

Month

: SEPTEMBER-2022

Location

: A6-Gunda Tanda Village

Duration of Monitoring Report Issued Date : 1 Hour : **04.10.2022**

RESULTS

SI. No.	Date of Sampling	Sample Code	CO (1 Hour) [mg/m³]	Standard
1	07.09.2022	2466	0.13	
2	08.09.2022	2485	< 0.01	7
3	14.09.2022	2571	< 0.01	
4	15.09.2022	2602	0.08	1
5	21.09.2022	2779	< 0.01	4.0
6	22.09.2022	2809	0.09	
7	28.09.2022	2900	< 0.01	
8	29.09.2022	2913	< 0.01	7

Note: CO - GEMS/SOP/86/as per CO Analyzer Manual (1 Hour)

ND - Not Detected

SL NO	INS	TRUMENT DETAILS
1	Instrument Name	CO Gas Detector
2	Make & Model	Vasthi Instruments Pvt Ltd & VS-70-70-C0
3	Serial No	180883821
4	Calibration Date	09.07.2022
5	Calibration Due Date	08.07.2023

INFERENCE As per NAAQMS Standards (2009),
Report Status: • Measured Values for the above parameters are within the limit

Ruy 6. Analysed By Rukmini G Chemist



- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory
- Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

: +918394 229433, 295018

e-mail : gems_hpt@yahoo.com Website : www.globalmining.in



TC-5323

ANNEXURE-07 GEMS-LD/TF/11/01

FORTNIGHTLY FUGITIVE AIR QUALITY DATA MONITORING

Name of the Industry 1

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference** WO/ADMIN/FY22/R038

3 Sample collected by **GLOBAL Environment & Mining Services**

Particulars of sample collected 4

RDS Sampler (GEMS-01, GEMS-02, GEMS-03, GEMS-04, GEMS-05)

Month 5

SEPTEMBER-2022(1st Fort Night)

Discipline 6

Chemical

7 Group Atmospheric Pollution

8 Method adopted IS 5182 (Part 4): 1999 RA 2014

9 Report Issued Date 04.10.2022

Report Number 10

ULR-TC532322000000673F

RESULTS

		Sample	Date Of	Date Of	SPM	
Sl. No.	Location / Plant	Code	Monitoring	Sample Receipt	$(\mu g/m^3)$	Standard
I. Benefi	ciation Plant-II					
1.	Ball Mill Area (Zero Meter)	2375	01.09.2022	02.09.2022	389.58	2000
2.	Iron Ore Hopper (Near Monsoon Shed)	2376	01.09.2022	02.09.2022	438.85	2000
3.	Concentrate Thickner	2377	01.09.2022	02.09.2022	469.55	2000
II. Pellet	Plant-I					
4.	PR-6	2378	01.09.2022	02.09.2022	895.62	2000
5.	Annual Cooler	2379	01.09.2022	02.09.2022	780.22	2000
6.	Additive Grinding Building	2387	02.09.2022	03.09.2022	888.99	2000
III. Spon	ge Iron Division -2 (Kiln 1 & 2)					
7.	Control room	2388	02.09.2022	03.09.2022	414.22	2000
8,	Near Weigh bridge (dispatch)	2389	02.09.2022	03.09.2022	264.44	2000
9.	Pellet Storage bin	2391	02.09.2022	03.09.2022	1416.93	2000
10.	Transfer House area	2401	03.09.2022	04.09.2022	1101.86	2000
11.	Production Separation Bin-PSB	2390	02.09.2022	03.09.2022	1200.42	2000
IV. Spon	ge Iron Division -2 (Kiln 3 & 4)			7/1		
12.	Near Control room	2402	03.09.2022	04.09.2022	695.14	2000
13.	Near Coal Crusher	2404	03.09.2022	04.09.2022	1579.96	2000
14.	Near Product bin	2403	03.09.2022	04.09.2022	1231.82	2000
15.	Coal Drier	2405	03.09.2022	04.09.2022	636.89	2000
V. Wago	n Tipper/RMHS	· · · · · · · · · · · · · · · · · · ·				pressure and a
16.	Near Tipping point	2421	05.09.2022	06.09.2022	455.99	2000
17.	Monsoon Shed (CPU)	2422	05.09.2022	06.09.2022	483.95	2000
18.	MCC Room (2nd Gate)	2423	05.09.2022	06.09.2022	509.91	2000
VI. Powe	er Plant-70 MW					
19.	70MW-DM Plant (Near R.O. Plant)	2447	06.09.2022	07.09.2022	536.19	2000
20.	Coal Screen (near gate weigh bridge)	2424	05.09.2022	06.09.2022	701.07	2000
21.	CFBC boiler	2425	05.09.2022	06.09.2022	717.48	2000
VII. 2X70	OMW Power Plant					
22.	Near Boiler	2448	06.09.2022	07.09.2022	687.01	2000
23.	Near Coal storage Shed	2449	06.09.2022	07.09.2022	441.63	2000
24.	Bricks Plant	2450	06.09.2022	07.09.2022	305.82	2000

SL NO	INSTRUMENT DETAILS	GEMS-01	GEMS-02	GEMS-03	GEMS-04	GEMS-05
1	Instrument Name	Respirable Dust Sampler				
2	Make & Model	Greentech Instruments/GTI-151	Greentech Instruments/GTI-151	Greentech Instruments/GTI-151	Greentech Instruments/GTI-151	Greentech Instruments/GTI-151
3	Serial No	RDS / 241-DTC-2020	RDS / 243-DTL-2020	RDS / 244-DTL-2020	RDS / 193-DTH-2019	RDS / 197-DTH-2019
4	Calibration Date	01.04.2022	01.04.2022	01.04.2022	01.04.2022	01.04.2022
5	Calibration Due Date	31.03.2023	31.03.2023	31.03.2023	31.03.2023	31.03.2023



Lingaraja B egolo

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

 Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

 This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Bosapete jurisdiction only.
- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

: +918394 229433, 295018 e-mail : gems_hpt@yahoo.com Website : www.globalmining.in



TC-5323

ANNEXURE-08 GEMS-LD/TF/11/01

FORTNIGHTLY FUGITIVE AIR QUALITY DATA MONITORING

1 Name of the Industry BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference** WO/ADMIN/FY22/R038

3 Sample collected by **GLOBAL Environment & Mining Services**

4 Particulars of sample collected RDS Sampler (GEMS-01, GEMS-02, GEMS-03, GEMS-04, GEMS-05)

5 Month SEPTEMBER-2022(2nd Fort Night)

Discipline Chemical 6

7 Group Atmospheric Pollution

8 Method adopted IS 5182 (Part 4): 1999 RA 2014

9 Report Issued Date 04.10.2022

10 ULR-TC532322000000778F Report Number

RESULTS

		RESULIS				
Sl. No.	Location / Plant	Sample Code	Date Of Monitoring	Date Of Sample Receipt	SPM (μg/m³)	Standard
I. Benefi	ciation Plant-II					
1.	Ball Mill Area (Zero Meter)	2636	16.09.2022	17.09.2022	449.79	2000
2.	Iron Ore Hopper (Near Monsoon Shed)	2638	16.09.2022	17.09.2022	1218.18	2000
3.	Concentrate Thickner	2637	16.09.2022	17.09.2022	620.31	2000
II. Pellet	Plant-I					-
4.	PR-6	2639	16.09.2022	17.09.2022	874.49	2000
5.	Annual Cooler	2670	17.09.2022	18.09.2022	835.40	2000
6.	Additive Grinding Building	2671	17.09.2022	18.09.2022	1329.40	2000
III. Spon	ge Iron Division -2 (Kiln 1 & 2)			*		
7.	Control room	2672	17.09.2022	18.09.2022	556.78	2000
8.	Near Weigh bridge (dispatch)	2673	17.09.2022	18.09.2022	481.92	2000
9.	Pellet Storage bin	2723	19.09.2022	20.09.2022	1317.25	2000
10.	Transfer House area	2721	19.09.2022	20.09.2022	1050.12	2000
11.	Production Separation Bin-PSB	2722	19.09.2022	20.09.2022	1307.40	2000
IV. Spon	ge Iron Division -2 (Kiln 3 & 4)					
12.	Near Control room	2724	19.09.2022	20.09.2022	1720.71	2000
13.	Near Coal Crusher	2750	20.09.2022	21.09.2022	657.31	2000
14.	Near Product bin	2749	20.09.2022	21.09.2022	1400.55	2000
15.	Coal Dryer	2783	21.09.2022	22.09.2022	1308.14	2000
V. Wagoi	Tipper/RMHS	701				72,1-53-2
16.	Near Tipping point	2825	23.09.2022	24.09.2022	1542.45	2000
17.	Monsoon Shed (CPU)	2784	21.09.2022	22.09.2022	1260.05	2000
18.	MCC Room (2nd Gate)	2785	21.09.2022	22.09.2022	847.54	2000
VI. Powe	r Plant-70 MW					
19.	70MW-DM Plant (Near R.O. Plant)	2751	20.09.2022	21.09.2022	278.35	2000
20.	Coal Screen (near gate weigh bridge)	2786	21.09.2022	22.09.2022	958.65	2000
21.	CFBC boiler	2752	20.09.2022	21.09.2022	1567.15	2000
VII. 2X70	DMW Power Plant					
22.	Near Boiler	2813	22.09.2022	23.09.2022	1159.45	2000
23.	Near Coal storage Shed	2814	22.09.2022	23.09.2022	411.62	2000
24.	Bricks Plant	2815	22.09.2022	23.09.2022	848.56	2000

Note: SPM -Suspended Particulate matter (ug/m3) INSEPENCE: The Measured Values are within the limits

SL NO	INSTRUMENT DETAILS	GEMS-01	GEMS-02	GEMS-03	GEMS-04	GEMS-05
1	Instrument Name	Respirable Dust Sampler				
2	Make & Model	Greentech Instruments/GTI-151	Greentech Instruments/GTI-151	Greentech Instruments/GTI-151	Greentech Instruments/GTI-151	Greentech Instruments/ GTI-151
3	Serial No	RDS / 241-DTC-2020	RDS / 243-DTL-2020	RDS / 244-DTL-2020	RDS / 193-DTH-2019	RDS / 197-DTH-2019
4	Calibration Date	01.04.2022	01.04.2022	01.04.2022	01.04.2022	01.04.2022
5	Calibration Due Date	31.03.2023	31.03.2023	31.03.2023	31.03.2023	31.03.2023

Analysed By Rukmini G Chemist

Verified By Lingaraja B Chemist

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied. Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.
- This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing Total liability of our laboratory is limited to the Invoice amount. Any dispate arising out of this report is subject to Hosapete jurisdiction only. 3.
- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory Recognised by Government of Karnataka, Mahanashira, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

: +918394 229433, 295018

e-mail

: gems_hpt@yahoo.com

Website : www.globalmining.in



TC-5323

ANNEXURE-09 GEMS-LD/TF/10/01

Analysis Report of Stack Emission

Name of the Industry 1

2 **Customer Reference**

3 Sample collected by

4 Particulars of sample collected

5 **Instrument Details**

6 Discipline

7 Group

8 Sample Type

Sampling Location 9

10 Month of Sampling

Date of Sample Received 11

Date of Sample Analysis 12

13 **Date Sample Analysis Completion**

Report Issued Date 14 15 Report Number

Fuel Used 2

3 Stack Diameter (mtr) : BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

: WO/ADMIN/FY22/R038

: GLOBAL Environment & Mining Services

: Vayubodhan Stack sampler / VSS-1

Sl. No: Stack Monitoring Kit/304-DTB-2007

: Calibration Date: 07.02.2022

Calibration Due Date: 06.02.2023

Chemical

Atmospheric Pollution 2

Stack Monitoring :

: Pellet Plant-2 ESP

: SEPTEMBER-2022

: 01.09.2022 & 16.09.2022

: 02.09.2022 & 17.09.2022

: 03.09.2022 & 19.09.2022

: 04.10.2022

: ULR-TC532322000000671F

Stack Details

1

Stack Height (mtr)

Coal 100 4.4

Emission Details

				Res	sult		
SI.	Parameters Method		Unit	1 st Fort Night	2 nd Fort Night	Permissible	
No.	Date of Monitoring			01.09.2022	16.09.2022	Limit	
	Sample Code			2372	2633		
1	Ambient Temperature	IS: 11255 (Part 1) - 1985 (RA 2014)	oC.	28	28	(#)	
2	Stack Temperature	IS: 11255 (Part 1) - 1985 (RA 2014)	oC.	121	119	1.50	
3	Velocity of Fuel Gas	IS: 11255 (Part 1) - 1985 (RA 2014)	m/sec	7.04	6.80	-	
4	Gas flow rate at Stack Condition	IS-11255(Part 03)1985(RA 2014)	m³/hr	385413	372274		
5	Gas flow rate at NTP	IS-11255(Part 03)1985(RA 2014)	Nm³/hr	290278	282222	-	
6	Particulate Matter	IS: 11255 (Part 1) - 1985 (RA 2014)	mg/Nm³	37.20	34.60	100	
7	Sulphur Dioxide	IS: 11255 (Part 2): 1985 (RA 2014)	mg/Nm³	120.12	114.40	NS	
8	Nitrogen Dioxide	IS:11255 (Part7): 2005(RA 2017)	mg/Nm³	30.75	26.65	NS	
9	Carbon Monoxide	GEMS/SOP/69	%	0.021	0.017	•	

Note: NS- Not Specified. RA: Reaffirmed. INFERENCE: The Measured Values are within the limits.

Ruy G **Analysed By** Rukmini G Chemist

Lingaraja B P Chemist



The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied. Water Samples will be destroyed after 15Days, Minerals 3 Months, Fifter papers & Thimbles After analysis Discard.

This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing.

Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only. Recognised by Ministry of Environment, Forest and Climate Change for Laboratory

Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey







(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

: +918394 229433, 295018 : gems_hpt@yahoo.com e-mail Website : www.globalmining.in



TC-5323

ANNEXURE-10 GEMS-LD/TF/10/01

Analysis Report of Stack Emission

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District. 1 Name of the Industry

WO/ADMIN/FY22/R038 **Customer Reference** 2

3 Sample collected by **GLOBAL Environment & Mining Services**

4 Particulars of sample collected Vayubodhan Stack sampler/ VSS-1

Sl. No: Stack Monitoring Kit/ 304-DTB-2007

5 Instrument Details Calibration Date: 07.02.2022

Calibration Due Date: 06.02.2023

6 Discipline Chemical

7 Group Atmospheric Pollution 8 Sample Type Stack Monitoring 9 Sampling Location SID Axis 1 &2 10 Month of Sampling SEPTEMBER-2022

11 Date of Sample Received 03.09.2022 & 27.09.2022 Date of Sample Analysis 12 05.09.2022 & 28.09.2022 **Date Sample Analysis Completion** 13 06.09.2022 & 29.09.2022

Report Issued Date 04.10.2022 14

15 Report Number ULR-TC532322000000682F

Stack Details

1 Fuel Used Coal 2 Stack Height (mtr) 70.0 3 Stack Diameter (mtr) 3.00

Emission Details

				Re	sult	
Sl. No.	Parameters	Method	Unit	1st Fort Night	2 nd Fort Night	Permissible Limit
140.	Date of Monitoring			03.09.2022	27.09.2022	Limit
	Sample Code			2398	2878	
1	Ambient Temperature	IS: 11255 (Part 1) - 1985 (RA 2014)	oC	29	28	-
2	Stack Temperature	IS: 11255 (Part 1) - 1985 (RA 2014)	°C	129	124	•
3	Velocity of Fuel Gas	IS: 11255 (Part 1) - 1985 (RA 2014)	m/sec	6.89	6.58	-
4	Gas flow rate at Stack Condition	IS-11255(Part 03)1985(RA 2014)	m³/hr	175352	167462	¥
5	Gas flow rate at NTP	IS-11255(Part 03)1985(RA 2014)	Nm³/hr	129560	125305	•
6	Particulate Matter	IS: 11255 (Part 1) - 1985 (RA 2014)	mg/Nm ³	44.70	35.30	100
7	Sulphur Dioxide	IS: 11255 (Part 2): 1985 (RA 2014)	mg/Nm³	111.54	120.12	NS
8	Nitrogen Dioxide	IS:11255 (Part7): 2005(RA 2017)	mg/Nm³	28.70	32.80	NS
9	Carbon Monoxide	GEMS/SOP/69	%	0.018	0.023	1%

Note: NS- Not Specified. RA: Reaffirmed. INFERENCE: The Measured Values are within the limits.

Rukmini G Chemist

Chemist



The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of Law & should not use any advertising media without special permission in writing.

Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only. Recognised by Ministry of Environment, Forest and Climate Change for Laboratory

Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

: +918394 229433, 295018

e-mail : gems_hpt@yahoo.com Website : www.globalmining.in



ANNEXURE-11 GEMS-LD/TF/10/01

Analysis Report of Stack Emission

1 Name of the Industry BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference** WO/ADMIN/FY22/RO38

3 Sample collected by **GLOBAL Environment & Mining Services** Vayubodhan Stack sampler / VSS-1

4 Particulars of sample collected

Sl. No: Stack Monitoring Kit/304-DTB-2007

5 Instrument Details Calibration Date: 07.02.2022

Calibration Due Date: 06.02.2023

Chemical

6 Discipline 7 Group

8 Sample Type

Atmospheric Pollution Stack Monitoring

9 Sampling Location

SID Axis 3&4

10 Month of Sampling SEPTEMBER-2022

11 Date of Sample Received : 05.09.2022 & 22.09.2022

12 **Date of Sample Analysis** : 06.09.2022 & 23.09.2022

13 **Date Sample Analysis Completion** : 07.09.2022 & 24.09.2022

14 Report Issued Date 04.10.2022

15 Report Number ULR-TC532322000000691F

Stack Details

1 Fuel Used Coal

2 Stack Height (mtr) 70.0

3 Stack Diameter (mtr) 3.00

Emission Details

				Re	sult		
SI. No.	Parameters	Method	Unit	1 st Fort Night	2 nd Fort Night	Permissible Limit	
140.	Date of Monitoring			05.09.2022	22.09.2022	Limit	
	Sample Code			2418	2810		
1	Ambient Temperature	IS: 11255 (Part 1) - 1985 (RA 2014)	oC.	29	29	-	
2	Stack Temperature	IS: 11255 (Part 1) - 1985 (RA 2014)	oC.	134	135	•	
3	Velocity of Fuel Gas	IS: 11255 (Part 1) - 1985 (RA 2014)	m/sec	8.07	7.99		
4	Gas flow rate at Stack Condition	IS-11255(Part 03)1985(RA 2014)	m³/hr	205383	203347		
5	Gas flow rate at NTP	IS-11255(Part 03)1985(RA 2014)	Nm³/hr	149825	148347		
6	Particulate Matter	IS: 11255 (Part 1) - 1985 (RA 2014)	mg/Nm³	47.80	55.80	100	
7	Sulphur Dioxide	IS: 11255 (Part 2): 1985 (RA 2014)	mg/Nm³	98.20	87.36	NS	
8	Nitrogen Dioxide	IS:11255 (Part7): 2005 (RA 2017)	mg/Nm³	73.80	63.55	NS	
9	Carbon Monoxide	GEMS/SOP/69	%	0.697	0.574	1%	

Note: NS- Not Specified. RA: Reaffirmed. INFERENCE: The Measured Values are within the limits.

Analysed By Rukmini G Chemist

Lingaraja B Chemist

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.
- Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

 This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing.
- Total liability of our laboratory is limited to the invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only. Recognised by Ministry of Environment, Forest and Climate Change for Laboratory
- Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

Ph : +918394 229433, 295018 e-mail : gems_hpt@yahoo.com

Website : www.globalmining.in TC-5323



ANNEXURE-12 GEMS-LD/TF/10/01

Analysis Report of Stack Emission

1 Name of the Industry : BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 Customer Reference : WO/ADMIN/FY22/RO38

3 Sample collected by : GLOBAL Environment & Mining Services
4 Particulars of sample collected : Vayubodhan Stack sampler / VSS-1

Particulars of sample collected : Vayubodhan Stack sampler / VSS-1 Sl. No: Stack Monitoring Kit / 304-DTB-2007

5 Instrument Details : Calibration Date: 07.02.2022

Calibration Due Date: 06.02.2023

6 Discipline : Chemical

7 Group : Atmospheric Pollution 8 Sample Type : Stack Monitoring

9 Sampling Location : 1X70 MW-CFBC Boiler ESP

10 Month of Sampling : SEPTEMBER-2022

 11
 Date of Sample Received
 : 07.09.2022 & 23.09.2022

 12
 Date of Sample Analysis
 : 08.09.2022 & 24.09.2022

 13
 Date Sample Analysis Completion
 : 09.09.2022 & 26.09.2022

14 Report Issued Date : 04.10.2022

15 Report Number : **ULR-TC532322000000711F**

Stack Details

 1
 Fuel Used
 Coal

 2
 Stack Height (mtr)
 70.0

 3
 Stack Diameter (mtr)
 3.00

Emission Details

				Re	sult	
Sl. No.	Parameters	Method	Unit	1 st Fort Night	2 nd Fort Night	Permissible Limit
110.	Date of Monitoring			07.09.2022	23.09.2022	Limit
	Sample Code			2467	2822	
1	Ambient Temperature	IS: 11255 (Part 1) - 1985 (RA 2014)	oC.	28	28	-
2	Stack Temperature	IS: 11255 (Part 1) - 1985 (RA 2014)	oC.	121	112	
3	Velocity of Fuel Gas	IS: 11255 (Part 1) - 1985 (RA 2014)	m/sec	6.66	6.26	7
4	Gas flow rate at Stack Condition	IS-11255(Part 03)1985(RA 2014)	m³/hr	169498	159318	-
5	Gas flow rate at NTP	IS-11255(Part 03)1985(RA 2014)	Nm³/hr	127626	123268	-
6	Particulate Matter	IS: 11255 (Part 1) - 1985 (RA 2014)	mg/Nm³	32.80	33.80	50
7	Sulphur Dioxide	IS: 11255 (Part 2): 1985 (RA 2014)	mg/Nm³	51.48	22.88	600
8	Nitrogen Dioxide	IS:11255 (Part7): 2005 (RA 2017)	mg/Nm ³	147.6	139.40	300
9	Carbon Monoxide	GEMS/SOP/69	%	0.022	0.018	-

Note: NS- Not Specified. RA: Reaffirmed. INFERENCE: The Measured Values are within the limits.

Rug In. Analysed By Rukmini G Chemist Verified By Lingaraja B P Chemist



Note:

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.
- Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.
 This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permissis.

This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing.
 Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

Recognised by Ministry of Environment, Forest and Climate Change for Laboratory
 Recognised by Government of Karnataka, Maharashira, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE – 583201, Dist., Vijayanagara (Karnataka)

: +918394 229433, 295018

e-mail

: gems_hpt@yahoo.com

Website : www.globalmining.in



TC-5323

ANNEXURE-13 GEMS-LD/TF/10/01

Analysis Report of Stack Emission

1 Name of the Industry BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference** WO/ADMIN/FY22/R038

3 Sample collected by

Instrument Details

: GLOBAL Environment & Mining Services : Vayubodhan Stack sampler/ VSS-1

4 Particulars of sample collected

Sl. No: Stack Monitoring Kit/304-DTB-2007

: Calibration Date: 07.02.2022

Calibration Due Date: 06.02.2023

6 Discipline

: Chemical

7 Group

5

8 Sample Type Atmospheric Pollution

9 Sampling Location Stack Monitoring

2X70 MW CFBC Boiler ESP SEPTEMBER-2022

10 Month of Sampling

11 Date of Sample Received

Date of Sample Analysis 12

13 Date Sample Analysis Completion

04.10.2022

14 Report Issued Date 15 Report Number

:

Stack Details

Fuel Used 1

Coal

2 Stack Height (mtr) 110.0

3 Stack Diameter (mtr) 8.00

Emission Datails

				Re	sult	
SI. No.	Parameters	Method	Unit	1 st Fort Night	2 nd Fort Night	Permissible Limit
140.	Date of Monitoring			-	Limit	
	Sample Code			-		
1	Ambient Temperature	IS: 11255 (Part 1) - 1985 (RA 2014)	°C			% = %
2	Stack Temperature	IS: 11255 (Part 1) - 1985 (RA 2014)	°C			
3	Velocity of Fuel Gas	IS: 11255 (Part 1) - 1985 (RA 2014)	m/sec			•
4	Gas flow rate at Stack Condition	IS-11255(Part 03)1985(RA 2014)	m³/hr			
5	Gas flow rate at NTP	IS-11255(Part 03)1985(RA 2014)	Nm³/hr	Shutdown	Shutdown	180
6	Particulate Matter	IS: 11255 (Part 1) - 1985 (RA 2014)	mg/Nm ³			100
7	Sulphur Dioxide	IS: 11255 (Part 2): 1985 (RA 2014)	mg/Nm³			600
8	Nitrogen Dioxide	IS:11255 (Part7): 2005 (RA 2017)	mg/Nm³			300
9	Carbon Monoxide	GEMS/SOP/69	%			-
		ADDRESS PROPERTY AND ADDRESS OF THE PARTY AND	1735			

Note: NS- Not Specified. RA: Reaffirmed

Lingaraja B P Chemist

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied. Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.
- This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of kiw & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

 Recognised by Ministry of Environment, Forest and Climate Change for Laboratory

 Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

: +918394 229433, 295018

e-mail Website

: gems_hpt@yahoo.com : www.globalmining.in

TC-5323

ANNEXURE-14 GEMS-LD/TF/10/01

Analysis Report of Stack Emission

Name of the Industry 1

: BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference** : WO/ADMIN/FY22/RO38

3 Sample collected by

: GLOBAL Environment & Mining Services

Particulars of sample collected

: Vayubodhan Stack sampler / VSS-1

Sl. No: Stack Monitoring Kit/ 304-DTB-2007

5 Instrument Details : Calibration Date: 07.02.2022

Calibration Due Date: 06.02.2023

6 Discipline Chemical

7 Group : Atmospheric Pollution

8 Sample Type : Stack Monitoring

SEPTEMBER-2022 (1st Fort Night)

9 Month of Sampling

: 13.09.2022

10 Date of Sample Received

: 14.09.2022

Date of Sample Analysis 11

: 15.09.2022

12 **Date Sample Analysis Completion** 13 Report Issued Date

: 04.10.2022

Report Number

ULR-TC532322000000745F

RESULTS

Sl. No	Stack Attached to	Date of Monitoring	Sample Code	Fuel Used	Ta °C	TS °C	V m/Sec	Height (m)	Diameter (m)	PM mg/Nm³	KSPCB Std mg/Nm ³
	neys attached to Bag Filter (De ficiation Plant-2	e dusting Units)									
1	Iron Ore Cone Crusher	13.09.2022	2560		29	37	5.32	30	1.20	21.40	50
2	Iron Ore Screening	13.09.2022	2559		28	39	5.30	30	0.90	18.80	50

SI. No	Beneficiation Plant	Gas flow rate at Stack Condition m ³ /hr	Gas flow rate at NTP Nm³/hr	KSPCB Std
1	Iron Ore Cone Crusher	21663	20669	-
2	Iron Ore Screening	12140	11514	2

Parameter	Protocol
Particulate Matter (mg/Nm3)	IS: 11255 (Part 1) - 1985 (reaffirmed 2014)
Gas flow rate at Stack Condition	IS-11255(Part 03) (RA 2014)
Gas flow rate at NTP	IS-11255(Part 03) (RA 2014)

INFERENCE: The Measured Values are within the limits.

Rukmini G Chemist

Lingaraja B P Chemist

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied. Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.
- This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of Law & should not use any advertising media without special permission in writing
- Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only. Recognised by Ministry of Environment, Forest and Climate Change for Laboratory
- Recognised by Government of Karnataka, Maharashira, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

: +918394 229433, 295018

e-mail

: gems_hpt@yahoo.com

Website : www.globalmining.in



ANNEXURE-15 GEMS-LD/TF/10/01

Analysis Report of Stack Emission

Name of the Industry 1

Customer Reference 2

3 Sample collected by

4 Particulars of sample collected

5 **Instrument Details**

6 Discipline

7 Group

8 Sample Type

9 Month of Sampling

Date of Sample Received 10 11

Date of Sample Analysis **Date Sample Analysis Completion** 12

13 Report Issued Date

Report Number 14

: BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

WO/ADMIN/FY22/R038

: GLOBAL Environment & Mining Services

Vayubodhan Stack sampler / VSS-1

Sl. No: Stack Monitoring Kit/ 304-DTB-2007

: Calibration Date: 07.02.2022

Calibration Due Date: 06.02.2023

: Chemical

: Atmospheric Pollution

: Stack Monitoring

: SEPTEMBER-2022(1st Fort Night)

01.09.2022 & 02.09.2022

: 02.09.2022 & 03.09.2022

: 03.09.2022 & 05.09.2022

04.10.2022

: ULR-TC532322000000672F

RESULTS

Sl. No	Stack Attached to	Date of Monitoring	Sample Code	Fuel Used	Ta °C	TS °C	V m/Sec	Height (m)	Diameter (m)	PM mg/Nm³	KSPCB Std mg/Nm ³
Chin	nneys attached to Bag Filter (D	e dusting Units)									
Pelle	et Plant										
3	Additive grinding mill	01.09.2022	2374		29	39	4.84	6.0	0.50	26.70	50
4	Mixer building	01.09.2022	2373		29	38	5.21	6.0	0.35	38.10	50
5	Pellet discharge point	02.09.2022	2386		29	50	6.63	20	0.50	32.70	50

SI. No	Pellet Plant	Gas flow rate at Stack Condition m ³ /hr	Gas flow rate at NTP Nm³/hr	KSPCB Std
3	Additive grinding mill	3422	3247	•
4	Mixer building	1605	1716	(4)
5	Pellet discharge point	4667	4308	(#)

Parameter	Protocol
Particulate Matter (mg/Nm3)	IS: 11255 (Part 1) - 1985 (reaffirmed 2014)
Gas flow rate at Stack Condition	IS-11255(Part 03) (RA 2014)
Gas flow rate at NTP	IS-11255(Part 03) (RA 2014)

INFERENCE: The Measured Values are within the limits.

Rukmini G Chemist

Chemist

The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing.

Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only. Recognised by Ministry of Environment, Forest and Climate Change for Laboratory

Recognised by Government of Karnataka, Maharashira, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

: +918394 229433, 295018 : gems_hpt@yahoo.com e-mail

Website : www.globalmining.in



TC-5323

ANNEXURE-16 GEMS-LD/TF/10/01

Analysis Report of Stack Emission

Name of the Industry BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference** WO/ADMIN/FY22/RO38

3 Sample collected by **GLOBAL Environment & Mining Services**

Particulars of sample collected : Vayubodhan Stack sampler / VSS-1

Sl. No: Stack Monitoring Kit/304-DTB-2007

5 **Instrument Details** Calibration Date: 07.02.2022

Calibration Due Date: 06.02.2023

6 Discipline Chemical

7 Group Atmospheric Pollution 8 Sample Type Stack Monitoring

9 Month of Sampling SEPTEMBER-2022 (1st Fort Night) :

10 Date of Sample Received : 05.09.2022 & 06.09.2022 Date of Sample Analysis 11 06.09.2022 & 07.09.2022 12 **Date Sample Analysis Completion** : 07.09.2022 & 08.09.2022

13 Report Issued Date 04.10.2022

14 Report Number ULR-TC532322000000692F

RESULTS

Sl. No	Stack Attached to	Date of Monitoring	Sample Code	Fuel Used	Ta °C	TS °C	V m/Sec	Height (m)	Diameter (m)	PM mg/Nm³	KSPCB Std mg/Nm ³
Chin	nneys attached to Bag Filter (De o	lusting Units)									
2 X 5	500 TPD Sponge Iron Kiln 1 & 2										
6	Cooler Discharge -1	05.09.2022	2419		28	37	4.77	30	1.20	38.90	50
7	Cooler Discharge -2							30	1.20		50
8	Coal stock house	05.09.2022	2420		30	39	4.78	30	1.20	16.80	50
9	Production Separation bin1&2	06.09.2022	2445	5777	29	39	5.30	30	1.20	29.80	50
10	Production Separation bin3&4	06.09.2022	2446		29	41	7.85	30	1.20	24.30	50
11	Transfer House	06.09.2022	2444		28	37	5.46	30	1.20	26.20	50

SI. No	2 X 500 TPD Sponge Iron Kiln 1 & 2	Gas flow rate at Stack Condition m ³ /hr	Gas flow rate at NTP Nm³/hr	KSPCB Std
6	Cooler Discharge -1	19424	18478	•
7	Cooler Discharge -2			
8	Coal stock house	19464	18439	-
9	Production Separation bin-1&2	21582	20524	-
10	Production Separation bin-3&4	19749	18642	-
11	Transfer House	22233	21294	-

Parameter	Protocol
Particulate Matter (mg/Nm3)	IS: 11255 (Part 1) - 1985 (reaffirmed 2014)
Gas flow rate at Stack Condition	IS-11255(Part 03) (RA 2014)
Gas flow rate at NTP	IS-11255(Part 03) (RA 2014)

INFERENCE: The Measured Values are within the limits.

Pufly.
Analysed By Rukmini G Chemist

Lingaraja B F Chemist



- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

 Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

 This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing.

Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only. Recognised by Ministry of Environment, Forest and Climate Change for Laboratory

Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

: +918394 229433, 295018

: gems_hpt@yahoo.com Website : www.globalmining.in



TC-5323

ANNEXURE-17 GEMS-LD/TF/10/01

Analysis Report of Stack Emission

1 Name of the Industry BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference** WO/ADMIN/FY22/RO38

3 Sample collected by **GLOBAL Environment & Mining Services**

4 Particulars of sample collected Vayubodhan Stack sampler/ VSS-1

Sl. No: Stack Monitoring Kit/ 304-DTB-2007

5 Instrument Details Calibration Date: 07.02.2022

Calibration Due Date: 06.02.2023

6 Discipline Chemical

7 Group Atmospheric Pollution

8 Sample Type **Stack Monitoring**

9 Month of Sampling

10 Date of Sample Received SEPTEMBER-2022(1st Fort Night) 07.09.2022,08.09.2022 & 12.09.2022

Date of Sample Analysis 11

08.09.2022,09.09.2022 & 13.09.2022

Date Sample Analysis Completion 12

09.09.2022,10.09.2022 & 14.09.2022

13 Report Issued Date 04.10.2022

Report Number

ULR-TC532322000000712F

RESULTS

SI. No	Stack Attached to	Date of Monitoring	Sample Code	Fuel Used	Ta °C	TS °C	V m/s	Height (m)	Diameter (m)	PM mg/Nm³	KSPCB Std mg/Nm ³
Chim	neys attached to Bag Filter (De	dusting Units)						-			
2X50	00 TPD Sponge Iron Kiln 3&4										
12	Coal Primary Screen				-	-	-	30	1.20	•	50
13	Coal Stock House -1 & coal stock house-2	****			1,50	(*)	-	30	1.20	•	50
14	Cooler Discharge -1	07.09.2022	2468		29	38	5.00	30	1.30	21.10	50
15	Cooler Discharge - 2 & PSB transfer tower	07.09.2022	2469		30	39	5.68	30	1.4	35.90	50
16	Production Bunker & Intermediate bin	08.09.2022	2487	•••	29	38	5.39	35	1.90	30.50	50
17	Production Separation bin	08.09.2022	2488		28	39	5.76	35	1.90	28.60	50
18	Pellet Stock house				-	-	-	30	1.20	-	50
19	Dolochar Stock House 1 & 2				1.5	-	-	30	1.20		50
20	CPU Building	12.09.2022	2536		27	39	5.42	35	1.50	23.40	50

SI. No	2X500 TPD Sponge Iron Kiln 3&4	Gas flow rate at Stack Condition m³/hr	Gas flow rate at NTP Nm³/hr	KSPCB Std
12	Coal Primary Screen	-	-	-
13	Coal Stock House -1 & coal stock house-2	-	-	-
14	Cooler Discharge -1	23895	22770	***
15	Cooler Discharge -2 & PSB transfer tower	31481	29800	-
16	Production Bunker & Intermediate bin	55023	53431	
17	Production Separation bin	58800	56727	-
18	Pellet Stock house			(-)
19	Dolochar Stock House 1 & 2	-	-	
20	CPU Building	34485	32699	*

INFERENCE: The Measured Values are within the limits.



Lingaraja B Chemist

- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

 Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

 This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of knw & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

 Recognised by Ministry of Environment, Forest and Climate Change for Laboratory

 Recognised by Government of Karnataka, Maharashim, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

: +918394 229433, 295018

e-mail

: gems_hpt@yahoo.com Website : www.globalmining.in



TC-5323

ANNEXURE-18 GEMS-LD/TF/10/01

Analysis Report of Stack Emission

Name of the Industry

: BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference** : WO/ADMIN/FY22/RO38

3 Sample collected by : GLOBAL Environment & Mining Services

Particulars of sample collected

: Vayubodhan Stack sampler / VSS-1

Sl. No: Stack Monitoring Kit/304-DTB-2007

5 **Instrument Details** : Calibration Date: 07.02.2022

Calibration Due Date: 06.02,2023

6 Discipline

: Chemical

7 Group

Atmospheric Pollution :

8 Sample Type : Stack Monitoring

9 Month of Sampling : SEPTEMBER-2022(2ndFort Night)

10 Date of Sample Received : 22.09.2022

: 23.09.2022

Date of Sample Analysis 11 12 **Date Sample Analysis Completion**

: 24.09.2022

13 Report Issued Date

: 04.10.2022

14 Report Number ULR-TC532322000000833F

RESULTS

Sl. No	Stack Attached to	Date of Monitoring	Sample Code	Fuel Used	Ta °C	TS °C	V m/Sec	Height (m)	Diameter (m)	PM mg/Nm³	KSPCB Std mg/Nm ³
10000000	nneys attached to Bag Filter eficiation Plant-2	(De dusting Units	i)						(60000000000000000000000000000000000000		-
1	Iron Ore Cone Crusher	22.09.2022	2811		30	38	5.25	30	1.20	17.10	50
	If off of e cone crasher	22.07.2022	2011		30	36	3.23	30	1,20	17.10	30
2	Iron Ore Screening	22.09.2022	2812		31	36	5.14	30	0.90	20.30	50

SI. No	Beneficiation Plant	Gas flow rate at Stack Condition m ³ /hr	Gas flow rate at NTP Nm³/hr	KSPCB Std
1	Iron Ore Cone Crusher	21378	20398	-
2	Iron Ore Screening	11773	11284	-

Parameter	Protocol	
Particulate Matter (mg/Nm3)	IS: 11255 (Part 1) - 1985 (reaffirmed 2014)	
Gas flow rate at Stack Condition	IS-11255(Part 03) (RA 2014)	
Gas flow rate at NTP	IS-11255(Part 03) (RA 2014)	

INFERENCE: The Measured Values are within the limits.





- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied. Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.
- This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Bosapete jurisdiction only.
- Recognised by Ministry of Environment, Forest and Climate Change for Laboratory Recognised by Government of Karmataka, Maharashtra, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

: +918394 229433, 295018

e-mail

: gems_hpt@yahoo.com

Website

: www.globalmining.in



ANNEXURE-19 GEMS-LD/TF/10/01

Analysis Report of Stack Emission

1 Name of the Industry : BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference** WO/ADMIN/FY22/RO38

3 Sample collected by **GLOBAL Environment & Mining Services**

Particulars of sample collected 4

Vayubodhan Stack sampler/ VSS-1

Sl. No: Stack Monitoring Kit/ 304-DTB-2007

Instrument Details 5

Calibration Date: 07.02.2022

Calibration Due Date: 06.02.2023

6 Discipline

7

Chemical

Group

Atmospheric Pollution

8 Sample Type Stack Monitoring

Month of Sampling 9

10

: SEPTEMBER-2022(2ndFort Night)

Date of Sample Received

16.09.2022 & 19.09.2022

11 Date of Sample Analysis : 17.09.2022 & 20.09.2022

Date Sample Analysis Completion 12

: 17.09.2022 & 21.09.2022

Report Issued Date 13

04.10.2022

14 Report Number

: ULR-TC532322000000777F

RESULTS

Si. No	Stack Attached to	Date of Monitoring	Sample Code	Fuel Used	Ta °C	TS °C	V m/Sec	Height (m)	Diameter (m)	PM mg/Nm³	KSPCB Std mg/Nm ³
	neys attached to Bag Filte Plant	r (De dusting Un	its)								
3	Additive grinding mill	16.09.2022	2635		29	38	4.75	6.0	0.50	21.20	50
4	Mixer building	16.09.2022	2634		29	40	5.16	6.0	0.35	27.50	50
5	Pellet discharge point	19.09.2022	2720		28	40	6.13	20	0.50	29.60	50

SI. No	Pellet Plant	Gas flow rate at Stack Condition m³/hr	Gas flow rate at NTP Nm³/hr	KSPCB Std
3	Additive grinding mill	3358	3261	-
4	Mixer building	1787	1725	
5	Pellet discharge point	4334	4167	-

Parameter	Protocol
Particulate Matter (mg/Nm3)	IS: 11255 (Part 1) - 1985 (reaffirmed 2014)
Gas flow rate at Stack Condition	IS-11255(Part 03) (RA 2014)
Gas flow rate at NTP	IS-11255(Part 03) (RA 2014)

INFERENCE: The Measured Values are within the limits.



- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

 Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

 This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing.
- Total liability of our laboratory is limited to the invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only. Recognised by Ministry of Environment, Forest and Climate Change for Laboratory
- Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

: +918394 229433, 295018

e-mail : gems_hpt@yahoo.com Website : www.globalmining.in



ANNEXURE-20 GEMS-LD/TF/10/01

Analysis Report of Stack Emission

- 1 Name of the Industry
- 2 **Customer Reference**
- 3 Sample collected by
- Particulars of sample collected
- 5 Instrument Details
- 6 Discipline
- 7 Group
- 8 Sample Type
- 9 Month of Sampling
- 10 Date of Sample Received
- 11 Date of Sample Analysis
- **Date Sample Analysis Completion** 12
- 13 Report Issued Date
- Report Number 14

- : BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.
- WO/ADMIN/FY22/R038
- **GLOBAL Environment & Mining Services**
- Vayubodhan Stack sampler/ VSS-1
 - SI. No: Stack Monitoring Kit/304-DTB-2007
- Calibration Date: 07.02.2022
 - Calibration Due Date: 06.02.2023
- Chemical
- : Atmospheric Pollution
- : Stack Monitoring
- : SEPTEMBER-2022 (2ndFort Night)
- : 27.09.2022, 28.09.2022 & 29.09.2022
- : 28.09.2022, 29.09.2022 & 30.09.2022
- : 29.09.2022, 30.09.2022 & 30.09.2022
- 04.10.2022
- ULR-TC532322000000840F

RESULTS

Si. No	Stack Attached to	Date of Monitoring	Sample Code	Fuel Used	Ta °C	TS °C	V m/Sec	Height (m)	Diameter (m)	PM mg/Nm³	KSPCB Std mg/Nm ³
Chin	neys attached to Bag Filter (De d	usting Units)									2011
2 X 5	500 TPD Sponge Iron Kiln 1 & 2										
6	Cooler Discharge -1	27.09.2022	2879		30	36	4.77	30	1.20	25.60	50
7	Cooler Discharge -2	29.09.2022	2915		29	38	5.63	30	1.20	29.40	50
8	Coal stock house	28.09.2022	2902		27	38	4.99	30	1.20	12.40	50
9	Production Separation bin-1&2	28.09.2022	2901		30	39	5.45	30	1.20	30.50	50
10	Production Separation bin-3&4	29.09.2022	2914		27	40	4.87	30	1.20	32.10	50
11	Transfer House	28.09.2022	2903		29	37	5.37	30	1.20	29.60	50

SI. No	2 X 500 TPD Sponge Iron Kiln 1 & 2	Gas flow rate at Stack Condition m ³ /hr	Gas flow rate at NTP Nm³/hr	KSPCB Std
6	Cooler Discharge - 1	19424	18599	*
7	Cooler Discharge -2	22926	21814	
8	Coal stock house	20319	19409	•
9	Production Separation bin-1&2	22193	21080	
10	Production Separation bin-3&4	19831	18801	
11	Transfer House	21867	20937	

Parameter	Protocol	
Particulate Matter (mg/Nm3)	IS: 11255 (Part 1) - 1985 (reaffirmed 2014)	
Gas flow rate at Stack Condition	IS-11255(Part 03) (RA 2014)	
Gas flow rate at NTP	IS-11255(Part 03) (RA 2014)	

INFERENCE: The Measured Values are within the limits.







- The result listed refers only to the tested samples & applicable parameters. Endorsement of products is neither inferred nor implied.

 Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

 This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing. Total liability of our laboratory is limited to the Invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only.

 Recognised by Ministry of Environment, Forest and Climate Change for Laboratory
- Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey





(Consulting Engineers, Mine designers, Geologist & Surveyors) 3rd Main Road, Basaveswara Badavane,

HOSAPETE - 583201, Dist., Vijayanagara (Karnataka)

: +918394 229433, 295018

e-mail

: gems_hpt@yahoo.com

Website : www.globalmining.in



ANNEXURE-21 GEMS-LD/TF/10/01

Analysis Report of Stack Emission

Name of the Industry

BMM Ispat Ltd., Danapur, Hosapete Taluk, Vijayanagara District.

2 **Customer Reference** WO/ADMIN/FY22/RO38

3 Sample collected by **GLOBAL Environment & Mining Services** Vayubodhan Stack sampler / VSS-1

Particulars of sample collected 4

Sl. No: Stack Monitoring Kit/ 304-DTB-2007

Instrument Details 5

Calibration Date: 07.02.2022 Calibration Due Date: 06.02.2023

6 Discipline Chemical

7 Group 8

Atmospheric Pollution

Sample Type

Stack Monitoring

9 Month of Sampling

Date of Sample Received 10

SEPTEMBER-2022 (2nd Fort Night) 21.09.2022, 23.09.2022 & 24.09.2022

Date of Sample Analysis

22.09.2022, 24.09.2022 & 26.09.2022

Date Sample Analysis Completion 12

22.09.2022, 24.09.2022 & 26.09.2022

13 Report Issued Date 04.10.2022

Report Number 14

ULR-TC532322000000835F

RESULTS

SI. NO	Stack Attached to	Date of Monitoring	Sample Code	Fuel Used	Ta °C	TS °C	V m/s	Height (m)	Diameter (m)	PM mg/Nm³	KSPCB Std mg/Nm ³
Chir	nneys attached to Bag Filter (E	e dusting Units)				Allesearch L. C.		,			
2X5	00 TPD Sponge Iron Kiln 3&	4									
12	Coal Primary Screen	I			-		•	30	1.20	•	50
13	Coal Stock House -1 & coal stock house-2		***		-	-	-	30	1.20	-	50
14	Cooler Discharge -1	23.09.2022	2823		30	36	4.84	30	1.20	23.50	50
15	Cooler Discharge -2 & PSB transfer tower	23.09.2022	2824	***	31	39	5.58	30	1.20	31.70	50
16	Production Bunker & Intermediate bin	24.09.2022	2839		29	40	5.29	30	1.20	32.20	50
17	Production Separation bin	24.09.2022	2840		31	38	5.83	30	1.20	27.30	50
18	Pellet Stock house				-	-	-	30	1.20		50
19	Dolochar Stock House 1 & 2				-	-	-	30	1.20	•	50
20	CPU Building	21.09.2022	2780		28	38	5.32	35	1.50	18.90	50

SI. No	2X500 TPD Sponge Iron Kiln 3&4	Gas flow rate at Stack Condition m ³ /hr	Gas flow rate at NTP Nm³/hr	KSPCB Std
12	Coal Primary Screen			
13	Coal Stock House -1 & coal stock house-2			
14	Cooler Discharge -1	23130	22257	
15	Cooler Discharge - 2 & PSB transfer tower	30927	29411	100
16	Production Bunker & Intermediate bin	54002	52104	-
17	Production Separation bin	59515	58175	121
18	Pellet Stock house	•		-
19	Dolochar Stock House 1 & 2		(5)	-
20	CPU Building	33849	32760	6.8

INFERENCE: The Measured Values are within the limits.

Ruf 6. Rukmini G Chemist

Lingaraja B P Chemist

- The result listed refers only to the tested samples & applicable para neters. Endorsement of products is neither inferred nor implied.
- Water Samples will be destroyed after 15Days, Minerals 3 Months, Filter papers & Thimbles After analysis Discard.

 This report is not to be reproduced wholly or in part & cannot be used as evidence in the Court of law & should not use any advertising media without special permission in writing
- Total liability of our laboratory is limited to the invoice amount. Any dispute arising out of this report is subject to Hosapete jurisdiction only Recognised by Ministry of Environment, Forest and Climate Change for Laboratory
- Recognised by Government of Karnataka, Maharashtra, Goa for DGPS survey